

MINO 60 CURVE system

ceiling/ suspended


EN Circular segment of rolled aluminium profile, angular design, seamlessly welded; no visible screws; for lighting systems; powder coated; luminaire profile for mounting available in advance; remaining components mounted without tools; pendant fitting with cable suspension; height adjustment without tools; spring clip attachment to the luminaire; freely positionable; with feeder cable; light inset consisting of highly reflective coated die-cast aluminium for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; energy-eff. LEDs – very good colour rendering

FR Segment rond en profil d'aluminium roulé, version arête, soudé sans trace visible ; aucune vis visible ; pour les systèmes d'éclairage ; thermolaquée ; Profilé de luminaire pour montage livrable avant ; composants restants montable sans outil ; suspension par câble ; réglage en hauteur sans outil ; fixation au luminaire au moyen de clips à ressort ; positionnement libre ; conduit d'alimentation inclus ; élément lumineux composé d'aluminium moulé laqué hautement réfléchissant pour une gestion thermique améliorée ; cache HPO (High Performance Opal) pour éclairage homogène ; cache PMMA microprismatique, avec film dif-fusant inclus pour réduire la brillance avec un éclairage homogène ; LED à haut rend. énerg. – excellent rendu coul.

Quickinfo

3000K, 4000K
 CRI ≥ 80, 3 SDCM
 up to 2090lm/m
 up to 145lm/W
 L90 @ 50 000h
 non DIM, DALI-2
 opal, microprismatic

Types



Colours



Light distributions



DiiA® standards
 251, 252, 253

Order options

LED TYPE	
mid lumen	4
high lumen	5


COLOUR TEMPERATURE	
3000K	5
4000K	6

CONTROL	
non DIM	1
DALI-2 (only high lumen)	3

MATERIAL COLOUR	
<input type="radio"/> pure white RAL 9010	7
<input type="radio"/> white aluminium RAL 9006	G
<input type="radio"/> jet black RAL 9005	8
<input type="radio"/> special colours	X

LIGHT OPTIC COVER	
opal high performance	H
microprismatic	Z

MINO 60 CURVE ceiling / suspended



INSTALLATION CHANNEL + LIGHT INSET + LIGHT OPTIC COVER

SYSTEM POWER (MID/HIGH LUMEN)	R (mm)	ORDER CODE
10.4/ 13.8 W	500-90°	034-09 5
7.9/11.9 W	750-45°	034-09 0
16.1/ 22.1 W	750-90°	034-09 1
16.1/ 22.1 W	1500-45°	034-09 2
31/ 43 W (2×DALI)	1500-90°	034-09 3
31/ 43 W (2×DALI)	3000-45°	034-09 4

COVER	COLOUR TEMP.	SYSTEM POWER	DELIVERED LUMENS	EFFICACY
mid lumen/ opal	3000K	13 W/m	1670 lm/m	122 lm/W
high performance	4000K		1900 lm/m	135 lm/W
high lumen/ opal	3000K	19 W/m	2230 lm/m	120 lm/W
high performance	4000K		2540 lm/m	130 lm/W


Accessories

END CAPS



TYPE	ORDER CODE
end caps (pair)	034-090201

LINEAR CONNECTOR



TYPE	ORDER CODE
linear to curve profile	005-40159
curve to curve profile	005-40158
opal cover linear connector	006-14000

CEILING CLIP / CABLE SUSPENSION / CANOPY



TYPE	L (mm)	ORDER CODE
ceiling clip	10	034-11636
cable suspension	1500	005-2122110
canopy/feeder cable 3 × 1.5 mm ²	1500	005-221231
canopy/feeder cable 5 × 1.5 mm ²	1500	005-221241
cable rail	1200	005-2491110

for electrical system configuration see luminaire data sheet at xal.com

THROUGH WIRE

TYPE	ORDER CODE
3 × 1.5 mm ² (non DIM, 10 pieces)	004-90003
5 × 1.5 mm ² (DALI-2, 10 pieces)	004-90005