

# FINA SUPPORT lead 30°

011-1305118A



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Éclairage de vitrine , Sur pied \_\_\_\_\_

rotation 360° \_\_\_\_\_

noir , RAL 9021 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Intérieur \_\_\_\_\_

1020 lm \_\_\_\_\_

insert optique 92 lm/W<sup>2</sup> \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 97 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 96 , R<sub>(1-15)</sub>: 98 \_\_\_\_\_

MR 0.86 \_\_\_\_\_

MDER 0.78 \_\_\_\_\_

## Optique

asymmetric \_\_\_\_\_

## Electrique

sans driver \_\_\_\_\_

24 V \_\_\_\_\_

luminaire 14.6 W \_\_\_\_\_

insert optique 11.1 W \_\_\_\_\_

CP3 \_\_\_\_\_

19 W/m \_\_\_\_\_

24 V \_\_\_\_\_

## Physique

longueur 800 mm \_\_\_\_\_


largeur 9 mm \_\_\_\_\_

hauteur 9 mm \_\_\_\_\_

0.09 kg \_\_\_\_\_

<sup>1</sup> Code RAL <sup>2</sup> y compris la prise en compte des pertes optiques.

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage

