




HEX-O MODULE FLAT

suspended single + group


EN Hexagonal acoustic element made of high quality, self-supporting, at least 50% recycled PET felt with sound absorbing properties; in the dimensions of the HEX-O luminaires - with reduced height; suitable for single or group installation; pendant fitting with cable suspension (single: 3 cables / group: 1 cable); height adjustment without tools; including rear rail for alignment of the housings (group); can be combined with all HEX-O ceiling and TRIG-O ceiling luminaires and acoustic elements; improvement of room acoustics through absorption and scattering of sound waves; up to absorption class A

FR Élément acoustique hexagonal en feutre PET recyclé à 50 % au moins, autoportant, haute qualité, doué de propriétés insonorisantes ; dans les dimensions des luminaires HEX-O - à hauteur réduite ; adaptés pour montage individuel et groupé ; suspension par câble (single : 3 câbles / group : 1 câble) ; réglage en hauteur sans outil ; y compris un rail arrière pour l'alignement des corps (group) ; peut être combiné avec tous les plafonniers et éléments acoustiques HEX-O TRIG-O ; amélioration de l'acoustique grâce à l'absorption et à la dispersion du son ; jusqu'à la classe d'absorption A

Quickinfo

feutre PET
 PET felt (made of at least 50% post-consumer recycled material)
 SAC (sound absorption class) up to D
 fire resistance class: B-s1, d0, fire resistance class: not fire-retardant

Types





Couleur



modular system



wide range of colours



HEX-O MODULE FLAT suspended

A	B	C	D	E
$\alpha_w = 0.5$				



0.7
NRC

0.69
SAA

ACOUSTIC | SINGLE + GROUP

COLOUR

acoustic special colours

black

felt grey

marble grey

white

ORDER CODE

0 7 3 - 6 9 **L** 2 0 X

0 7 3 - 6 9 **L** 2 0 L

0 7 3 - 6 9 **L** 2 0 G


0 7 3 - 6 9 **L** 2 0 D

0 7 3 - 6 9 **L** 2 0 W


Equivalent sound absorption area (A_{eq} m²)

W-L (mm)	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz
650-750	0.03	0.1	0.27	0.4	0.5	0.43
866-1000	0.06	0.17	0.45	0.67	0.84	0.72

Sound absorption coefficients



Acoustic accessories (optional)



HEX-O ABSORBER 1000

COLOUR

marble grey

felt grey

black

white

acoustic special colours

L-W-H (mm)

1000-866-237

1000-866-237

1000-866-237

1000-866-237

1000-866-237

ORDER CODE

0 7 3 - 6 9 1 7 4 0 D

0 7 3 - 6 9 1 7 4 0 G

0 7 3 - 6 9 1 7 4 0 L

0 7 3 - 6 9 1 7 4 0 W

0 7 3 - 6 9 1 7 4 0 X

only in combination with HEX-O 750, MODULE 750 or MODULE FLAT 750; for acoustic data see xal.com

Order options

MOUNTING	L	LENGTH	L
suitable for single installation	2	750 mm	6
suitable for group installation	3	1000 mm	7