



UNICO L4 / L6 basic

ceiling


EN Rectangular surface mounted multi-downlight made of aluminium; equipped with four (L4) / six (L6) individually selectable or pre-specified, customised light elements; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high-quality reflector with micro-faceted, aluminium-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering; clank-free

FR Multi-downlight apparent rectangulaire, en aluminium ; équipé de quatre (L4) / six (L6) éléments optiques à choisir de façon personnalisée ou définis de manière fixe, spécifiques à chaque application ; corps de luminaire pouvant être monté sans outils sur la plaque de montage grâce à un système de verrouillage ; convertisseur intégré dans le corps de luminaire ; surface thermolaquée ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; caractéristique de diffusion précise avec différentes possibilités de répartitions symétriques de la lumière ; ou avec distribution asymétrique de la lumière ; High-Power-LED à grande efficacité énergétique, très bon rendu des couleurs ; sans distorsions

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI \geq 90 / 3 SDCM (initial MacAd)
 UGR \leq 10, UGR \leq 19
 jusqu'à 134 lm/W
 L85 / 50000 h, L90 / 50000 h
 DALI-2, non DIM
 IP20

Types



Couleur




Réflecteur




Répartition de la lumière




one luminaire
multiple scenes




black & gold
reflector
(optional)



tunable white
2700 – 5000 K
(optional)




UNICO L4 basic high efficient ceiling



FLOOD ROUND 46°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.3 W	2700 K	1750 lm	114 lm/W	0 9 0 - 1 L 4 9 ◊ C ■ 1 1
	3000 K	1830 lm	120 lm/W	0 9 0 - 1 L 4 0 ◊ C ■ 1 1
	3500 K	1830 lm	120 lm/W	0 9 0 - 1 L 4 2 ◊ C ■ 1 1
	4000 K	1900 lm	124 lm/W	0 9 0 - 1 L 4 1 ◊ C ■ 1 1



WIDE FLOOD ROUND 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.3 W	2700 K	1800 lm	118 lm/W	0 9 0 - 1 L 4 9 ◊ D ■ 1 1
	3000 K	1880 lm	123 lm/W	0 9 0 - 1 L 4 0 ◊ D ■ 1 1
	3500 K	1880 lm	123 lm/W	0 9 0 - 1 L 4 2 ◊ D ■ 1 1
	4000 K	1950 lm	127 lm/W	0 9 0 - 1 L 4 1 ◊ D ■ 1 1

FLOOD SQUARE 54°, CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.3 W	2700 K	1840 lm	120 lm/W	0 9 0 - 1 L 4 9 ◊ F ■ 1 1
	3000 K	1920 lm	125 lm/W	0 9 0 - 1 L 4 0 ◊ F ■ 1 1
	3500 K	1920 lm	125 lm/W	0 9 0 - 1 L 4 2 ◊ F ■ 1 1
	4000 K	1990 lm	130 lm/W	0 9 0 - 1 L 4 1 ◊ F ■ 1 1

WIDE FLOOD SQUARE 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.3 W	2700 K	1890 lm	124 lm/W	0 9 0 - 1 L 4 9 ◊ G ■ 1 1
	3000 K	1970 lm	129 lm/W	0 9 0 - 1 L 4 0 ◊ G ■ 1 1
	3500 K	1970 lm	129 lm/W	0 9 0 - 1 L 4 2 ◊ G ■ 1 1
	4000 K	2050 lm	134 lm/W	0 9 0 - 1 L 4 1 ◊ G ■ 1 1



UNICO L4 basic ceiling



SPOT ROUND 15°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1100 lm	57 lm/W	0 9 0 - 1 L 4 4 ◊ K ■ 0 0 1
	3000 K	1180 lm	61 lm/W	0 9 0 - 1 L 4 5 ◊ K ■ 0 0 1
	4000 K	1260 lm	65 lm/W	0 9 0 - 1 L 4 6 ◊ K ■ 0 0 1



NARROW MEDIUM ROUND 22°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1120 lm	58 lm/W	0 9 0 - 1 L 4 4 ◊ N ■ 0 0 1
	3000 K	1200 lm	62 lm/W	0 9 0 - 1 L 4 5 ◊ N ■ 0 0 1
	4000 K	1280 lm	66 lm/W	0 9 0 - 1 L 4 6 ◊ N ■ 0 0 1

Order options

CONTROL	◊	COLOUR	■	REFLECTOR	■
non DIM	1	gold dust RAL 260-M	9	chrome	0
DALI-2	3	jet black RAL 9005	B	black	B
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		

MEDIUM ROUND 33° , CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1500 lm	78 lm/W	0 9 0 - 1 L 4 4 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> 0 1
	3000 K	1600 lm	83 lm/W	0 9 0 - 1 L 4 5 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> 0 1
	4000 K	1710 lm	89 lm/W	0 9 0 - 1 L 4 6 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> 0 1

FLOOD ROUND 49° , CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1720 lm	89 lm/W	0 9 0 - 1 L 4 4 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> 0 1
	3000 K	1840 lm	95 lm/W	0 9 0 - 1 L 4 5 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> 0 1
	4000 K	1970 lm	102 lm/W	0 9 0 - 1 L 4 6 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> 0 1

WIDE FLOOD ROUND 72° , CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1710 lm	89 lm/W	0 9 0 - 1 L 4 4 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> 0 1
	3000 K	1820 lm	94 lm/W	0 9 0 - 1 L 4 5 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> 0 1
	4000 K	1950 lm	101 lm/W	0 9 0 - 1 L 4 6 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> 0 1

MEDIUM SQUARE 32° , CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1470 lm	76 lm/W	0 9 0 - 1 L 4 4 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> 0 1
	3000 K	1570 lm	81 lm/W	0 9 0 - 1 L 4 5 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> 0 1
	4000 K	1680 lm	87 lm/W	0 9 0 - 1 L 4 6 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> 0 1

FLOOD SQUARE 56° , CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1750 lm	91 lm/W	0 9 0 - 1 L 4 4 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> 0 1
	3000 K	1870 lm	97 lm/W	0 9 0 - 1 L 4 5 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> 0 1
	4000 K	2000 lm	104 lm/W	0 9 0 - 1 L 4 6 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> 0 1

WIDE FLOOD SQUARE 71° , CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1800 lm	93 lm/W	0 9 0 - 1 L 4 4 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> 0 1
	3000 K	1920 lm	99 lm/W	0 9 0 - 1 L 4 5 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> 0 1
	4000 K	2060 lm	107 lm/W	0 9 0 - 1 L 4 6 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> 0 1

WALLWASHER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1520 lm	79 lm/W	0 9 0 - 1 L 4 4 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 0 1
	3000 K	1620 lm	84 lm/W	0 9 0 - 1 L 4 5 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 0 1
	4000 K	1740 lm	90 lm/W	0 9 0 - 1 L 4 6 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 0 1

WALL FLOOR CORRIDOR CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1590 lm	82 lm/W	0 9 0 - 1 L 4 4 <input checked="" type="checkbox"/> W <input checked="" type="checkbox"/> 0 1
	3000 K	1690 lm	88 lm/W	0 9 0 - 1 L 4 5 <input checked="" type="checkbox"/> W <input checked="" type="checkbox"/> 0 1
	4000 K	1820 lm	94 lm/W	0 9 0 - 1 L 4 6 <input checked="" type="checkbox"/> W <input checked="" type="checkbox"/> 0 1

Order options


CONTROL		COLOUR		REFLECTOR	
non DIM	1	gold dust RAL 260-M	9	chrome	0
DALI-2	3	jet black RAL 9005	B	black	B
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		

WALL FLOOR CRI \geq 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
19.3 W	2700 K	1590 lm	82 lm/W	0 9 0 - 1 L 4 4 \blacklozenge W \blacksquare 0 2
	3000 K	1690 lm	88 lm/W	0 9 0 - 1 L 4 5 \blacklozenge W \blacksquare 0 2
	4000 K	1820 lm	94 lm/W	0 9 0 - 1 L 4 6 \blacklozenge W \blacksquare 0 2



UNICO L6 basic high efficient ceiling

FLOOD ROUND 46°, CRI \geq 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.0 W	2700 K	2640 lm	115 lm/W	0 9 0 - 1 L 6 9 \blacklozenge C \blacksquare 1 1
	3000 K	2750 lm	120 lm/W	0 9 0 - 1 L 6 0 \blacklozenge C \blacksquare 1 1
	3500 K	2750 lm	120 lm/W	0 9 0 - 1 L 6 2 \blacklozenge C \blacksquare 1 1
	4000 K	2860 lm	124 lm/W	0 9 0 - 1 L 6 1 \blacklozenge C \blacksquare 1 1

WIDE FLOOD ROUND 71°, CRI \geq 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.0 W	2700 K	2720 lm	118 lm/W	0 9 0 - 1 L 6 9 \blacklozenge D \blacksquare 1 1
	3000 K	2830 lm	123 lm/W	0 9 0 - 1 L 6 0 \blacklozenge D \blacksquare 1 1
	3500 K	2830 lm	123 lm/W	0 9 0 - 1 L 6 2 \blacklozenge D \blacksquare 1 1
	4000 K	2950 lm	128 lm/W	0 9 0 - 1 L 6 1 \blacklozenge D \blacksquare 1 1

FLOOD SQUARE 54°, CRI \geq 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.0 W	2700 K	2780 lm	121 lm/W	0 9 0 - 1 L 6 9 \blacklozenge F \blacksquare 1 1
	3000 K	2890 lm	126 lm/W	0 9 0 - 1 L 6 0 \blacklozenge F \blacksquare 1 1
	3500 K	2890 lm	126 lm/W	0 9 0 - 1 L 6 2 \blacklozenge F \blacksquare 1 1
	4000 K	3010 lm	131 lm/W	0 9 0 - 1 L 6 1 \blacklozenge F \blacksquare 1 1

WIDE FLOOD SQUARE 71°, CRI \geq 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.0 W	2700 K	2850 lm	124 lm/W	0 9 0 - 1 L 6 9 \blacklozenge G \blacksquare 1 1
	3000 K	2970 lm	129 lm/W	0 9 0 - 1 L 6 0 \blacklozenge G \blacksquare 1 1
	3500 K	2970 lm	129 lm/W	0 9 0 - 1 L 6 2 \blacklozenge G \blacksquare 1 1
	4000 K	3090 lm	134 lm/W	0 9 0 - 1 L 6 1 \blacklozenge G \blacksquare 1 1

Order options

CONTROL		\blacklozenge COLOUR		\blacksquare REFLECTOR	
non DIM	1	gold dust RAL 260-M	9	chrome	0
DALI-2	3	jet black RAL 9005	B	black	B
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		




UNICO L6 basic ceiling



SPOT ROUND 15°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	1610 lm	59 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> K <input checked="" type="checkbox"/> 0 0 1
	3000 K	1710 lm	63 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> K <input checked="" type="checkbox"/> 0 0 1
	4000 K	1840 lm	68 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> K <input checked="" type="checkbox"/> 0 0 1



NARROW MEDIUM ROUND 22°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	1630 lm	60 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> N <input checked="" type="checkbox"/> 0 0 1
	3000 K	1740 lm	64 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> N <input checked="" type="checkbox"/> 0 0 1
	4000 K	1870 lm	69 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> N <input checked="" type="checkbox"/> 0 0 1

MEDIUM ROUND 33°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2180 lm	80 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> 0 0 1
	3000 K	2320 lm	86 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> 0 0 1
	4000 K	2490 lm	92 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> B <input checked="" type="checkbox"/> 0 0 1

FLOOD ROUND 49°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2510 lm	93 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> 0 0 1
	3000 K	2670 lm	99 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> 0 0 1
	4000 K	2870 lm	106 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> C <input checked="" type="checkbox"/> 0 0 1

WIDE FLOOD ROUND 72°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2480 lm	92 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> 0 0 1
	3000 K	2650 lm	98 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> 0 0 1
	4000 K	2840 lm	105 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> D <input checked="" type="checkbox"/> 0 0 1

MEDIUM SQUARE 32°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2140 lm	79 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> 0 0 1
	3000 K	2280 lm	84 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> 0 0 1
	4000 K	2450 lm	90 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> E <input checked="" type="checkbox"/> 0 0 1

FLOOD SQUARE 56°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2550 lm	94 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> 0 0 1
	3000 K	2720 lm	100 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> 0 0 1
	4000 K	2920 lm	108 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> 0 0 1

RECTANGULAR MEDIUM 34°x69°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2210 lm	82 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> R <input checked="" type="checkbox"/> 0 0 1
	3000 K	2360 lm	87 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> R <input checked="" type="checkbox"/> 0 0 1
	4000 K	2530 lm	93 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> R <input checked="" type="checkbox"/> 0 0 1

Order options

CONTROL		◇ COLOUR	■ REFLECTOR	
non DIM	1	gold dust RAL 260-M	chrome	0
DALI-2	3	jet black RAL 9005	black	B
		white aluminium RAL 9006		G
		traffic white RAL 9016		W

WIDE FLOOD SQUARE 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2620 lm	97 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> 0 1
	3000 K	2790 lm	103 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> 0 1
	4000 K	3000 lm	111 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> G <input checked="" type="checkbox"/> 0 1

WALLWASHER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2220 lm	82 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 0 1
	3000 K	2360 lm	87 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 0 1
	4000 K	2540 lm	94 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> A <input checked="" type="checkbox"/> 0 0 1

WALL FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.1 W	2700 K	2310 lm	85 lm/W	0 9 0 - 1 L 6 4 <input checked="" type="checkbox"/> W <input checked="" type="checkbox"/> 0 1
	3000 K	2460 lm	91 lm/W	0 9 0 - 1 L 6 5 <input checked="" type="checkbox"/> W <input checked="" type="checkbox"/> 0 1
	4000 K	2640 lm	97 lm/W	0 9 0 - 1 L 6 6 <input checked="" type="checkbox"/> W <input checked="" type="checkbox"/> 0 1

Order options

CONTROL		<input checked="" type="checkbox"/> COLOUR	<input checked="" type="checkbox"/> REFLECTOR	
non DIM	1	gold dust RAL 260-M	9	chrome
DALI-2	3	jet black RAL 9005	B	black
		white aluminium RAL 9006	G	
		traffic white RAL 9016	W	

Planning Information

L4 CEILING


SPOT ROUND




NARROW MEDIUM ROUND




MEDIUM ROUND



FLOOD ROUND



WIDE FLOOD ROUND



MEDIUM SQUARE



WIDE FLOOD SQUARE



WALLWASHER



WALL FLOOR CORRIDOR



4x wallwasher floor

WALL + FLOOR




4x wallwasher floor

L6 CEILING


SPOT ROUND




NARROW MEDIUM ROUND




MEDIUM ROUND




FLOOD ROUND



WIDE FLOOD ROUND



MEDIUM SQUARE



FLOOD SQUARE



RECTANGULAR MEDIUM



WIDE FLOOD SQUARE



WALLWASHER



WALL + FLOOR



6x wallwasher floor

New Babylon, The Hague

Pays-Bas

Architecte
Studio Linse


Photographe
Kris Dekeijser



Produits utilisés



UNICO L4 / L6 basic
ceiling



MINO 60 CIRCLE
suspended

