

SASSO 100 round

ceiling


EN Cylindrical ceiling mounted spotlight made of aluminium; surface light inset lacquered; surface housing powder coated; luminaire housing can be attached to mounting plate without tools by interlock; light inset rotatable and tiltable; symmetric radiation characteristic - precise due to high quality lens system; with different beam angles; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; converter integrated into spotlight head

FR Spot de plafond cylindrique en aluminium ; surface de l'insert d'éclairage peinte ; surface du boîtier thermolaquée ; corps de luminaire pouvant être monté sans outils sur la plaque de montage grâce à un système de verrouillage ; module d'éclairage rotatif et orientable ; caractéristiques de rayonnement symétriques - précision grâce aux lentilles de grande qualité ; avec différents angles de rayonnement ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; convertisseur intégré à la tête de spot

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI \geq 90 / 2 SDCM
 UGR \leq 13, UGR \leq 16, UGR \leq 19
 jusqu'à 101 lm/W
 L80 / 50000 h
 DALI-2, non DIM
 IP20

Types



Couleur



Couleur intérieure



Répartition de la lumière



wallwasher and
wallwasher
floor inset



glare control
(UGR \leq 16)



easy mounting
no visible
screws




Colour Warm
Dimming 1800
- 3000 K
(optional)



CRI \geq 95 2
SDCM
(optional)



SASSO 100 round adjustable ceiling



SPOT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1450 lm	81 lm/W	0 4 8 - 3 4 1 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	3000 K	1490 lm	83 lm/W	0 4 8 - 3 4 1 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	3500 K	1530 lm	85 lm/W	0 4 8 - 3 4 1 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	4000 K	1560 lm	87 lm/W	0 4 8 - 3 4 1 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to inner colour traffic white.

MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1450 lm	81 lm/W	0 4 8 - 3 4 1 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	3000 K	1500 lm	84 lm/W	0 4 8 - 3 4 1 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	3500 K	1530 lm	85 lm/W	0 4 8 - 3 4 1 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	4000 K	1570 lm	88 lm/W	0 4 8 - 3 4 1 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M

The data values for the luminous flux may differ for specific order options by -7%. Luminous flux value refers to inner colour traffic white.

FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1600 lm	89 lm/W	0 4 8 - 3 4 1 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	3000 K	1650 lm	92 lm/W	0 4 8 - 3 4 1 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	3500 K	1690 lm	94 lm/W	0 4 8 - 3 4 1 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	4000 K	1730 lm	97 lm/W	0 4 8 - 3 4 1 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F

WIDE FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1670 lm	93 lm/W	0 4 8 - 3 4 1 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	3000 K	1720 lm	96 lm/W	0 4 8 - 3 4 1 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	3500 K	1760 lm	98 lm/W	0 4 8 - 3 4 1 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	4000 K	1800 lm	101 lm/W	0 4 8 - 3 4 1 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

Optical accessories (optional)



HONEYCOMB LOUVER

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 55 SASSO 100	jet black	50.3	0 0 7 - 1 9 6 5 5 9 8

Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white	7
				gold dust	9

Atelier Martin Auer, Graz

Autriche

Architecte

JANSER CASTORINA
KATZENBERGER

Photographe

Tim Ertl



Produits utilisés



STREAMCUT bollard



SASSO 100 round ceiling





Waterdrop Headquarters, Vienna

Autriche

Architecte


AllesWirdGut Architekten

Photographe

tschinkersten fotografie



Produits utilisés



JANE semi-recessed / surface / suspended



BETO suspended



SASSO 100 round ceiling



SASSO 100 round suspended

