



## SASSO 60 round

suspended


**EN** Cylindrical spotlight made of aluminium; surface light inset lacquered; surface housing powder coated; pendant fitting with cable suspension; incl. feed (black or white); can be individually shortened; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy

**FR** Spot cylindrique en aluminium ; surface de l'insert d'éclairage peinte ; surface du boîtier thermolaquée ; suspension par câble ; câble d'alimentation inclus (noir ou blanche) ; recoupable à volonté ; caractéristiques de rayonn. précises grâce à l'optique à lentille ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; cache-piton pour câblage continu ; convertisseur inclus dans le cache-piton

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
 CRI  $\geq$  90 / 2 SDCM (initial MacAdam)  
 UGR  $\leq$  13, UGR  $\leq$  16, UGR  $\leq$  19  
 jusqu'à 94 lm/W  
 L80 / 50000 h  
 DALI-2, non DIM  
 IP20

### Types



### Couleur



### Couleur intérieure



### Répartition de la lumière



glare control  
(UGR  $\leq$  16)



easy mounting  
no visible  
screws



CRI  $\geq$  95 2  
SDCM  
(optional)




## SASSO 60 round downlight suspended



### SPOT 15°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.4 W	2700 K	754 lm	73 lm/W	0 4 8 - 3 1 H 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	3000 K	778 lm	75 lm/W	0 4 8 - 3 1 H 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	3500 K	795 lm	76 lm/W	0 4 8 - 3 1 H 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	4000 K	819 lm	79 lm/W	0 4 8 - 3 1 H 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S

The data values for the luminous flux may differ for specific order options by -7%. Luminous flux value refers to inner colour traffic white.



### MEDIUM 26°-27°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	888 lm	87 lm/W	0 4 8 - 3 1 H 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	3000 K	921 lm	90 lm/W	0 4 8 - 3 1 H 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	3500 K	941 lm	92 lm/W	0 4 8 - 3 1 H 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	4000 K	961 lm	94 lm/W	0 4 8 - 3 1 H 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M

The data values for the luminous flux may differ for specific order options by -9%. Luminous flux value refers to inner colour traffic white.

### FLOOD 40°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	845 lm	83 lm/W	0 4 8 - 3 1 H 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	3000 K	877 lm	86 lm/W	0 4 8 - 3 1 H 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	3500 K	896 lm	88 lm/W	0 4 8 - 3 1 H 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	4000 K	915 lm	90 lm/W	0 4 8 - 3 1 H 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F

The data values for the luminous flux may differ for specific order options by -14%. Luminous flux value refers to inner colour traffic white.

### WIDE FLOOD 56°-57°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	887 lm	87 lm/W	0 4 8 - 3 1 H 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	3000 K	920 lm	90 lm/W	0 4 8 - 3 1 H 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	3500 K	941 lm	92 lm/W	0 4 8 - 3 1 H 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	4000 K	961 lm	94 lm/W	0 4 8 - 3 1 H 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.

### Order options

HEIGHT	H	CONTROL	COLOUR	INNER COLOUR
75 mm	2	non DIM	1 jet black RAL 9005	1 jet black RAL 9005
150 mm	7	DALI-2	3 traffic white RAL 9016	7 matt silver
				4 traffic white RAL 9016
				7 gold dust RAL 260-M
				9

# James Good Coiffeur LoungeaJames Good For You GmbH, Flums

Suisse

## Architecte

Daniel Huber Architektur  
GmbH

## Lighting Design

Daniel Huber Architektur  
GmbH

## Photographe

Bruno Helbling



## Produits utilisés



**SASSO 60 round  
suspended**



**TULA suspended**



