


Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 13, UGR ≤ 16, UGR ≤ 19, UGR ≤ 22, UGR ≤ 25
jusqu'à 94 lm/W
L90 / 100000 h
DALI-2, non DIM
IP20

Types



Colours

Couleur intérieure

Répartition de la lumière

SASSO 60 round

suspended

EN Cylindrical spotlight made of aluminium; surface light inset lacquered; surface housing powder coated; pendant fitting with cable suspension; incl. feed (black or white); can be individually shortened; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy

FR Spot cylindrique en aluminium ; surface de l'insert d'éclairage peinte ; surface du boîtier thermolaquée ; suspension par câble ; câble d'alimentation inclus (noir ou blanche) ; recoupable à volonté ; caractéristiques de rayonn. précises grâce à l'optique à lentille ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; cache-piton pour câblage continu ; convertisseur inclus dans le cache-piton



glare control
(UGR ≤ 16)




easy mounting
no visible
screws




CRI ≥ 95 2
SDCM
(optional)









SASSO 60 round downlight suspended

CRI ≥ 90 | 2 SDCM | UGR ≤ 13 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SPOT 15°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.4 W	2700 K	754 lm	73 lm/W	0 4 8 - 3 1 H 0 9 ◪ ■ S
	3000 K	778 lm	75 lm/W	0 4 8 - 3 1 H 0 0 ◪ ■ S
	3500 K	795 lm	76 lm/W	0 4 8 - 3 1 H 0 2 ◪ ■ S
	4000 K	819 lm	79 lm/W	0 4 8 - 3 1 H 0 1 ◪ ■ S

The data values for the luminous flux of fraction may differ for specific order options by -7%. Luminous flux value refers to inner colour traffic white.

MEDIUM 26°-27°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	888 lm	87 lm/W	0 4 8 - 3 1 H 0 9 ◪ ■ M
	3000 K	921 lm	90 lm/W	0 4 8 - 3 1 H 0 0 ◪ ■ M
	3500 K	941 lm	92 lm/W	0 4 8 - 3 1 H 0 2 ◪ ■ M
	4000 K	961 lm	94 lm/W	0 4 8 - 3 1 H 0 1 ◪ ■ M

The data values for the luminous flux of fraction may differ for specific order options by -9%. Luminous flux value refers to inner colour traffic white.

FLOOD 40°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	845 lm	83 lm/W	0 4 8 - 3 1 H 0 9 ◪ ■ F
	3000 K	877 lm	86 lm/W	0 4 8 - 3 1 H 0 0 ◪ ■ F
	3500 K	896 lm	88 lm/W	0 4 8 - 3 1 H 0 2 ◪ ■ F
	4000 K	915 lm	90 lm/W	0 4 8 - 3 1 H 0 1 ◪ ■ F

The data values for the luminous flux of fraction may differ for specific order options by -14%. Luminous flux value refers to inner colour traffic white.

WIDE FLOOD 56°-57°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	887 lm	87 lm/W	0 4 8 - 3 1 H 0 9 ◪ ■ W
	3000 K	920 lm	90 lm/W	0 4 8 - 3 1 H 0 0 ◪ ■ W
	3500 K	941 lm	92 lm/W	0 4 8 - 3 1 H 0 2 ◪ ■ W
	4000 K	961 lm	94 lm/W	0 4 8 - 3 1 H 0 1 ◪ ■ W

The data values for the luminous flux of fraction may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.

Order options

HEIGHT H	CONTROL ⇕	COLOUR ◪	INNER COLOUR ■
75 mm 2	non DIM 1	jet black RAL 9005 1	jet black RAL 9005 1
150 mm 7	DALI-2 3	traffic white RAL 9016 7	matt silver 4
			traffic white RAL 9016 7
			gold dust RAL 260-M 9

James Good Coiffeur LoungeaJames Good For You GmbH, Flums

Suisse

Architecte
Daniel Huber Architektur GmbH

Lighting Design
Daniel Huber Architektur GmbH

Photographe
Bruno Helbling




Produits utilisés



SASSO 60 round suspended



TULA suspended



SASSO 60 round downlight recessed 1 lamp

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com






SHU UEMURA
SHU UEMURA
SHU UEMURA

