


## Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 16, UGR ≤ 19
jusqu'à ↓ 9 370 lm / ↑ 4 370 lm
jusqu'à 138 lm/W
L80 / 50000 h, L90 / 50000 h
Cache : Microprismatic
DALI-2
IP40

### Types




### Colours



### Répartition de la lumière



# **TASK** round


suspended

EN Round luminaire housing in aluminium; ultra low-profile design (only 15 mm); surface powder coated; pendant fitting with cable suspension; with integrated toolless suspension height adjustment; incl. feeder cable or with height adjustable rod suspension (chrome), feed in rod; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; optional: indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; canopy for through wiring; sound absorbing accessories available

FR Corps de luminaire rond en aluminium ; forme extrêm. plate (15 mm seulement) ; surface thermolaquée ; suspension par câble ; réglage en hauteur sans outil au luminaire ; incl. conduit d'alimentation ou avec suspension pouvant être raccourcie (chrome), conduit d'alimentation dans le tube de suspension ; distribution de lumière directe par LGP-Body (Light Guiding Prism) ; lumière couplée latéralement guidée vers le bas par gravure laser ; guidage lumière au moyen de matériau réflecteur hautement réfléchissant ; en option : partie indirecte avec platines dédiées pour un flux lumineux accru et un éclairage maximal du plafond ; éclairage parfaitement homogène ; LED économes en énergie à restitution de couleur élevée ; cache-piton pour câblage continu ; accessoires doté de propriétés d'absorption acoustique




DiiA® standards
251, 252, 253




DIN EN 12464-1
UGR ≤ 19



direct / indirect
illumination





acoustic
elements



CRI ≥ 98
XPECTRUM
(optional)






## **TASK 450** round suspended

CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | DALI 1 ADDR. | IP40 | X-PERT | X-PERT


**MICROPRISMATIC | DIRECT** CRI ≥ 90, DALI-2


| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 16.0 W | 3000 K | 1750 lm | 109 lm/W | 059-0ơ4103◪P |
| | 4000 K | 1860 lm | 116 lm/W | 059-0ơ4113◪P |

**MICROPRISMATIC | DIRECT / INDIRECT POWER** CRI ≥ 90, DALI-2

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 37.0 W | 3000 K | ↧2710/↥1460 lm | 113 lm/W | 059-0ơ6103◪P |
| | 4000 K | ↧2880/↥1550 lm | 120 lm/W | 059-0ơ6113◪P |






## **TASK 600** round suspended

CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤3000 | 220-240 V | DALI 1 ADDR. | IP40 | X-PERT | X-PERT


**MICROPRISMATIC | DIRECT** CRI ≥ 90, DALI-2


| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 29.6 W | 3000 K | 3470 lm | 117 lm/W | 059-0ơ4203◪P |
| | 4000 K | 3690 lm | 125 lm/W | 059-0ơ4213◪P |

**MICROPRISMATIC | DIRECT / INDIRECT POWER** CRI ≥ 90, DALI-2

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 44.0 W | 3000 K | ↧3470/↥1770 lm | 119 lm/W | 059-0ơ6203◪P |
| | 4000 K | ↧3690/↥1880 lm | 127 lm/W | 059-0ơ6213◪P |






## **TASK 900** round suspended

CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | DALI 1-2 ADDR. | IP40 | X-PERT | X-PERT

**MICROPRISMATIC | DIRECT** CRI ≥ 90, DALI-2

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 51.0 W | 3000 K | 6630 lm | 130 lm/W | 059-0ơ4303◪K |
| | 4000 K | 7060 lm | 138 lm/W | 059-0ơ4313◪K |

**MICROPRISMATIC | DIRECT / INDIRECT POWER** CRI ≥ 90, DALI-2

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 100.0 W | 3000 K | ↧8800/↥4110 lm | 129 lm/W | 059-0ơ6303◪K |
| | 4000 K | ↧9370/↥4370 lm | 137 lm/W | 059-0ơ6313◪K |

### Order options

| MOUNTING | ơ |
|---|---|
| cable 1500 mm | 2 |
| rod 1000 mm | 4 |

| COLOUR | ◪ |
|---|---|
| pure white RAL 9010 | 7 |
| jet black RAL 9005 | 8 |
| special colours | X |