

TASK square

surface


EN Square housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; convenient quick mounting system without tools; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring; sound absorbing accessories available

FR Corps du luminaire carré en aluminium avec bords arrondis ; forme extrêm. plate (15mm seulement) ; surface thermolaquée ; système de montage rapide, convivial et sans outil ; distribution de lumière directe par LGP-Body (Light Guiding Prism) ; lumière couplée latéralement guidée vers le bas par gravure laser ; guidage lumière au moyen de matériau réflecteur hautement réfléchissant ; éclairage parfaitement homogène ; LED économes en énergie à restitution de couleur élevée ; luminaire avec 2 ouvertures câblage et borne enfichable pour câblage passant ; accessoires doté de propriétés d'absorption acoustique

Quickinfo

3000 K, 4000 K
 CRI ≥ 90 / 3 SDCM (initial MacAdam)
 UGR ≤ 19
 jusqu'à 137 lm/W
 L90 / 50000 h
 DALI-2
 Microprismatic
 IP20

Types



Couleur



Répartition de la lumière




DiA® standards
 251, 252, 253




DIN EN 12464-1
 UGR ≤ 19




easy mounting




acoustic elements



CRI ≥ 98 XPECTRUM
 (optional)





TASK 320 square surface




MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.8 W	3000 K	1230 lm	114 lm/W	0 5 9 - 2 1 1 0 0 3 <input checked="" type="checkbox"/> K
	4000 K	1310 lm	121 lm/W	0 5 9 - 2 1 1 0 1 3 <input checked="" type="checkbox"/> K





TASK 450 square surface




MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.0 W	3000 K	1880 lm	125 lm/W	0 5 9 - 2 1 4 1 0 3 <input checked="" type="checkbox"/> K
	4000 K	2000 lm	133 lm/W	0 5 9 - 2 1 4 1 1 3 <input checked="" type="checkbox"/> K




TASK 600 square surface



MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2



SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.3 W	3000 K	3510 lm	129 lm/W	0 5 9 - 2 1 4 2 0 3 <input checked="" type="checkbox"/> K
	4000 K	3730 lm	137 lm/W	0 5 9 - 2 1 4 2 1 3 <input checked="" type="checkbox"/> K



Order options

COLOUR	<input checked="" type="checkbox"/>
special colours	X
pure white RAL 9010	7
jet black RAL 9005	8

Planning Information



TASK 600 square surface
27.3W, 4000K, direct

ROOM VALUES

Room dimensions 5.4 × 4 × 2.8 m
Reflection factor 0.7 | 0.5 | 0.2
Maintenance factor 0.8

CALCULATION SURFACE

Surface dimensions 1.6 × 0.8 m
Surface height 0.75 m
Average illuminance (E_m) > 500 lx
Uniformity (U_0) > 0.6

GLARE EVALUATION

Table Classification X=4H | Y=8H | S=0.25H
UGR transversal ≤ 19
UGR axial ≤ 19
≥ 65° ≤ 3000 cd/m²

Order options

COLOUR	<input checked="" type="checkbox"/>
special colours	X
pure white RAL 9010	7
jet black RAL 9005	8