




**Quickinfo**

3000 K, 4000 K, tunable white  
 2700 - 6500 K  
 CRI ≥ 80, CRI ≥ 90 / 3 SDCM  
 (initial MacAdam)  
 UGR ≤ 19  
 jusqu'à 131 lm/W  
 L85 / 50000 h, L90 / 50000 h  
 DALI-2  
 Microprismatic  
 IP20

**Types**



**Couleur**



**Répartition de la lumière**



**TASK**

ceiling

**EN** Rectangular housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; convenient quick mounting system without tools; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**FR** Corps du luminaire rectangulaire en aluminium avec bords arrondis ; forme extrêm. plate (15mm seulement) ; surface thermolaquée ; système de montage rapide, convivial et sans outil ; distribution de lumière directe par LGP-Body (Light Guiding Prism) ; lumière couplée latéralement guidée vers le bas par gravure laser ; guidage lumière au moyen de matériau réflecteur hautement réfléchissant ; éclairage parfaitement homogène ; LED économes en énergie à restitution de couleur élevée ; luminaire avec 2 ouvertures câblage et borne enfichable pour câblage passant




Dii® standards  
 251, 252, 253




DIN EN 12464-1  
 UGR ≤ 19



tunable white  
 2700 – 6500 K



CRI ≥ 98  
 XPECTRUM  
 (optional)





### TASK 1200 ceiling



#### MICROPRISMATIC | DIRECT DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
28.4 W	3000 K, CRI ≥ 90	3440 lm	121 lm/W	0 5 9 - 2 1 1 4 0 3 <input checked="" type="checkbox"/> K
	4000 K, CRI ≥ 90	3660 lm	129 lm/W	0 5 9 - 2 1 1 4 1 3 <input checked="" type="checkbox"/> K
29.2 W	tunable w., CRI ≥ 80	3470 lm	119 lm/W	0 5 9 - 2 1 1 4 D 3 <input checked="" type="checkbox"/> K




### TASK 1500 ceiling




#### MICROPRISMATIC | DIRECT DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
35.0 W	3000 K, CRI ≥ 90	4300 lm	123 lm/W	0 5 9 - 2 1 1 5 0 3 <input checked="" type="checkbox"/> K
	4000 K, CRI ≥ 90	4570 lm	131 lm/W	0 5 9 - 2 1 1 5 1 3 <input checked="" type="checkbox"/> K
36.0 W	tunable w., CRI ≥ 80	4330 lm	120 lm/W	0 5 9 - 2 1 1 5 D 3 <input checked="" type="checkbox"/> K




## Planning Information



**TASK 1500 ceiling**  
36W, 4000K, direct

**ROOM VALUES**  
Room dimensions 5.4 × 4 × 2.8 m  
Reflection factor 0.7 | 0.5 | 0.2  
Maintenance factor 0.8

**CALCULATION SURFACE** .....  
Surface dimensions 1.6 × 0.8 m  
Surface height 0.75 m  
Average illuminance (E<sub>m</sub>) > 500 lx  
Uniformity (U<sub>0</sub>) > 0.6



**GLARE EVALUATION**  
Table Classification X=4H | Y=8H | S=0.25H  
UGR transversal ≤ 19  
UGR axial ≤ 19  
≥ 65° ≤ 3000 cd/m²

### Order options

COLOUR	<input checked="" type="checkbox"/>
special colours	X
pure white RAL 9010	7
jet black RAL 9005	8