
Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
jusqu'à 3 280 lm/m
jusqu'à 142 lm/W
L90 / 50000 h
Cache : Clear Cover, Opal
DALI-2
IP20

Types



Colours



Répartition de la lumière



TUBO 60

surface

EN Supporting profile in extruded aluminium; end cap in aluminium; surface raw or powder coated; suitable for wall or ceiling mounting; light control via high quality lens system for maximum, homogeneous illumination; optionally cylindr. opal cover or clear, cylindrical cover with linear prismatic optic; energy-efficient LEDs with very good colour rendering

FR Profilé portant en profil extrudé en aluminium ; couvercle final en aluminium ; surface brute ou thermolaquée ; convient au montage mur ou plafond ; conduction de la lumière par optique à lentille pour un éclairage max. et homogène ; en option, cache cylindr. opale ou diffuseur cylindrique clair avec optique à prismes linéaires ; LED économes en énergie à restitution de couleur élevée




driver integrated



system solution



uniform illumination



TUBO 60 opal surface

CRI ≥90 · 220-240 V · 1 ADDR. · X-PERT · X-PERT



OPAL DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
13.9 W	625 mm	3000 K	80	1700 lm	122 lm/W	058-311253 ◪ O
			90	1480 lm	106 lm/W	058-311203 ◪ O
		4000 K	80	1810 lm	130 lm/W	058-311263 ◪ O
			90	1480 lm	106 lm/W	058-311213 ◪ O
27.9 W	1210 mm	3000 K	80	3400 lm	122 lm/W	058-311453 ◪ O
			90	2960 lm	106 lm/W	058-311403 ◪ O
		4000 K	80	3620 lm	130 lm/W	058-311463 ◪ O
			90	2960 lm	106 lm/W	058-311413 ◪ O
34.0 W	1500 mm	3000 K	80	4220 lm	124 lm/W	058-311553 ◪ O
			90	3670 lm	108 lm/W	058-311503 ◪ O
		4000 K	80	4490 lm	132 lm/W	058-311563 ◪ O
			90	3670 lm	108 lm/W	058-311513 ◪ O
54.0 W	2375 mm	3000 K	80	6740 lm	125 lm/W	058-311853 ◪ O
			90	5870 lm	109 lm/W	058-311803 ◪ O
		4000 K	80	7170 lm	133 lm/W	058-311863 ◪ O
			90	5870 lm	109 lm/W	058-311813 ◪ O



TUBO 60 ribbed surface

CRI ≥90 · 220-240 V · 1 ADDR. · X-PERT · X-PERT



CLEAR COVER WITH LINEAR PRISMATIC OPTIC DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
13.9 W	625 mm	3000 K	80	1820 lm	131 lm/W	058-511253 ◪ C
			90	1580 lm	114 lm/W	058-511203 ◪ C
		4000 K	80	1940 lm	140 lm/W	058-511263 ◪ C
			90	1580 lm	114 lm/W	058-511213 ◪ C
27.9 W	1210 mm	3000 K	80	3640 lm	130 lm/W	058-511453 ◪ C
			90	3170 lm	114 lm/W	058-511403 ◪ C
		4000 K	80	3870 lm	139 lm/W	058-511463 ◪ C
			90	3170 lm	114 lm/W	058-511413 ◪ C
34.0 W	1500 mm	3000 K	80	4510 lm	133 lm/W	058-511553 ◪ C
			90	3930 lm	116 lm/W	058-511503 ◪ C
		4000 K	80	4800 lm	141 lm/W	058-511563 ◪ C
			90	3930 lm	116 lm/W	058-511513 ◪ C
54.0 W	2375 mm	3000 K	80	7210 lm	134 lm/W	058-511853 ◪ C
			90	6280 lm	116 lm/W	058-511803 ◪ C
		4000 K	80	7680 lm	142 lm/W	058-511863 ◪ C
			90	6280 lm	116 lm/W	058-511813 ◪ C

Order options

COLOUR	◪
pure white RAL 9010	7
jet black RAL 9005	8
aluminium raw	R