



TASK

table


EN Desk lamp in puristic design with high functionality; lamp head 360° rotatable and +/- 15° tiltable; surface powder coated; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; continuously adjustable dimming via optical sensor (10-100% analog); integrated USB charging socket for charging of a smart device; version with presence detector

FR Lampe de bureau au design épuré et hautement fonctionnel ; tête de luminaire pivotant à 360° et orientable à +/- 15° ; surface thermolaquée ; distribution de lumière directe par LGP-Body (Light Guiding Prism) ; lumière couplée latéralement guidée vers le bas par gravure laser ; éclairage parfaitement homogène ; LED économes en énergie à restitution de couleur élevée ; gradation en continu grâce à un capteur optique (10-100% analogue) ; prise de chargement USB intégrée pour le chargement d'un Smart Device ; version avec capteur de présence

Quickinfo

3000 K, 4000 K
CRI $\geq$ 90 / 3 SDCM (initial MacAdam)
jusqu'à 100 lm/W
L95 / 50000 h
touch DIM / capteur autonome
Opal
IP20

Types




Colours



Montage



Répartition de la lumière



360° rotatable,
 $\pm$ 15° tiltable




presence
sensor



USB charging
socket




TASK table




OPAL | DIRECT CRI ≥ 90, touch DIM / stand alone sensor

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.1 W	3000 K	950 lm	94 lm/W	0 5 9 - 2 8 1 1 0 7 ☒ O
	4000 K	1010 lm	100 lm/W	0 5 9 - 2 8 1 1 1 7 ☒ O



Mounting accessories (required)



BASE PLATE

Ø-H (mm)	ORDER CODE
220·13	0 5 9 - 2 8 9 1 1 1 ☒



TABLE CLAMP height 77-88 mm

Ø (mm)	ORDER CODE
75	0 5 9 - 2 8 9 2 1 1 ☒

for hole ø68 mm, 10–30 mm range

Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8