


Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
jusqu'à 147 lm/W
L85 / 50000 h
DALI-2, non DIM
Opal
IP54, IK07

Types



Colours

Répartition de la lumière

SONO IP54

surface

EN Round luminaire housing in die-cast aluminium; surface powder coated; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

FR Corps de luminaire rond en fonte d'aluminium injectée ; surface thermolaquée ; convient au montage mur ou plafond ; cache PMMA, à éclairage parfaitement homogène, satiné ; luminance identique pour toutes les variantes de taille ; LED économes en énergie à restitution de couleur élevée ; luminaire avec 2 ouvertures câblage et borne enfichable pour câblage passant



DiiA® standards 251, 252, 253



easy mounting by click-mechanism



dust & insect protection (IP 54)




tunable white 2700 – 6500 K (optional)

SONO 260 ip54 surface

CRI ≥ 80 | UGR ≤ 22 | 220-240 V | DALI 1 ADDR. | IP54 | IK07 | X-PERT

OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.0 W	3000 K	950 lm	136 lm/W	871-91265 ◆ 70
	4000 K	1010 lm	144 lm/W	871-91266 ◆ 70




SONO 350 ip54 surface

CRI ≥ 80 | 220-240 V | DALI 1 ADDR. | IP54 | IK07 | X-PERT

OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.9 W	3000 K	2090 lm	131 lm/W	871-91365 ◆ 70
	4000 K	2210 lm	139 lm/W	871-91366 ◆ 70




SONO 450 ip54 surface

CRI ≥ 80 | UGR ≤ 22 | 220-240 V | DALI 1 ADDR. | IP54 | IK07 | X-PERT

OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.2 W	3000 K	3060 lm	132 lm/W	871-91465 ◆ 70
	4000 K	3240 lm	140 lm/W	871-91466 ◆ 70




Order options

CONTROL ◆	
non DIM	1
DALI-2	3

COLOUR	
pure white	RAL 9010





SONO 600 ip54 surface

CRI ≥ 80 | 220-240 V | DALI 1 ADDR. | IP54 | X-PERT

OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
42.0 W	3000 K	5830 lm	139 lm/W	871-91565 ⬍ 7O
	4000 K	6170 lm	147 lm/W	871-91566 ⬍ 7O

Mounting tools accessories

DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	086-30000

Order options

CONTROL ⬍	
non DIM	1
DALI-2	3

COLOUR	
pure white	RAL 9010