



TWIST 100 2 lamps

recessed

EN Round recessed spotlight in die-cast aluminium; powder coated; installation without tools in mounting set with ball catch system; with trim; double lamps; 360° rotatable and 45° tiltable outward; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high quality reflector with spherical facet finish; precise radiation characteristic

FR Spot rond encastrable en fonte d'aluminium injectée ; thermolaquée ; montage sans outil en kit de montage par système à déclic à bille ; avec bord continu ; biflamme ; rotatif à 360° et pivotant à 45° ; Technologie COB (Chip on Board) pour efficacité maximale ; pas de formation d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; réflecteur de grande qualité avec optique facette sphérique ; caractéristique de rayonnement précise

Quickinfo

3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
jusqu'à 141 lm/W
L80 / 50000 h
DALI-2, non DIM
front IP20, back IP20

Types

double trim



Couleur



Set de montage



Répartition de la lumière



360° rotatable,
45° tiltable



TWIST 100 trim 2 lamps



SPOT 20°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x22.7 W,	3000 K	2x3100 lm	136 lm/W	0 4 8 - 1 1 2 1 0 1 <input checked="" type="checkbox"/> S
650 mA	3500 K	2x3140 lm	138 lm/W	0 4 8 - 1 1 2 1 2 1 <input checked="" type="checkbox"/> S
	4000 K	2x3140 lm	138 lm/W	0 4 8 - 1 1 2 1 1 1 <input checked="" type="checkbox"/> S




MEDIUM 27°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x22.7 W,	3000 K	2x3150 lm	139 lm/W	0 4 8 - 1 1 2 1 0 1 <input checked="" type="checkbox"/> M
650 mA	3500 K	2x3190 lm	140 lm/W	0 4 8 - 1 1 2 1 2 1 <input checked="" type="checkbox"/> M
	4000 K	2x3200 lm	141 lm/W	0 4 8 - 1 1 2 1 1 1 <input checked="" type="checkbox"/> M

FLOOD 39°, CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x22.7 W,	3000 K	2x3110 lm	137 lm/W	0 4 8 - 1 1 2 1 0 1 <input checked="" type="checkbox"/> F
650 mA	3500 K	2x3150 lm	138 lm/W	0 4 8 - 1 1 2 1 2 1 <input checked="" type="checkbox"/> F
	4000 K	2x3160 lm	139 lm/W	0 4 8 - 1 1 2 1 1 1 <input checked="" type="checkbox"/> F

Planning Information



2 optical accessories can be combined

Electrical mounting accessories (optional)



THROUGH WIRING CONNECTION BOX


TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)

Order options


COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8

**MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm**

L-W-H (mm)
218-118-35

ORDER CODE0 4 8 - 2 7 9 8 3 1 **Electrical accessories (required)****POWER SUPPLY** 650 mA, PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
31 W non DIM	198-264 V AC	η 88 %	143-43-30	0 0 2 - 9 0 7 8 0
28 W DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 8 9

Optical accessories (optional)**HONEYCOMB LOUVER**

Ø-H (mm)
75-9

ORDER CODE

0 8 0 - 6 4 0 1 1 1 8

LINEAR PRISMATIC LENS

Ø-H (mm)
75-9

ORDER CODE

0 8 0 - 6 4 0 2 1 1 0 P

SNOOT angle

Ø-H (mm)
66-38

ORDER CODE

0 8 0 - 6 4 0 3 3 1 8

SNOOT medium

Ø-H (mm)
66-38

ORDER CODE

0 8 0 - 6 4 0 3 2 1 8

SNOOT short

Ø-H (mm)
66-23

ORDER CODE

0 8 0 - 6 4 0 3 1 1 8

Order options

COLOUR	
traffic white RAL 9016	7 <input checked="" type="checkbox"/>
jet black RAL 9005	8