

Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 16
jusqu'à ↓ 5 530 lm / ↑ 7 850 lm
jusqu'à 7 460 lm/m
jusqu'à 163 lm/W
L90 / 75000 h
Cache : Lens, Reflector
DALI-2, DALI-2 / DALI-2 ESSENTIAL sensor, DALI-2 D/I contrôlable séparément
IP20

Types



Colours



Réflecteur



Répartition de la lumière





DiiA® standards
251, 252, 253



DIN EN 12464-1
UGR ≤ 19



system solution



glare-free direct and 170° indirect illumination



CRI ≥ 98
XPECTRUM
(optional)

BETO

suspended

EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 42 x 42 mm); no visible screws; surface powder coated; pendant fitting with cable suspension; with integrated toolless suspension height adjustment; spring clip attachment to the luminaire; freely positionable; incl. feeder cable; extruded profile for improved thermal management; high gloss reflector with faceted design; direct / indirect light distribution; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination, optionally separately controllable; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en profil extrudé en alu, version arête ; forme extrêmement élancée (seulement 42 x 42 mm) ; aucune vis visible ; surface thermolaquée ; suspension par câble ; réglage en hauteur sans outil au luminaire ; fixation au luminaire au moyen de clips à ressort ; positionnement libre ; incl. conduit d'alimentation ; profil extrudé pour une meilleure gestion de la température ; réflecteur ultra-brillant avec optique à facettes ; caractéristique de rayonnement direct / indirect ; dispositif d'éclairage indirect avec platines dédiées et optique de lentille de grande qualité pour un éclairage maximal et homogène du plafond, contrôle séparé en option ; LED économes en énergie à restitution de couleur élevée





BETO suspended

TUNABLE WHITE | CRI ≥90 | UGR ≤10 | cd/m² ≤1500 | 220-240 V | 1-2 ADDR. | X-PERT | X-PERT | presence | brightness

DIRECT / INDIRECT 2700-6500K POWER CRI ≥ 90, DALI-2 D/I separately controllable

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
51.0 W	1857 mm	↧ 3000 K/ ↥tunable w.	↧3200/↥3050 lm	123 lm/W	074-62D604
		↧ 4000 K/ ↥tunable w.	↧3200/↥3050 lm	123 lm/W	074-62D614
88.0 W	3057 mm	↧ 3000 K/ ↥tunable w.	↧4810/↥6110 lm	124 lm/W	074-62D904
		↧ 4000 K/ ↥tunable w.	↧4810/↥6110 lm	124 lm/W	074-62D914

The data values for the luminous flux may differ for specific order options by -14%. Luminous flux value refers to reflector chrome. tunable white only INDIRECT

INDIRECT POWER

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
54.0 W	3457 mm	3000 K	80	7840 lm	145 lm/W	074-62N95
			90	6840 lm	127 lm/W	074-62N90
		4000 K	80	8360 lm	155 lm/W	074-62N96
			90	6840 lm	127 lm/W	074-62N91
61.0 W	3457 mm	tunable w.	90	6880 lm	113 lm/W	074-62N9D

DIRECT / INDIRECT POWER

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
48.0 W	1857 mm	3000 K	80	↧3470/↥3440 lm	144 lm/W	074-62465
			90	↧3020/↥2970 lm	125 lm/W	074-62460
		4000 K	80	↧3690/↥3930 lm	159 lm/W	074-62466
			90	↧3020/↥3210 lm	130 lm/W	074-62461
51.0 W	1857 mm	tunable w.	90	↧3320/↥3120 lm	126 lm/W	074-6246D
82.0 W	3057 mm	3000 K	80	↧5200/↥6890 lm	147 lm/W	074-62495
			90	↧4530/↥5940 lm	128 lm/W	074-62490
		4000 K	80	↧5530/↥7850 lm	163 lm/W	074-62496
			90	↧4530/↥6410 lm	133 lm/W	074-62491
87.0 W	3057 mm	tunable w.	90	↧4980/↥6240 lm	129 lm/W	074-6249D

The data values for the luminous flux may differ for specific order options by -14%. Luminous flux value refers to reflector chrome.

Order options

CONTROL	
DALI-2	3
DALI-2 D/I separately controllable	4
DALI-2 / DALI-2 ESSENTIAL sensor	7

CONTROL	
DALI-2	3
DALI-2 / DALI-2 ESSENTIAL sensor	7

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8

REFLECTOR	
dark chrome	B
chrome	R

Planning Information





BETO suspended, 86 W, 4000 K direct / indirect power

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 | 0.5 | 0.2
Maintenance factor	0.8
Mounting height	2.25 m

CALCULATION SURFACE ·····

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E_m)	> 500 lx
Uniformity (U_0)	> 0.6

GLARE EVALUATION

Table Classification X=4H | Y=8H | S=0.25H

UGR transversal	≤ 19
UGR axial	≤ 19

65° < 1500 cd/m²

F+P Architekten, Vienna

Autriche

Architecte
F+P Architekten

Lighting Design
Ing. Gerald Pummer,
Illuminazione

Photographe
Kurt Kuball



Produits utilisés



SASSO 100 square ceiling



BETO ceiling / suspended system

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com









Granitlab Coworking

Autriche

Architecte
GHT-Plan GmbH

Lighting Design
GHT-Plan GmbH, AREA
C.I. Design GmbH

Photographe
Kurt Kuball



Produits utilisés



BETO suspended



INO square suspended



UNICO Q1 / Q4 ceiling

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

