



LITO 60

suspended


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; pendant fitting with cable suspension; with integrated toolless suspension height adjustment; spring clip attachment to the luminaire; freely positionable; incl. transparent feed; light inset made from extruded profile for improved thermal management; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; direct / indirect light distribution; indirect light component with integrated PCBs for maximum, homogeneous ceiling illumination; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en profil extrudé en alu, version arête ; aucune vis visible ; surface thermolaquée ; suspension par câble ; réglage en hauteur sans outil au luminaire ; fixation au luminaire au moyen de clips à ressort ; positionnement libre ; incl. conduit d'alimentation transparent ; insert lumineux en profil extrudé pour une meilleure gestion de la température ; cache PMMA microprismatique, avec film diffusant inclus pour réduire la brillance avec un éclairage homogène ; caractéristique de rayonnement direct / indirect ; dispositif de lumière indirecte avec platines dédiées pour un éclairage de plafond homogène maximal ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000 K, 4000 K
 CRI ≥ 80 / 3 SDCM (initial MacAdam)
 UGR ≤ 19
 jusqu'à ↓ 5,530 lm / ↑ 3,980 lm
 jusqu'à 4,060 lm/m
 jusqu'à 122 lm/W
 L90 / 50000 h
 DALI-2, capteur autonome
 ESSENTIAL, non DIM
 Microprismatic
 IP20

Types




Couleur




Répartition de la lumière



DiiA® standards
 251, 252, 253



microprismatic
 UGR ≤ 19



suspension
 freely
 positionable



170° indirect
 illumination




LITO 60 suspended





DIRECT / INDIRECT CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
40.0 W	1180 mm	3000 K	↓2610/↑1880 lm	112 lm/W	0 4 6 - 5 2 2 4 5 <input checked="" type="checkbox"/> Z
		4000 K	↓2760/↑1990 lm	119 lm/W	0 4 6 - 5 2 2 4 6 <input checked="" type="checkbox"/> Z
50.0 W	1480 mm	3000 K	↓3260/↑2350 lm	112 lm/W	0 4 6 - 5 2 2 5 5 <input checked="" type="checkbox"/> Z
		4000 K	↓3450/↑2480 lm	119 lm/W	0 4 6 - 5 2 2 5 6 <input checked="" type="checkbox"/> Z
78.0 W	2352 mm	3000 K	↓5220/↑3750 lm	115 lm/W	0 4 6 - 5 2 2 8 5 <input checked="" type="checkbox"/> Z
		4000 K	↓5530/↑3980 lm	122 lm/W	0 4 6 - 5 2 2 8 6 <input checked="" type="checkbox"/> Z



Planning Information



LITO 60 suspended, 51W, 4000K direct / indirect

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Mounting height	2.25m

CALCULATION SURFACE

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E _m)	>500lx
Uniformity (U ₀)	>0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤19
UGR axial	≤19

Order options

CONTROL		COLOUR	
non DIM	1	white aluminium RAL 9006	G <input checked="" type="checkbox"/>
DALI-2	3	pure white RAL 9010	7
stand alone ESSENTIAL sensor	7	jet black RAL 9005	8

Grundschule St. Martin, South Tyrol


Italie

Architecte
tasserball architekten

Photographe
rené riller fotografie



Produits utilisés




UNICO L4 / L6
recessed



UNICO L2 / L3
recessed



UNICO Q1 / Q4
recessed



UNICO L4 / L6 basic
recessed



UNICO L2 / L3 basic
recessed



UNICO Q1 / Q4 basic
recessed



SONO surface



LITO 60 suspended







