




Quickinfo

6500 K
 jusqu'à 217 lm/W
 DALI-2 ESSENTIAL sensor,
 DALI-2 SENSE sensor
 front IP20, IP40, back IP20

Types



Couleur



Set de montage



SASSO 60 round sensor / emergency

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement

FR Insert rond (écl. de secours ou capteur) ; montage sans outil en kit de montage (sans bord ou avec bord continu) ; surface laquée ; encastrement possible dans différents boîtiers ; insert pour éclairage de secours LED : 3 var. avec diff. possib. d'essai - Basic avec touche d'essai, auto-test avec LED d'état ou Pro DALI avec surveill. par DALI ; capteur avec commande DALI-2 : 2 variantes - Basic avec capteur de luminosité et de présence ou Pro avec mesure suppl. de la température, de l'humidité de l'air et du bruit



quick mounting
 in soft acoustic
 ceilings



SASSO 60 round sensor essential



DALI-2 ESSENTIAL sensor

COLOUR

jet black

traffic white

ORDER CODE

0 4 8 - 2 6 9 3 1 1 1

0 4 8 - 2 6 9 3 1 1 7



SASSO 60 round sensor sense



DALI-2 SENSE sensor

COLOUR

jet black

traffic white

ORDER CODE

0 4 8 - 2 6 9 3 1 2 1

0 4 8 - 2 6 9 3 1 2 7



SASSO 60 round emergency light



3H | BASIC | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 1 <input checked="" type="checkbox"/>

incl. 3 interchangeable lenses



3H | SELFTEST | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 2 <input checked="" type="checkbox"/>

incl. 3 interchangeable lenses

3H | PRO | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 3 <input checked="" type="checkbox"/>


incl. 3 interchangeable lenses

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
traffic white RAL 9016	7	traffic black	RAL 9017

Mounting accessories (required)

		MOUNTING SET trimless for plasterboard ceilings		
COLOUR	PLASTERBOARD CEILING THICKNESS	Ø-H (mm)	ORDER CODE	
traffic white	12.5/15/25 mm	73-29	0 4 8 - 2 6 9 6 1 1 7	
for SASSO 60 round SPIO 60 downlight				





 73
 60*/115**
 non DIM
 120
 DALI-2
 145
 loop through
 function
 * SASSO 60
 ** SPIO 60

		MOUNTING SET trimless for soft acoustic ceilings		
COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE	
traffic white	25-40 mm	80-25	0 4 8 - 2 6 9 6 1 9 7	





 74
 120
 non DIM
 120
 DALI-2
 145
 loop through
 function

		MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm		
COLOUR		Ø-H (mm)	ORDER CODE	
traffic white		80-27	0 4 8 - 2 6 9 6 3 9 7	
jet black		80-27	0 4 8 - 2 6 9 6 3 9 8	




 74
 100
 non DIM
 100
 DALI-2
 125
 loop through
 function


		MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm		
COLOUR		Ø-H (mm)	ORDER CODE	
traffic white		80-40	0 4 8 - 2 6 9 6 3 1 7	
jet black		80-40	0 4 8 - 2 6 9 6 3 1 8	




 73
 60
 non DIM
 100
 DALI-2
 125
 loop through
 function

Mounting accessories (optional)

		EXPOSED CONCRETE MOUNTING HOUSING		
COLOUR		L-W-H (mm)	ORDER CODE	
white aluminium		230-230-162	0 4 8 - 2 6 9 5 2 1 0	

		PRIMED CONCRETE MOUNTING HOUSING		
L-W-H (mm)			ORDER CODE	
614-307-120			0 4 8 - 2 6 9 5 1 1 0	
order mounting set separately				

Mounting tools accessories (optional)

		MOUNTING TOOL for soft acoustic ceilings		
COLOUR		L-W-H (mm)	ORDER CODE	
traffic black		77-77-35	0 4 8 - 2 6 9 5 9 1 8	

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
traffic white RAL 9016	7	traffic black	RAL 9017



Electrical accessories (optional)

REPLACEMENT ACCUPACK

TYPE

3h battery life

ORDER CODE

0 4 8 - 2 6 9 3 9 1 0

Order options

COLOUR

jet black RAL 9005

traffic white RAL 9016



COLOUR

white aluminium

traffic black

RAL 9006

RAL 9017