


Quickinfo

2700 K, 3000 K, 4000 K, colour warm dimming 1800 - 2700 K
 CRI \geq 90, CRI \geq 95 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam), 4 SDCM (initial MacAdam)
 UGR \leq 10, UGR \leq 19
 jusqu'à 103 lm/W
 L80 / 50000 h, L85 / 50000 h, L90 / 50000 h
 DALI-2, non DIM
 front IP20

Types



Couleur



Set de montage



Répartition de la lumière



SASSO PRO 80 adjustable offset round recessed

EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; surface powder coated; light inset rotatable and tiltable; offset lighting level; optical attachments available as accessories; with optional high-quality lens system with precise radiation characteristic; and high-quality reflector with spherical facet effect design, precise radiation characteristic with two different beam angles; installed and exchanged without tools; COB (Chip on Board) technology or high power LEDs for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

FR Spot rond encastrable en fonte d'aluminium injectée ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; surface thermolaquée ; module d'éclairage rotatif et orientable ; luminaire en retrait ; éléments optiques disponibles comme accessoires ; également possible avec une optique de lentilles de haute qualité présentant des caractéristiques de rayonnement précises ; ou un réflecteur de haute qualité avec une optique sphérique à facettes, caractéristiques de rayonnement précises avec deux angles de rayonnement différents ; Installation resp. remplacement sans outil ; avec technologie COB (Chip on Board) ou High-Power-LED pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée



DiiA® standards
251, 252, 253



360° rotatable,
35° tiltable



Colour Warm
Dimming 1800 –
2700 K



SASSO PRO 80 adjustable



SUPER SPOT 8°, CRI ≥ 90, non DIM

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|-----------|----------|---|
| 7.0 W | 2700 K | 388 lm | 55 lm/W | 0 4 8 - 2 3 1 0 4 1 <input checked="" type="checkbox"/> V |
| | 3000 K | 379 lm | 54 lm/W | 0 4 8 - 2 3 1 0 5 1 <input checked="" type="checkbox"/> V |
| | 4000 K | 408 lm | 58 lm/W | 0 4 8 - 2 3 1 0 6 1 <input checked="" type="checkbox"/> V |




MEDIUM 26°,

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|------------------|-----------|----------|---|
| 6.5 W | CWD, CRI ≥ 95 | 377 lm | 58 lm/W | 0 4 8 - 2 3 1 0 E 3 <input checked="" type="checkbox"/> M |
| 7.5 W | 2700 K, CRI ≥ 90 | 721 lm | 96 lm/W | 0 4 8 - 2 3 1 0 4 1 <input checked="" type="checkbox"/> M |
| | 3000 K, CRI ≥ 90 | 757 lm | 101 lm/W | 0 4 8 - 2 3 1 0 5 1 <input checked="" type="checkbox"/> M |
| | 4000 K, CRI ≥ 90 | 765 lm | 102 lm/W | 0 4 8 - 2 3 1 0 6 1 <input checked="" type="checkbox"/> M |
| 12.2 W | 2700 K, CRI ≥ 90 | 1010 lm | 83 lm/W | 0 4 8 - 2 3 1 2 4 <input checked="" type="checkbox"/> M |
| | 3000 K, CRI ≥ 90 | 1050 lm | 86 lm/W | 0 4 8 - 2 3 1 2 5 <input checked="" type="checkbox"/> M |
| | 4000 K, CRI ≥ 90 | 1120 lm | 92 lm/W | 0 4 8 - 2 3 1 2 6 <input checked="" type="checkbox"/> M |

FLOOD 37°, CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|-----------|----------|---|
| 7.5 W | 2700 K | 728 lm | 97 lm/W | 0 4 8 - 2 3 1 0 4 1 <input checked="" type="checkbox"/> F |
| | 3000 K | 765 lm | 102 lm/W | 0 4 8 - 2 3 1 0 5 1 <input checked="" type="checkbox"/> F |
| | 4000 K | 773 lm | 103 lm/W | 0 4 8 - 2 3 1 0 6 1 <input checked="" type="checkbox"/> F |
| 12.2 W | 2700 K | 1020 lm | 84 lm/W | 0 4 8 - 2 3 1 2 4 <input checked="" type="checkbox"/> F |
| | 3000 K | 1060 lm | 87 lm/W | 0 4 8 - 2 3 1 2 5 <input checked="" type="checkbox"/> F |
| | 4000 K | 1130 lm | 93 lm/W | 0 4 8 - 2 3 1 2 6 <input checked="" type="checkbox"/> F |

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

| TYPE | L-W-H (mm) | ORDER CODE |
|---------------------------|------------|-----------------------|
| non DIM cable ø 4 – 12 mm | 105-58-30 | 0 0 5 - 2 5 3 1 1 1 0 |
| DALI cable ø 4 – 12 mm | 105-58-30 | 0 0 5 - 2 5 5 1 1 1 0 |


Linect®-Ready

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings, 12.5/15/25 mm

| L-W-H (mm) | ORDER CODE |
|------------|---|
| 124-92-33 | 0 5 2 - 1 9 3 1 3 2 <input checked="" type="checkbox"/> |




MOUNTING SET with trim for intermediate ceilings, 5-25 mm

| Ø-H (mm) | ORDER CODE |
|----------|---|
| 98-43 | 0 5 2 - 1 9 3 2 3 2 <input checked="" type="checkbox"/> |

Order options

| CONTROL | | COLOUR | |
|---------|---|------------------------|---|
| non DIM | 1 | traffic white RAL 9016 | 7 |
| DALI-2 | 3 | jet black RAL 9005 | 8 |



Mounting accessories (optional)

PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)

240-400-130

ORDER CODE

0 5 2 - 1 9 1 4 3 2 0

order mounting set separately

Optical accessories (optional)



HONEYCOMB LOUVER

Ø-H (mm)

54-11

ORDER CODE

0 4 8 - 2 0 9 1 3 1

LINEAR PRISMATIC LENS

Ø-H (mm)

54-11

ORDER CODE

0 4 8 - 2 0 9 2 3 1



SNOOT

Ø-H (mm)

54-25

ORDER CODE

0 4 8 - 2 0 9 1 1 1



SNOOT WITH HONEYCOMB LOUVER

Ø-H (mm)

54-25

ORDER CODE

0 4 8 - 2 0 9 1 2 1

Order options

| CONTROL | | COLOUR | |
|---------|---|------------------------|---|
| non DIM | 1 | traffic white RAL 9016 | 7 |
| DALI-2 | 3 | jet black RAL 9005 | 8 |