



MIRA 150

recessed

EN Round recessed spotlight in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; lighting level recessed; completely homogeneously illuminated, satinised or microprismatic PMMA cover; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion


FR Spot rond encastrable en fonte d'aluminium injectée ; avec bord continu ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; montage sans outil avec fermeture par ressort à déclic ; niveau de luminaire en retrait ; cache PMMA, à éclairage parfaitement homogène, satiné ou microprismatique ; LED économes en énergie à restitution de couleur élevée ; convertisseur externe pour fente plafond

Quickinfo

3000 K, 4000 K
CRI \geq 90 / 3 SDCM (initial MacAdam)
jusqu'à 128 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non DIM
Microprismatic, Opal
front IP20, IP54, back IP20

Types

MIRA round



Couleur




Répartition de la lumière





MIRA 150 round trim




OPAL CRI ≥ 90

SYSTEM	COLOUR TEMP.	COLOUR	LUM. FLUX	EFFICACY	ORDER CODE
13.0 W	3000 K	jet black	1380 lm	106 lm/W	● 5 2 - 9 3 2 3 5 ◆ 8 O
		pure white	1500 lm	115 lm/W	● 5 2 - 9 3 2 3 5 ◆ 7 O
	4000 K	jet black	1520 lm	117 lm/W	● 5 2 - 9 3 2 3 6 ◆ 8 O
		pure white	1660 lm	128 lm/W	● 5 2 - 9 3 2 3 6 ◆ 7 O
18.6 W	3000 K	jet black	1850 lm	99 lm/W	● 5 2 - 9 3 2 4 5 ◆ 8 O
		pure white	2020 lm	109 lm/W	● 5 2 - 9 3 2 4 5 ◆ 7 O
	4000 K	jet black	2040 lm	110 lm/W	● 5 2 - 9 3 2 4 6 ◆ 8 O
		pure white	2220 lm	119 lm/W	● 5 2 - 9 3 2 4 6 ◆ 7 O

MICROPRISMATIC CRI ≥ 90

SYSTEM	COLOUR TEMP.	COLOUR	LUM. FLUX	EFFICACY	ORDER CODE
13.0 W	3000 K	jet black	1340 lm	103 lm/W	● 5 2 - 9 3 2 3 5 ◆ 8 P
		pure white	1470 lm	113 lm/W	● 5 2 - 9 3 2 3 5 ◆ 7 P
	4000 K	jet black	1480 lm	114 lm/W	● 5 2 - 9 3 2 3 6 ◆ 8 P
		pure white	1620 lm	125 lm/W	● 5 2 - 9 3 2 3 6 ◆ 7 P
18.6 W	3000 K	jet black	1800 lm	97 lm/W	● 5 2 - 9 3 2 4 5 ◆ 8 P
		pure white	1970 lm	106 lm/W	● 5 2 - 9 3 2 4 5 ◆ 7 P
	4000 K	jet black	1980 lm	106 lm/W	● 5 2 - 9 3 2 4 6 ◆ 8 P
		pure white	2170 lm	117 lm/W	● 5 2 - 9 3 2 4 6 ◆ 7 P

Electrical mounting accessories (optional)



THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Order options

IP RATING FRONT	● CONTROL	◆ COLOUR	
IP20	0 non DIM	1 pure white	RAL 9010
IP54	8 DALI-2	3 jet black	RAL 9005