


Quickinfo

3000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
jusqu'à 4 290 lm/m
jusqu'à 139 lm/W
L80 / 50000 h
non DIM
Opal
IP20

Types



Colours

Répartition de la lumière

CORNER

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile for mounting available in advance; suitable for wall or ceiling mounting; with double-sided light beam; opal cover for uniform illumination; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en profil extrudé en alu, version arête ; aucune vis visible ; surface thermolaquée ; Profilé de luminaire pour montage livrable avant ; convient au montage mur ou plafond ; avec diffusion de lumière par 2 côtés ; cache opale pour éclairage homogène ; LED économes en énergie à restitution de couleur élevée



wall / ceiling illumination




tunable white 2700 – 6500 K (optional)



CORNER surface

CRI ≥ 80 | 220-240 V | X-PERT | X-PERT



OPAL | MID LUMEN CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.8 W	588 mm	3000 K	1810 lm	131 lm/W	040-895251 O
20.7 W	888 mm	3000 K	2720 lm	131 lm/W	040-895351 O
27.6 W	1188 mm	3000 K	3620 lm	131 lm/W	040-895451 O
53.0 W	2358 mm	3000 K	7250 lm	137 lm/W	040-895851 O
67.0 W	3014 mm	3000 K	9340 lm	139 lm/W	040-895951 O

OPAL | HIGH LUMEN CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.2 W	588 mm	3000 K	2460 lm	122 lm/W	040-896251 O
29.6 W	888 mm	3000 K	3680 lm	124 lm/W	040-896351 O
39.0 W	1188 mm	3000 K	4910 lm	126 lm/W	040-896451 O
76.0 W	2358 mm	3000 K	9820 lm	129 lm/W	040-896851 O
98.0 W	3014 mm	3000 K	12700 lm	130 lm/W	040-896951 O

Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8
white aluminium RAL 9006	G