








Quickinfo

2700 K, 3000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
jusqu'à 106 lm/W
L80 / 50000 h, L85 / 50000 h, L90 / 100000 h
DALI-2, non DIM
front IP20

Types



Colours



Set de montage



Répartition de la lumière



MOVE IN flex round

recessed

EN Round spotlight element in aluminium, available in 3 sizes; surface polished chrome, brushed aluminium or powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; spotlight head rotates 360° and tilts 90°; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

FR Elément de spot rond en aluminium, disponible dans 3 tailles ; surface en chrome poli, aluminium brossé ou thermolaquée ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; outil de montage spécial pour faciliter la mise en place du boîtier sans rebord proposé comme accessoire ; elément de spot réglable en hauteur sans outil : affleurant avec le plafond, dépassant de 25 mm ou 35 mm ; tête de spot pivotant à 360° et orientable à 90° ; Technologie COB (Chip on Board) pour efficacité maximale ; pas de formation d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; réflecteur de grande qualité, métallisée à l'aluminium avec optique facette ; caractéristique de rayonnement précise ; bon anti-éblouissement grâce aux points lumineux en retrait ; eléments optiques comme accessoires



360° rotatable, 90° tiltable



tool-free height adjustment, rotatable & tiltable



trimless installation in plasterboard







MOVE IN 22 FLEX ROUND

90° 360° | CRI ≥ 90 | 2 SDCM | III | DALI 1 ADDR. | X-PERT | X-PERT

SPOT 15°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.6 W, 36 Vf, 150 mA	2700 K	328 lm	59 lm/W	063-820141 S
	3000 K	346 lm	62 lm/W	063-820151 S

incl. connection cable 600 mm

MEDIUM 26°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.6 W, 36 Vf, 150 mA	2700 K	345 lm	62 lm/W	063-820141 M
	3000 K	364 lm	65 lm/W	063-820151 M

incl. connection cable 600 mm

FLOOD 43°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.6 W, 36 Vf, 150 mA	2700 K	371 lm	67 lm/W	063-820141 F
	3000 K	391 lm	70 lm/W	063-820151 F

incl. connection cable 600 mm







MOVE IN 32 FLEX ROUND

90° 360° | CRI ≥ 90 | 2 SDCM | III | DALI 1 ADDR. | X-PERT

SPOT 18°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W, 36 Vf, 250 mA	2700 K	788 lm	91 lm/W	063-821141 S
	3000 K	817 lm	94 lm/W	063-821151 S

incl. connection cable 600 mm

MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W, 36 Vf, 250 mA	2700 K	821 lm	94 lm/W	063-821141 M
	3000 K	852 lm	98 lm/W	063-821151 M

incl. connection cable 600 mm

FLOOD 34°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W, 36 Vf, 250 mA	2700 K	783 lm	90 lm/W	063-821141 F
	3000 K	813 lm	93 lm/W	063-821151 F

incl. connection cable 600 mm

Order options

COLOUR	
chrome	4
brushed aluminium	6
traffic white RAL 9016	7
jet black RAL 9005	8



MOVE IN 45 FLEX ROUND

90° 360° | CRI ≥ 90 | 2 SDCM | III | DALI 1 ADDR. | X-PERT





SUPER SPOT 8°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.9 W, 11 Vf, 600 mA	2700 K	406 lm	59 lm/W	0 6 3 - 8 2 2 1 4 1 ◪ V
	3000 K	432 lm	63 lm/W	0 6 3 - 8 2 2 1 5 1 ◪ V

incl. connection cable 600 mm; do not use optical filters

SPOT 12°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
12.7 W, 37 Vf, 350 mA	2700 K	1100 lm	87 lm/W	0 6 3 - 8 2 2 1 4 1 ◪ S
	3000 K	1150 lm	91 lm/W	0 6 3 - 8 2 2 1 5 1 ◪ S

incl. connection cable 600 mm

MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W, 36 Vf, 400 mA	2700 K	1330 lm	100 lm/W	0 6 3 - 8 2 2 1 4 1 ◪ M
	3000 K	1380 lm	104 lm/W	0 6 3 - 8 2 2 1 5 1 ◪ M


incl. connection cable 600 mm

FLOOD 36°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W, 36 Vf, 400 mA	2700 K	1360 lm	102 lm/W	0 6 3 - 8 2 2 1 4 1 ◪ F
	3000 K	1420 lm	106 lm/W	0 6 3 - 8 2 2 1 5 1 ◪ F

incl. connection cable 600 mm


Mounting accessories (required)



MOUNTING HOUSING trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	9-25 mm	56·64	0 6 3 - 8 8 1 0 1 1 7


for MOVE IN 22 round



MOUNTING HOUSING trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	9-25 mm	63·93	0 6 3 - 8 8 1 1 1 1 7

for MOVE IN 32 round




MOUNTING HOUSING trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	9-25 mm	75·106	0 6 3 - 8 8 1 2 1 1 7

for MOVE IN 45 round

Order options


COLOUR ◪	
chrome	4
brushed aluminium	6
traffic white RAL 9016	7
jet black RAL 9005	8



MOUNTING HOUSING with trim for ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	59·65	063-882011 7
jet black	59·65	063-882011 8


for MOVE IN 22 round



MOUNTING HOUSING with trim for ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	65·93	063-882111 7
jet black	65·93	063-882111 8

for MOVE IN 32 round




MOUNTING HOUSING with trim for ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	77·107	063-882211 7
jet black	77·107	063-882211 8

for MOVE IN 45 round


Mounting tools accessories (optional)



SPECIAL MOUNTING TOOL

TYPE	Ø·H (mm)	ORDER CODE
for MOVE IN 22 | SPIO 20		048-169000 0
for MOVE IN 32 round	83·107	063-891111 0

necessary to install mounting housing trimless



SPECIAL MOUNTING TOOL for ARY | MOVE IN 45 | NOBA trimless | TULA

Ø·H (mm)	ORDER CODE
100·107	063-891211 0

necessary to install mounting housing trimless


Electrical accessories (required)

POWER SUPPLY 198-264 V AC

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
350 mA | 15 W | DALI-2 | PC2	η 87 %	166·29·21	002-90720
350 mA | 22 W | non DIM | PC2	η 89 %	180·30·21	002-90722
400 mA | 22 W | non DIM | PC2	η 89 %	180·30·21	002-90724
600 mA | 30 W | non DIM | PC1	η 89 %	180·30·21	002-90726
400 mA | 15 W | DALI-2 | PC2	η 87 %	166·29·21	002-90728
600 mA | 40 W | DALI-2 | PC2	η 89 %	197·29·21	002-90729
250 mA | 10 W | non DIM | PC2	η 80 %	65·39·20	002-90742
250 mA | 10 W | DALI-2 | PC2	η 82 %	166·29·21	002-90743
150 mA | 15 W | DALI-2 | PC2	η 87 %	112·29·21	002-90811

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 -1050 mA settable const. current | 2 × 42 W | 48V DC | U OUT 10 – 40 V SELV

Optical accessories (optional)



HONEYCOMB LOUVER for BO 32 | JUST 32 | MOVE IN 32 | TARO 32 | TILA 32

COLOUR	Ø·H (mm)	ORDER CODE
jet black	30·3	007-196516 8



HONEYCOMB LOUVER for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

COLOUR	Ø·H (mm)	ORDER CODE
jet black	42·3	007-196518 8



OVAL LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007-196586 0



OVAL LENS for BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007-196588 0



SOFT LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007-196596 0



SOFT LENS for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007-196598 0



WALLWASHER LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007-196576 0



WALLWASHER LENS for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007-1965780