

LINEA

system


EN Luminaire housing and front cover from extruded aluminium profile, angular version; no visible screws; designed for continuous lighting systems, 90° angle connectors for flexible system design; surface powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; HPO (High Performance Opal) cover for uniform illumination; or with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); energy-efficient LEDs with very good colour rendering; optionally JUST 26 spotlight module can be installed

FR Corps de luminaire et cache avant en profil extrudé en aluminium, version à bords en arête ; aucune vis visible ; conçu pour systèmes d'éclairage continus, équerres de raccordement 90° pour structure de système flexible ; surface thermolaquée ; convient à un montage mural ; éclairage homogène du mur ou du plafond par une distribution de lumière uniforme directe / indirecte ; cache HPO (High Performance Opal) pour éclairage homogène ; ou avec lentille spécialement calculée et asym. pour des intensités lum. homogènes (montage au choix pour éclairage du sol ou du plafond) ; LED économes en énergie à restitution de couleur élevée ; insert de spot JUST 26 montable au choix


Quickinfo

3000 K, 4000 K, tunable white
2700 - 5000 K
CRI \geq 90, CRI \geq 97 / 3 SDCM
(initial MacAdam)
jusqu'à \downarrow 4,020 lm/l 4,770 lm
jusqu'à 125 lm/W
L85 / 50000 h, L95 / 50000 h
DALI-2, non DIM
High Performance Opal, High
Performance Opal / Asymmetric
IP20 / CP1 / 220-240 V

Types



Répartition de la lumière



CRI \geq 98
XPECTRUM
(optional)



LINEA wall system



OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W	306 mm	3000 K	↓428/±509 lm	105 lm/W	0 5 8 - 6 1 4 1 5 <input checked="" type="checkbox"/> A A
		4000 K	↓472/±562 lm	116 lm/W	0 5 8 - 6 1 4 1 6 <input checked="" type="checkbox"/> A A
17.6 W	606 mm	3000 K	↓881/±1050 lm	110 lm/W	0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> A A
		4000 K	↓972/±1160 lm	121 lm/W	0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> A A
34.0 W	1206 mm	3000 K	↓1760/±2090 lm	113 lm/W	0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> A A
		4000 K	↓1940/±2310 lm	125 lm/W	0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> A A
39.0 W	1206 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2390 lm	113 lm/W	0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> A A
68.0 W	2406 mm	3000 K	↓3520/±4190 lm	113 lm/W	0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> A A
		4000 K	↓3890/±4620 lm	125 lm/W	0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> A A
76.0 W	2406 mm	↓ tunable w./ ±2700 K - 5000 K	↓4020/±4770 lm	116 lm/W	0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> A A



OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W	306 mm	3000 K	↓428/±428 lm	96 lm/W	0 5 8 - 6 1 4 1 5 <input checked="" type="checkbox"/> A H
		4000 K	↓472/±472 lm	106 lm/W	0 5 8 - 6 1 4 1 6 <input checked="" type="checkbox"/> A H
17.6 W	606 mm	3000 K	↓881/±881 lm	100 lm/W	0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> A H
		4000 K	↓972/±972 lm	110 lm/W	0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> A H
34.0 W	1206 mm	3000 K	↓1760/±1760 lm	104 lm/W	0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> A H
		4000 K	↓1940/±1940 lm	114 lm/W	0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> A H
39.0 W	1206 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2010 lm	103 lm/W	0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> A H
68.0 W	2406 mm	3000 K	↓3520/±3520 lm	104 lm/W	0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> A H
		4000 K	↓3890/±3890 lm	114 lm/W	0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> A H
76.0 W	2406 mm	↓ tunable w./ ±2700 K - 5000 K	↓4020/±4020 lm	106 lm/W	0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> A H




LINEA inner corner wall system



OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	633 mm	3000 K	↓1760/±2090 lm	113 lm/W	0 5 8 - 6 1 1 1 5 <input checked="" type="checkbox"/> A A
		4000 K	↓1940/±2310 lm	125 lm/W	0 5 8 - 6 1 1 1 6 <input checked="" type="checkbox"/> A A
39.0 W	633 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2390 lm	113 lm/W	0 5 8 - 6 1 1 1 D 3 <input checked="" type="checkbox"/> A A



OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	633 mm	3000 K	↓1760/±1760 lm	104 lm/W	0 5 8 - 6 1 1 1 5 <input checked="" type="checkbox"/> A H
		4000 K	↓1940/±1940 lm	114 lm/W	0 5 8 - 6 1 1 1 6 <input checked="" type="checkbox"/> A H
39.0 W	633 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2010 lm	103 lm/W	0 5 8 - 6 1 1 1 D 3 <input checked="" type="checkbox"/> A H

Order options

CONTROL		COLOUR		MOUNTING	
non DIM		1 pure white RAL 9010		7 spotlight left	B
DALI-2	3	jet black RAL 9005		8 spotlight right	C




LINEA outer corner wall system



OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	637 mm	3000 K	↓1760/±2090 lm	113 lm/W	0 5 8 - 6 1 1 2 5 <input checked="" type="checkbox"/> A A
		4000 K	↓1940/±2310 lm	125 lm/W	0 5 8 - 6 1 1 2 6 <input checked="" type="checkbox"/> A A
39.0 W	637 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2390 lm	113 lm/W	0 5 8 - 6 1 1 2 D 3 <input checked="" type="checkbox"/> A A



OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	637 mm	3000 K	↓1760/±1760 lm	104 lm/W	0 5 8 - 6 1 1 2 5 <input checked="" type="checkbox"/> A H
		4000 K	↓1940/±1940 lm	114 lm/W	0 5 8 - 6 1 1 2 6 <input checked="" type="checkbox"/> A H
39.0 W	637 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2010 lm	103 lm/W	0 5 8 - 6 1 1 2 D 3 <input checked="" type="checkbox"/> A H




LINEA 1 spotlight wall system



OPAL / OPAL | 1 SPOTLIGHT 30°, CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.6 W	706 mm	3000 K	↓881/±881 lm	100 lm/W	0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	↓972/±972 lm	110 lm/W	0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
34.0 W	1306 mm	3000 K	↓1760/±1760 lm	104 lm/W	0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	↓1940/±1940 lm	114 lm/W	0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
39.0 W	1306 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2010 lm	103 lm/W	0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
68.0 W	2506 mm	3000 K	↓3520/±3520 lm	104 lm/W	0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	↓3890/±3890 lm	114 lm/W	0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
76.0 W	2506 mm	↓ tunable w./ ±2700 K - 5000 K	↓4020/±4020 lm	106 lm/W	0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H



spotlight 1 x 2,6 W / 159 lm only with 3000 K

Mounting accessories (optional)



END CAPS 1 pair

L-W-H (mm)
40-100-12

ORDER CODE
0 5 0 - 2 5 4 0 1 0



LINEAR CONNECTOR

TYPE
1 piece
10 pieces

L-W (mm) ORDER CODE
60-38 0 5 0 - 2 5 5 1 1 0 0
60-38 0 5 0 - 2 5 5 1 1 0 0 · 1 0

Order options

CONTROL		COLOUR		MOUNTING	
non DIM		1 pure white RAL 9010		7 spotlight left	B
DALI-2	3	jet black RAL 9005		8 spotlight right	C

Electrical accessories (optional)**THROUGH WIRE****TYPE**3×1.5mm² | 10 pieces | non DIM5×1.5mm² | 10 pieces | DALI-2**ORDER CODE**

0 0 4 - 9 0 0 0 3

0 0 4 - 9 0 0 0 5

Order options

CONTROL		COLOUR	<input checked="" type="checkbox"/>	MOUNTING	
non DIM	1	pure white RAL 9010	7	spotlight left	B
DALI-2	3	jet black RAL 9005	8	spotlight right	C