

## UNICO wall

surface


**EN** Rectangular wall surface mounted multi-uplight made of aluminium; equipped with one light inset (1 LAMP) / two (2 LAMPS) / four (4 LAMPS) light insets; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high-quality reflector with micro-faceted, aluminum-vaporised surface; homogeneous wall or ceiling illumination through uniform light distribution; energy-efficient high power LEDs with very good colour rendering; luminaire for through wiring

**FR** Multi-Uplight mural apparent rectangulaire en alum. ; avec insert d'éclairage (1 LAMP) / deux (2 LAMPS) / quatre (4 LAMPS) inserts d'éclairage ; corps de luminaire pouvant être monté sans outils sur la plaque de montage grâce à un système de verrouillage ; convertisseur intégré dans le corps de luminaire ; surface thermolaquée ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; éclairage homogène du mur ou du plafond par une distribution de lumière uniforme ; High-Power-LED à grande efficacité énergétique, très bon rendu des couleurs ; luminaire pour câblage continu

### Quickinfo

2700 K, 3000 K, 4000 K  
 CRI ≥ 90 / 3 SDCM (initial MacAdam)  
 jusqu'à 48 lm/W  
 L80 / 50000 h, L90 / 50000 h  
 DALI-2, non DIM  
 IP20

### Types



### Couleur




### Répartition de la lumière



homogeneous ceiling illumination



safety glass for dust protection




### UNICO wall 1 lamp surface



#### WIDE FLOOR CRI ≥ 90, non DIM

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|--------|--------------|-----------|----------|---|
| 5.8 W  | 2700 K       | 220 lm    | 38 lm/W  | 0 9 0 - 0 L 1 4 1 T <input checked="" type="checkbox"/> 0 0 1 |
|        | 3000 K       | 235 lm    | 41 lm/W  | 0 9 0 - 0 L 1 5 1 T <input checked="" type="checkbox"/> 0 0 1 |
|        | 4000 K       | 244 lm    | 42 lm/W  | 0 9 0 - 0 L 1 6 1 T <input checked="" type="checkbox"/> 0 0 1 |




### UNICO wall 2 lamps surface



#### WIDE FLOOR CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|--------|--------------|-----------|----------|---|
| 17.3 W | 2700 K       | 650 lm    | 38 lm/W  | 0 9 0 - 0 L 2 4 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1 |
|        | 3000 K       | 693 lm    | 40 lm/W  | 0 9 0 - 0 L 2 5 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1 |
|        | 4000 K       | 744 lm    | 43 lm/W  | 0 9 0 - 0 L 2 6 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1 |




### UNICO wall 4 lamps surface



#### WIDE FLOOR CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|--------|--------------|-----------|----------|---|
| 29.1 W | 2700 K       | 1230 lm   | 42 lm/W  | 0 9 0 - 0 L 4 4 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1 |
|        | 3000 K       | 1310 lm   | 45 lm/W  | 0 9 0 - 0 L 4 5 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1 |
|        | 4000 K       | 1410 lm   | 48 lm/W  | 0 9 0 - 0 L 4 6 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1 |



#### Order options

| CONTROL |   | COLOUR                   |   |
|---------|---|--------------------------|---|
| non DIM | 1 | jet black RAL 9005       | B |
| DALI-2  | 3 | white aluminium RAL 9006 | G |
|         |   | traffic white RAL 9016   | W |