

UNICO wall

surface


EN Rectangular wall surface mounted multi-uplight made of aluminium; equipped with one light inset (1 LAMP) / two (2 LAMPS) / four (4 LAMPS) light insets; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high-quality reflector with micro-faceted, aluminum-vaporised surface; homogeneous wall or ceiling illumination through uniform light distribution; energy-efficient high power LEDs with very good colour rendering; luminaire for through wiring

FR Multi-Uplight mural apparent rectangulaire en alum. ; avec insert d'éclairage (1 LAMP) / deux (2 LAMPS) / quatre (4 LAMPS) inserts d'éclairage ; corps de luminaire pouvant être monté sans outils sur la plaque de montage grâce à un système de verrouillage ; convertisseur intégré dans le corps de luminaire ; surface thermolaquée ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; éclairage homogène du mur ou du plafond par une distribution de lumière uniforme ; High-Power-LED à grande efficacité énergétique, très bon rendu des couleurs ; luminaire pour câblage continu

Quickinfo

2700 K, 3000 K, 4000 K
 CRI \geq 90 / 3 SDCM (initial MacAdam)
 jusqu'à 48 lm/W
 L80 / 50000 h, L90 / 50000 h
 DALI-2, non DIM
 IP20

Types



Couleur



Répartition de la lumière



homogeneous ceiling illumination



safety glass for dust protection



UNICO wall 1 lamp surface



WIDE FLOOR CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.8 W	2700 K	220 lm	38 lm/W	0 9 0 - 0 L 1 4 1 T <input checked="" type="checkbox"/> 0 0 1
	3000 K	235 lm	41 lm/W	0 9 0 - 0 L 1 5 1 T <input checked="" type="checkbox"/> 0 0 1
	4000 K	244 lm	42 lm/W	0 9 0 - 0 L 1 6 1 T <input checked="" type="checkbox"/> 0 0 1




UNICO wall 2 lamps surface



WIDE FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.3 W	2700 K	650 lm	38 lm/W	0 9 0 - 0 L 2 4 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1
	3000 K	693 lm	40 lm/W	0 9 0 - 0 L 2 5 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1
	4000 K	744 lm	43 lm/W	0 9 0 - 0 L 2 6 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1




UNICO wall 4 lamps surface



WIDE FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
29.1 W	2700 K	1230 lm	42 lm/W	0 9 0 - 0 L 4 4 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1
	3000 K	1310 lm	45 lm/W	0 9 0 - 0 L 4 5 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1
	4000 K	1410 lm	48 lm/W	0 9 0 - 0 L 4 6 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1



Order options

CONTROL		COLOUR	
non DIM	1	jet black RAL 9005	B
DALI-2	3	white aluminium RAL 9006	G
		traffic white RAL 9016	W