

SQUADRO wallwasher

recessed 2 lamps


EN Recessed ceiling spotlight in die cast aluminium in two different types (2 lamps or 2x2 lamps) and with 2 types of light modules (for shelf floor washer and wall floor washer); with trim; surface powder coated; installation without tools using snap spring closure; aisle spotlight with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone, adjustable light modules; COB (Chip on Board) technology for maximum efficiency; efficient LEDs with very good colour rendering; IP40 protection glass available as an accessory

FR Spot encastré en aluminium moulé en 2 variantes différentes (à 2 lampes ou 2 x 2 lampes) et avec deux modules lumineux différents (pour shelf floor washer et wall floor washer) ; avec bord continu ; surface thermolaquée ; montage sans outil avec fermeture par ressort à déclic ; Spot pour couloirs avec réflecteurs spéciaux multiples dotés d'une technologie à forme libre avec optique à facettes pour un guidage extrêmement précis du flux lumineux ; éclairage précis des étagères et des couloirs, anti-éblouissement longitudinal optimal pour un confort visuel élevé dans les couloirs, modules lumineux réglables ; Technologie COB (Chip on Board) pour efficacité maximale ; LED économes en énergie à restitution de couleur élevée ; verre de protection IP40 disponible comme accessoire

Quickinfo

3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
jusqu'à 138 lm/W
L80 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours



Répartition de la lumière



DiiA® standards
251, 252, 253



up to 139 lm/W
(high efficiency)



glare-free
reflector
longitudinally &
transversely



+20° up to -15°
tiltable







SQUADRO 1 x 2 lamps wallwasher trim




SINGLE-SIDED CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
36.0 W	3000 K	4830 lm	134 lm/W	0 4 9 - 2 0 1 2 0 ▾ ▴ ▲
	3500 K	4880 lm	136 lm/W	0 4 9 - 2 0 1 2 2 ▾ ▴ ▲
	4000 K	4900 lm	136 lm/W	0 4 9 - 2 0 1 2 1 ▾ ▴ ▲







SQUADRO 2 x 2 lamps wallwasher trim



DOUBLE-SIDED CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
71.0 W	3000 K	9650 lm	136 lm/W	0 4 9 - 2 0 2 0 0 ▾ ▴ ▲
	3500 K	9770 lm	138 lm/W	0 4 9 - 2 0 2 0 2 ▾ ▴ ▲
	4000 K	9790 lm	138 lm/W	0 4 9 - 2 0 2 0 1 ▾ ▴ ▲




Order options


CONTROL	COLOUR	OPTIC	OPTIC	OPTIC
non DIM	1 traffic white RAL 9016	7 wall floor washer	A wall floor washer	A
DALI-2	3 jet black RAL 9005	8 shelf floor washer	S shelf / wall floor washer	B
			shelf floor washer	S

Planning Information

SQUADRO 1×2 lamps, shelf wall washer, trim, 36 W, 3000 K



SQUADRO 1×2 lamps, wall floor washer, trim, 36 W, 3000 K



ROOM VALUES		CALCULATION SURFACE	
Wall dimensions	H = 3.5 m W = 10.8 m	Surface dimensions	10.8 × 3.5 m
Distance to wall	B = 1.3 m	Surface height	0 – 3.5 m
Aisle width	2.6 m		
Reflection factor	0.7 0.7 0.2	Eye level	1.35 m – 1.75 m
Maintenance factor	0.9		

Optical accessories (optional)

IP40 PROTECTION GLASS		ORDER CODE
TYPE		
1 x 2 lamps / single-sided		0 4 9 - 2 9 1 0 0 1 0
2 x 2 lamps / double-sided		0 4 9 - 2 9 2 0 0 1 0

Order options					
CONTROL		COLOUR	OPTIC	OPTIC	
non DIM	1	traffic white RAL 9016	7 wall floor washer	A wall floor washer	A
DALI-2	3	jet black RAL 9005	8 shelf floor washer	S shelf / wall floor washer	B
				shelf floor washer	S