


Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 13, UGR ≤ 16, UGR ≤ 19
jusqu'à ↓ 4 750 lm / ↑ 4 380 lm
jusqu'à 163 lm/W
L90 / 100000 h, L90 / 75000 h
Cache : Opal, Reflector
DALI-2
IP20

Types



Colours



Réflecteur



Répartition de la lumière





dark chrome reflector option



up to 139 lm/W (high efficiency)



version with opal cover



magnetic blind cover



DIN EN 12464-1 UGR ≤ 19

MITA circle 450


suspended

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high gloss reflector with faceted design; opal cover for uniform illumination; either with direct or direct / indirect light distribution; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en forme d'anneau en fonte d'alu injectée ; forme extrêmement élancée ; surface thermolaquée ; suspendu ; avec suspension pouvant être raccourcie (chrome), conduit d'alimentation dans le tube de suspension ; disp. électronique d'alimentation intégré au cache-piton ; en option : cache, fixé par aimant dans l'encoche intérieure, disponible comme accessoire ; réflecteur ultra-brillant avec optique à facettes ; cache opale pour éclairage homogène ; au choix avec caractéristique de rayonnement direct ou direct / indirect ; LED économes en énergie à restitution de couleur élevée



MITA CIRCLE 450 reflector suspended



CRI ≥ 90 | UGR ≤ 13 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

DIRECT | REFLECTOR (UGR ≤ 19) DALI-2


SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
29.4 W	3000 K	80	chrome	4500 lm	153 lm/W	0 7 4 - 7 6 1 1 5 3 ◪ R
			dark chr.	3220 lm	110 lm/W	0 7 4 - 7 6 1 1 5 3 ◪ B
		90	chrome	3920 lm	133 lm/W	0 7 4 - 7 6 1 1 0 3 ◪ R
			dark chr.	2800 lm	95 lm/W	0 7 4 - 7 6 1 1 0 3 ◪ B
	4000 K	80	chrome	4790 lm	163 lm/W	0 7 4 - 7 6 1 1 6 3 ◪ R
			dark chr.	3430 lm	117 lm/W	0 7 4 - 7 6 1 1 6 3 ◪ B
		90	chrome	3920 lm	133 lm/W	0 7 4 - 7 6 1 1 1 3 ◪ R
			dark chr.	2800 lm	95 lm/W	0 7 4 - 7 6 1 1 1 3 ◪ B
40.0 W	3000 K	80	chrome	5850 lm	146 lm/W	0 7 4 - 7 6 2 1 5 3 ◪ R
			dark chr.	4190 lm	105 lm/W	0 7 4 - 7 6 2 1 5 3 ◪ B
		90	chrome	5100 lm	128 lm/W	0 7 4 - 7 6 2 1 0 3 ◪ R
			dark chr.	3650 lm	91 lm/W	0 7 4 - 7 6 2 1 0 3 ◪ B
	4000 K	80	chrome	6230 lm	156 lm/W	0 7 4 - 7 6 2 1 6 3 ◪ R
			dark chr.	4460 lm	112 lm/W	0 7 4 - 7 6 2 1 6 3 ◪ B
		90	chrome	5100 lm	128 lm/W	0 7 4 - 7 6 2 1 1 3 ◪ R
			dark chr.	3650 lm	91 lm/W	0 7 4 - 7 6 2 1 1 3 ◪ B

DIRECT / INDIRECT POWER | REFLECTOR (UGR ≤ 19) DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
58.0 W	3000 K	80	chrome	↧4460/↥3850 lm	143 lm/W	0 7 4 - 7 6 5 1 5 3 ◪ R
			dark chr.	↧3180/↥3850 lm	121 lm/W	0 7 4 - 7 6 5 1 5 3 ◪ B
		90	chrome	↧3880/↥3320 lm	124 lm/W	0 7 4 - 7 6 5 1 0 3 ◪ R
			dark chr.	↧2770/↥3320 lm	105 lm/W	0 7 4 - 7 6 5 1 0 3 ◪ B
	4000 K	80	chrome	↧4750/↥4380 lm	157 lm/W	0 7 4 - 7 6 5 1 6 3 ◪ R
			dark chr.	↧3380/↥4380 lm	134 lm/W	0 7 4 - 7 6 5 1 6 3 ◪ B
		90	chrome	↧3880/↥3580 lm	129 lm/W	0 7 4 - 7 6 5 1 1 3 ◪ R
			dark chr.	↧2770/↥3580 lm	109 lm/W	0 7 4 - 7 6 5 1 1 3 ◪ B



MITA CIRCLE 450 opal suspended



CRI ≥ 90 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL | DIRECT DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
24.9 W	3000 K	80	2950 lm	118 lm/W	0 7 4 - 7 6 1 1 5 3 ◪ O
		90	2570 lm	103 lm/W	0 7 4 - 7 6 1 1 0 3 ◪ O
	4000 K	80	3140 lm	126 lm/W	0 7 4 - 7 6 1 1 6 3 ◪ O
		90	2570 lm	103 lm/W	0 7 4 - 7 6 1 1 1 3 ◪ O

Order options

COLOUR ◪	
traffic white RAL 9016	7
jet black RAL 9005	8

OPAL | DIRECT / INDIRECT POWER DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
58.0 W	3000 K	80	↧3580/↥3850 lm	128 lm/W	074-765153 O
		90	↧3120/↥3320 lm	111 lm/W	074-765103 O
	4000 K	80	↧3810/↥4380 lm	141 lm/W	074-765163 O
		90	↧3110/↥3580 lm	115 lm/W	074-765113 O

Optical accessories

BLIND COVER circle 450 ceiling

Ø (mm)	ORDER CODE
339	074-891162

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8