



UNICO Q1 sensor

recessed

EN UNICO Q1 sensor; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; clank-free

FR UNICO Q1 sensor ; montage sans outil en kit de montage par système à dé clic à bille ; installation électrique facile par enfichage protégé contre les inversions de polarité ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; encastrement possible dans différents boîtiers ; sans distorsions

Quickinfo

DALI-2 ESSENTIAL sensor,
DALI-2 SENSE sensor
front IP20

Types

trim



□ 63

trimless



□ 47

Couleur



Set de montage



Répartition de la lumière



DiiA® standards
251, 252, 253



one luminaire
multiple scenes



plug / socket
connector




black & gold
reflector
(optional)



tunable white
2700 – 5000 K
(optional)



UNICO Q1 sensor essential



jet black, DALI-2 ESSENTIAL sensor

ORDER CODE

0 9 0 - 7 Q 1 0 0 0 0



UNICO Q1 sensor sense




jet black, DALI-2 SENSE sensor

ORDER CODE

0 9 0 - 7 Q 1 0 0 1 0

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS

12.5/15/20/25 mm

L-W-H (mm)

47-47-47

ORDER CODE

0 9 0 - 7 Q 1 0 1 0 0

for UNICO Q1



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR

jet black

L-W-H (mm)

63-63-30

ORDER CODE

0 9 0 - 7 Q 1 0 2 0 B

traffic white

63-63-30

0 9 0 - 7 Q 1 0 2 0 W

for UNICO Q1

Order options

COLOUR

jet black

RAL 9005

traffic white

RAL 9016