



MITA circle 160

ceiling

EN Cylindrical ceiling surface mounted luminaire made of aluminium; slim design; ring shaped arranged reflectors; surface powder coated; mounting plate with pre-assembled converter unit can be pre-mounted; luminaire housing can be attached without tools by interlock; incl. blind cover made of plastic in the cut-out; optional: SASSO 60 round sensor installed in the cut-out; sensor with DALI-2 control: brightness and presence sensor; high gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering


FR Plafonnier cylindrique apparent en aluminium ; forme élancée ; réflecteurs disposés en anneau ; surface thermolaquée ; plaque de montage avec unité de conversion prémontée, pouvant être montée à l'avance ; corps de luminaire pouvant être monté sans outils grâce à un système de verrouillage ; y compris le capot en plastique dans la découpe intérieure ; en option : SASSO 60 round sensor monté en encoche intérieure ; capteur avec commande DALI-2 : capteur de luminosité et de présence ; réflecteur ultra-brillant avec optique à facettes ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI \geq 80, CRI \geq 90 / 3 SDCM
(initial MacAdam)
UGR \leq 16, UGR \leq 19
jusqu'à 153 lm/W
L90 / 100000 h, L90 / 50000 h
DALI-2, DALI-2 / DALI-2
ESSENTIAL sensor
Reflector
IP20

Types

ceiling



Couleur



Réflecteur



Répartition de la lumière




DIN EN 12464-1
UGR \leq 19



sensor version
available



dark chrome
reflector option



tunable white
2700 - 6500 K



MITA CIRCLE 160 ceiling



REFLECTOR

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
7.4 W	tunable w.	90	chrome	838 lm	113 lm/W	0 7 4 - 7 6 1 6 D 3 <input checked="" type="checkbox"/> R
			dark chr.	600 lm	81 lm/W	0 7 4 - 7 6 1 6 D 3 <input checked="" type="checkbox"/> B
7.8 W	3000 K	80	chrome	1120 lm	144 lm/W	0 7 4 - 7 6 1 6 5 <input checked="" type="checkbox"/> R
			dark chr.	799 lm	102 lm/W	0 7 4 - 7 6 1 6 5 <input checked="" type="checkbox"/> B
		90	chrome	973 lm	125 lm/W	0 7 4 - 7 6 1 6 0 <input checked="" type="checkbox"/> R
			dark chr.	696 lm	89 lm/W	0 7 4 - 7 6 1 6 0 <input checked="" type="checkbox"/> B
	4000 K	80	chrome	1190 lm	153 lm/W	0 7 4 - 7 6 1 6 6 <input checked="" type="checkbox"/> R
			dark chr.	851 lm	109 lm/W	0 7 4 - 7 6 1 6 6 <input checked="" type="checkbox"/> B
		90	chrome	973 lm	125 lm/W	0 7 4 - 7 6 1 6 1 <input checked="" type="checkbox"/> R
			dark chr.	696 lm	89 lm/W	0 7 4 - 7 6 1 6 1 <input checked="" type="checkbox"/> B

□ 76

⊙
∅ 165

Order options

CONTROL		COLOUR	
DALI-2	3	traffic white RAL 9016	7 <input checked="" type="checkbox"/>
DALI-2 / DALI-2 ESSENTIAL sensor	7	jet black RAL 9005	8 <input checked="" type="checkbox"/>