


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
jusqu'à 2 510 lm/m
jusqu'à 113 lm/W
L85 / 50000 h
DALI-2, non DIM
Opal
IP44

Types



Colours

Capuchon

Répartition de la lumière

STRETTA

wall

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be pre-mounted; end caps powder coated in same colour as housing or brushed aluminium; suitable for wall mounting; with three sided light beam; opal cover for uniform illumination; energy-efficient LEDs with very good colour rendering


FR Corps de luminaire en profil extrudé en alu, version arête ; aucune vis visible ; surface thermolaquée ; profilé de luminaire pouvant être monté à l'avance ; bouchons revêtus de poudre dans la couleur du boîtier ou en aluminium brossé ; convient à un montage mural ; avec diffusion de lumière trois côtés ; cache opale pour éclairage homogène ; LED économes en énergie à restitution de couleur élevée



wall illumination



splash water protection (IP 44)



CRI ≥ 98 XPECTRUM





STRETTA wall

CRI ≥ 90 | 220-240 V | DALI 1 ADDR. | IP 44 | X-PERT

OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	057-013251 H
		4000 K	1480 lm	113 lm/W	057-013261 H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	057-013351 H
		4000 K	2220 lm	113 lm/W	057-013361 H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	057-013451 H
		4000 K	2950 lm	112 lm/W	057-013461 H






STRETTA wall | end caps aluminium

CRI ≥ 90 | 220-240 V | DALI 1 ADDR. | IP 44 | X-PERT

OPAL pure white, CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	057-013251 2H
		4000 K	1480 lm	113 lm/W	057-013261 2H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	057-013351 2H
		4000 K	2220 lm	113 lm/W	057-013361 2H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	057-013451 2H
		4000 K	2950 lm	112 lm/W	057-013461 2H



Order options

CONTROL	
non DIM	1
DALI-2	3

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8