



STRETTA

wall


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be pre-mounted; end caps powder coated in same colour as housing or brushed aluminium; suitable for wall mounting; with three sided light beam; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en profil extrudé en alu, version arête ; aucune vis visible ; surface thermolaquée ; profilé de luminaire pouvant être monté à l'avance ; bouchons revêtus de poudre dans la couleur du boîtier ou en aluminium brossé ; convient à un montage mural ; avec diffusion de lumière trois côtés ; cache HPO (High Performance Opal) pour éclairage homogène ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000 K, 4000 K
CRI $\geq$ 90 / 3 SDCM (initial MacAdam)
jusqu'à 2,510 lm/m
jusqu'à 113 lm/W
L80 / 50000 h
DALI-2, non DIM
High Performance Opal
IP44

Types



Couleur



Capuchon




Répartition de la lumière



wall illumination



splash water
protection (IP
44)



CRI $\geq$ 98
XPECTRUM





STRETTA wall



OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	0 5 7 - 0 1 3 2 5 ↕ ▣ H
		4000 K	1480 lm	113 lm/W	0 5 7 - 0 1 3 2 6 ↕ ▣ H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	0 5 7 - 0 1 3 3 5 ↕ ▣ H
		4000 K	2220 lm	113 lm/W	0 5 7 - 0 1 3 3 6 ↕ ▣ H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	0 5 7 - 0 1 3 4 5 ↕ ▣ H
		4000 K	2950 lm	112 lm/W	0 5 7 - 0 1 3 4 6 ↕ ▣ H




STRETTA wall | end caps aluminium



OPAL pure white, CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	0 5 7 - 0 1 3 2 5 ↕ 2 H
		4000 K	1480 lm	113 lm/W	0 5 7 - 0 1 3 2 6 ↕ 2 H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	0 5 7 - 0 1 3 3 5 ↕ 2 H
		4000 K	2220 lm	113 lm/W	0 5 7 - 0 1 3 3 6 ↕ 2 H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	0 5 7 - 0 1 3 4 5 ↕ 2 H
		4000 K	2950 lm	112 lm/W	0 5 7 - 0 1 3 4 6 ↕ 2 H



Order options

CONTROL		COLOUR	
non DIM	1	pure white RAL 9010	7
DALI-2	3	jet black RAL 9005	8