






Quickinfo

3000 K, 4000 K
CRI ≥ 95 / 3 SDCM (initial MacAdam)
jusqu'à 106 lm/W
L80 / 50000 h, L85 / 50000 h
sans driver
IP20

Types



Colours

Répartition de la lumière

STADIO 10

semi-recessed

EN Cylindrical semi-recessed miniature spotlight made of aluminium; surface lacquered; spotlight head rotatable and tiltable; high quality lens system; precise radiation characteristics with different beam angles; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

FR Spot cylindrique miniature en aluminium monté en semi-encastré ; surface laquée ; tête de spot pivotant et orientable ; optique lentille de grande qualité ; précision de caractéristique de rayonnement avec divers angles de diffusion ; LED économes en énergie à restitution de couleur élevée ; système de branchement électrique par trous métallisés pour montage sans outil ; convertisseur préassemblé prêt à brancher ; convertisseur à commander séparément



CRI ≥ 95, R9 ≥ 90




360° rotatable, 90° tiltable



plug & play



STADIO 10 semi-recessed



SPOT 18°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W,	3000 K	44 lm	71 lm/W	011-800001 S
220 mA	4000 K	48 lm	75 lm/W	011-800011 S

light inset incl. connection cable with plug 0.5 m

MEDIUM 30°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W,	3000 K	60 lm	104 lm/W	011-800001 M
220 mA	4000 K	65 lm	105 lm/W	011-800011 M

light inset incl. connection cable with plug 0.5 m

FLOOD 39°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W,	3000 K	60 lm	105 lm/W	011-800001 F
220 mA	4000 K	66 lm	106 lm/W	011-800011 F

light inset incl. connection cable with plug 0.5 m

Electrical mounting accessories

EXTENSION CABLE 1 × socket / 1 × plug, 350 mA

feeder length	ORDER CODE
1000 mm	011-922112 0
2000 mm	011-922114 0
4000 mm	011-922118 0

Electrical accessories

POWER SUPPLY EU 220 mA

TYPE	L·W·H (mm)	ORDER CODE
non DIM	115·19·34	011-921121 0
DALI-2	145·33·21	011-921113 0

incl. power cable 2 m + connection cable with socket 1 m

POWER SUPPLY UL 220 mA, 42 W, 90-277 V AC, PC2

EFFICIENCY	L·W·H (mm)	ORDER CODE
η 89 %	131·43·30	011-927111 0
η 89 %		011-929111 0

CONNECTION CABLE 1 × open / 1 × top plug

FEEDER LENGTH	ORDER CODE
1000 mm	011-922162 0

Order options

COLOUR	
white aluminium RAL 9006	6
tar black RAL 9021	8

SPLITTER SERIAL

TYPE	L·W·H (mm)	ORDER CODE
3 × socket / 1 × plug	38·30·10	0 1 1 - 9 2 2 8 3 0 0
6 × socket / 1 × plug	55·32·10	0 1 1 - 9 2 2 8 6 0 0