



## STADIO 10

semi-recessed


**EN** Cylindrical semi-recessed miniature spotlight made of aluminium; surface lacquered; spotlight head rotatable and tiltable; high quality lens system; precise radiation characteristics with different beam angles; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

**FR** Spot cylindrique miniature en aluminium monté en semi-encastré ; surface laquée ; tête de spot pivotant et orientable ; optique lentille de grande qualité ; précision de caractéristique de rayonnement avec divers angles de diffusion ; LED économes en énergie à restitution de couleur élevée ; système de branchement électrique par trous métallisés pour montage sans outil ; convertisseur préassemblé prêt à brancher ; convertisseur à commander séparément

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  95 / 3 SDCM (initial MacAdam)  
 jusqu'à 106 lm/W  
 L80 / 50000 h, L85 / 50000 h  
 sans driver  
 IP20

### Types



### Couleur



### Répartition de la lumière



CRI  $\geq$  95, R9  $\geq$  90



360° rotatable,  
90° tiltable



plug & play




## STADIO 10 semi-recessed



### SPOT 18°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W,	3000 K	44 lm	71 lm/W	0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> S
220 mA	4000 K	48 lm	75 lm/W	0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> S

light inset incl. connection cable with socket 0.5 m



### MEDIUM 30°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W,	3000 K	60 lm	104 lm/W	0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> M
220 mA	4000 K	65 lm	105 lm/W	0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> M

light inset incl. connection cable with socket 0.5 m

### FLOOD 39°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W,	3000 K	60 lm	105 lm/W	0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> F
220 mA	4000 K	66 lm	106 lm/W	0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> F

light inset incl. connection cable with socket 0.5 m

## Electrical mounting accessories (optional)

### EXTENSION CABLE 1 × socket / 1 × plug, 350 mA

feeder length	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 1 2 0
2000 mm	0 1 1 - 9 2 2 1 1 4 0
4000 mm	0 1 1 - 9 2 2 1 1 8 0

## Electrical accessories (optional)

### POWER SUPPLY EU 220 mA

TYPE	L-W-H (mm)	ORDER CODE
non DIM	115-19-34	0 1 1 - 9 2 1 1 2 1 0
DALI-2	145-33-21	0 1 1 - 9 2 1 1 1 3 0

incl. power cable 2 m + connection cable with plug 1 m

### POWER SUPPLY UL 220 mA, 42 W, 90-277 V AC, PC2

EFFICIENCY	L-W-H (mm)	ORDER CODE
η 89 %	131-43-30	0 1 1 - 9 2 7 1 1 1 0
η 89 %		0 1 1 - 9 2 9 1 1 1 0

### CONNECTION CABLE 1 × open / 1 × top plug

FEEDER LENGTH	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 6 2 0

## Order options

COLOUR	
white aluminium RAL 9006	<input checked="" type="checkbox"/> 6
tar black RAL 9021	8

**SPLITTER SERIAL**

<b>TYPE</b>	<b>L·W·H (mm)</b>	<b>ORDER CODE</b>
3 × socket / 1 × plug	38·30·10	0 1 1 - 9 2 2 8 3 0 0
6 × socket / 1 × plug	55·32·10	0 1 1 - 9 2 2 8 6 0 0

**Order options**

<b>COLOUR</b>	<input type="checkbox"/>
white aluminium RAL 9006	<input checked="" type="checkbox"/> 6
tar black RAL 9021	<input type="checkbox"/> 8