



## SASSO 60 round

wall

<sup>EN</sup> Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

<sup>FR</sup> Applique cylindrique en aluminium pour montage en surface ; insert d'éclairage peint ; surface du boîtier thermolaquée ; disponible au choix, en rayonnement symétrique direct ou direct/indirect ; éclairage homogène du mur ou du plafond par une distribution de lumière uniforme ; caractéristiques de rayonn. précises grâce à l'optique à lentille ; variante de montage DIRECT disponible au choix pour l'éclairage du sol ou du plafond ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée

### Quickinfo

2700 K, 3000 K, 4000 K  
CRI ≥ 90 / 2 SDCM (initial MacAdam)  
jusqu'à ↓ 713 lm / ↑ 712 lm  
jusqu'à 70 lm/W  
L80 / 50000 h  
DALI-2, non DIM  
IP20

### Types



### Couleur



### Couleur intérieure



### Répartition de la lumière



direct and  
direct / indirect  
illumination



high quality lens



easy mounting



CRI ≥ 95 2  
SDCM  
(optional)




### SASSO 60 round direct wall



#### OPAL LENS | DIRECT 71°, CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|--------|--------------|-----------|----------|---|
| 10.3 W | 2700 K       | 661 lm    | 64 lm/W  | 0 4 8 - 3 1 5 0 4 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O |
|        | 3000 K       | 686 lm    | 67 lm/W  | 0 4 8 - 3 1 5 0 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O |
|        | 4000 K       | 716 lm    | 70 lm/W  | 0 4 8 - 3 1 5 0 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O |

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.




### SASSO 60 round direct / indirect wall



#### OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX    | EFFICACY | ORDER CODE  |
|--------|--------------|--------------|----------|---|
| 20.6 W | 2700 K       | ↓659/↑657 lm | 64 lm/W  | 0 4 8 - 3 1 6 0 4 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O |
|        | 3000 K       | ↓683/↑682 lm | 66 lm/W  | 0 4 8 - 3 1 6 0 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O |
|        | 4000 K       | ↓713/↑712 lm | 69 lm/W  | 0 4 8 - 3 1 6 0 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O |



#### Order options

| CONTROL |   | COLOUR                 |   | INNER COLOUR           |   |
|---------|---|------------------------|---|------------------------|---|
| non DIM | 1 | jet black RAL 9005     | 1 | jet black RAL 9005     | 1 |
| DALI-2  | 3 | traffic white RAL 9016 | 7 | matt silver            | 4 |
|         |   |                        |   | traffic white RAL 9016 | 7 |
|         |   |                        |   | gold dust RAL 260-M    | 9 |