


Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
jusqu'à ↓ 713 lm / ↑ 712 lm
jusqu'à 70 lm/W
L90 / 100000 h
DALI-2, non DIM
IP20

Types



Colours

Couleur intérieure

Répartition de la lumière

SASSO 60 round

wall

EN Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

FR Applique cylindrique en aluminium pour montage en surface ; insert d'éclairage peint ; surface du boîtier thermolaquée ; disponible au choix, en rayonnement symétrique direct ou direct/indirect ; éclairage homogène du mur ou du plafond par une distribution de lumière uniforme ; caractéristiques de rayonn. précises grâce à l'optique à lentille ; variante de montage DIRECT disponible au choix pour l'éclairage du sol ou du plafond ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée



direct and direct / indirect illumination


high quality lens


easy mounting


CRI ≥ 95 2 SDCM (optional)





SASSO 60 round direct wall


CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL LENS | DIRECT 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.3 W	2700 K	661 lm	64 lm/W	0 4 8 - 3 1 5 0 4 ◆ ◪ ■ O
	3000 K	686 lm	67 lm/W	0 4 8 - 3 1 5 0 5 ◆ ◪ ■ O
	4000 K	716 lm	70 lm/W	0 4 8 - 3 1 5 0 6 ◆ ◪ ■ O

The data values for the luminous flux of fraction may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.





SASSO 60 round direct / indirect wall

CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.6 W	2700 K	↧659/↥657 lm	64 lm/W	0 4 8 - 3 1 6 0 4 ◆ ◪ ■ O
	3000 K	↧683/↥682 lm	66 lm/W	0 4 8 - 3 1 6 0 5 ◆ ◪ ■ O
	4000 K	↧713/↥712 lm	69 lm/W	0 4 8 - 3 1 6 0 6 ◆ ◪ ■ O

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.

Order options

CONTROL ◆		COLOUR ◪		INNER COLOUR ■	
non DIM	1	jet black RAL 9005	1	jet black RAL 9005	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white RAL 9016	7
				gold dust RAL 260-M	9