



Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
jusqu'à 153 lm/W
L80 / 50000 h
IP20

Types





Colours



Câble



Répartition de la lumière




NOBA

multi suspended

EN Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

FR Luminaire décoratif à suspension en aluminium ; surface en chrome poli, aluminium brossé ou thermolaquée ; suspension par câble, câble d'alimentation inclus (noir ou blanche) ; recoupable à volonté ; cache-piton rond pour montage sur plafond (noir ou blanc) pour un équipement de deux à cinq lampes ou de deux à dix lampes au choix ; ou cache-piton linéaire pour montage sur plafond (noir ou blanc) pour un équipement de deux à cinq lampes au choix ; lentille verre plan-convexe grde qualité ; LED économes en énergie à restitution de couleur élevée ; cache-piton pour câblage continu ; convertisseur inclus dans le cache-piton ; anneaux de montage au plafond pour un positionnement multiple des luminaires dans la pièce disponibles comme accessoires



free positioning by cable and hook



high quality glass lens




NOBA 40 multi suspended

CRI ≥ 90 · 2 SDCM · UGR ≤ 22 · cd/m² ≤ 1500 · III · X-PERT

WIDE FLOOD 69°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.4 W,	2700 K	326 lm	133 lm/W	0 4 9 - 5 4 1 0 9 1 ◪ ■ W
9 Vf,	3000 K	322 lm	135 lm/W	0 4 9 - 5 4 1 0 0 1 ◪ ■ W
300 mA	4000 K	352 lm	144 lm/W	0 4 9 - 5 4 1 0 1 1 ◪ ■ W






NOBA 50 multi suspended

CRI ≥ 90 · 2 SDCM · UGR ≤ 19 · cd/m² ≤ 1500 · III · X-PERT

WIDE FLOOD 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.4 W,	2700 K	345 lm	141 lm/W	0 4 9 - 5 4 1 3 9 1 ◪ ■ W
9 Vf,	3000 K	342 lm	143 lm/W	0 4 9 - 5 4 1 3 0 1 ◪ ■ W
300 mA	4000 K	374 lm	153 lm/W	0 4 9 - 5 4 1 3 1 1 ◪ ■ W






NOBA 60 multi suspended

CRI ≥ 90 · 2 SDCM · UGR ≤ 16 · cd/m² ≤ 1500 · III · X-PERT

WIDE FLOOD 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.5 W,	2700 K	325 lm	132 lm/W	0 4 9 - 5 4 1 6 9 1 ◪ ■ W
9 Vf,	3000 K	337 lm	137 lm/W	0 4 9 - 5 4 1 6 0 1 ◪ ■ W
300 mA	4000 K	352 lm	143 lm/W	0 4 9 - 5 4 1 6 1 1 ◪ ■ W



Mounting accessories (optional)




HOOK surface

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	16·30	0 3 0 - 1 0 0 0 0 1 7
jet black	16·30	0 3 0 - 1 0 0 0 0 1 8

Order options

COLOUR ◪		COLOUR ◪		CABLE ■	
brushed brass	3	traffic white RAL 9016	7	white	7
chrome	4	jet black RAL 9005	8	black	8
gun metal	5	rose gold	9		
brushed aluminium	6				


Electrical accessories (required)



CANOPY WITH SLOTS multi round 2-10 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø·H (mm)	ORDER CODE
DALI-2	380·43	0 0 5 - 2 6 9 0 1 3 [1]
Casambi	380·43	0 0 5 - 2 6 9 0 1 9 [1]


2 converter a 300 mA; 2 DALI addresses



CANOPY WITH SLOTS multi round 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø·H (mm)	ORDER CODE
DALI-2	380·43	0 0 5 - 2 6 9 0 0 3 [1]
Casambi	380·43	0 0 5 - 2 6 9 0 0 9 [1]


1 DALI address



CANOPY WITHOUT SLOTS multi round 2-10 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø·H (mm)	ORDER CODE
DALI-2	380·43	0 0 5 - 2 6 9 1 1 3 [1]
Casambi	380·43	0 0 5 - 2 6 9 1 1 9 [1]


2 converter a 300 mA; 2 DALI addresses



CANOPY WITHOUT SLOTS multi round 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø·H (mm)	ORDER CODE
DALI-2	380·43	0 0 5 - 2 6 9 1 0 3 [1]
Casambi	380·43	0 0 5 - 2 6 9 1 0 9 [1]

1 DALI address



CANOPY multi linear 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	L·W·H (mm)	ORDER CODE
DALI-2	1000·34·50	0 0 5 - 2 6 9 2 0 3 [1]
Casambi	1000·34·50	0 0 5 - 2 6 9 2 0 9 [1]

Order options

COLOUR [1]	
traffic white RAL 9016	7
jet black RAL 9005	8