



## SASSO 100 round downlight

recessed 2 lamps


**EN** Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

**FR** Spot rond encastrable ; montage sans outil en kit de montage par système à dé clic à bille ; surface laquée ; avec bord continu ; biflamme ; caractéristiques de rayonn. précises grâce à l'optique à lentille ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K, colour warm dimming 1800 - 3000 K, tunable white 1800 - 4000 K, tunable white 2700 - 6500 K  
 CRI ≥ 90, CRI ≥ 92 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)  
 UGR ≤ 10, UGR ≤ 13, UGR ≤ 16, UGR ≤ 19  
 jusqu'à 124 lm/W  
 L80 / 50000 h, L85 / 50000 h, L90 / 50000 h  
 DALI-2, non DIM  
 front IP40, IP44, back IP20

### Types



### Couleur



### Set de montage



### Répartition de la lumière



glare control  
(UGR ≤ 16)




Colour Warm  
Dimming 1800 -  
3000 K



CRI ≥ 95 2  
SDCM  
(optional)



### SASSO 100 round downlight (tunable white)



#### MEDIUM 33°, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.1 W	2700 - 6500 K (tunable w., CRI ≥ 92)	1780 lm	74 lm/W	0 4 8 - 2 7 0 0 D 3 <input checked="" type="checkbox"/> M
27.6 W	1800 - 4000 K (tunable w., CRI ≥ 90)	1960 lm	71 lm/W	0 4 8 - 2 7 0 0 L 3 <input checked="" type="checkbox"/> M

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour matt silver, traffic white. DALI-2 power supply included


#### WIDE FLOOD 53°, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
24.1 W	2700 - 6500 K (tunable w., CRI ≥ 92)	1820 lm	76 lm/W	0 4 8 - 2 7 0 0 D 3 <input checked="" type="checkbox"/> W
27.6 W	1800 - 4000 K (tunable w., CRI ≥ 90)	2000 lm	72 lm/W	0 4 8 - 2 7 0 0 L 3 <input checked="" type="checkbox"/> W

DALI-2 power supply included



### SASSO 100 round downlight



#### SPOT 20°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.2 W, 36 Vf, 450 mA	2700 K	2x1670 lm	110 lm/W	0 4 8 - 2 7 0 0 9 1 <input checked="" type="checkbox"/> S
	3000 K	2x1720 lm	113 lm/W	0 4 8 - 2 7 0 0 0 1 <input checked="" type="checkbox"/> S
	3500 K	2x1760 lm	116 lm/W	0 4 8 - 2 7 0 0 2 1 <input checked="" type="checkbox"/> S
	4000 K	2x1800 lm	118 lm/W	0 4 8 - 2 7 0 0 1 1 <input checked="" type="checkbox"/> S
2x22.7 W, 36 Vf, 650 mA	2700 K	2x2300 lm	101 lm/W	0 4 8 - 2 7 0 0 9 1 <input checked="" type="checkbox"/> S
	3000 K	2x2330 lm	103 lm/W	0 4 8 - 2 7 0 0 0 1 <input checked="" type="checkbox"/> S
	3500 K	2x2380 lm	105 lm/W	0 4 8 - 2 7 0 0 2 1 <input checked="" type="checkbox"/> S
	4000 K	2x2440 lm	107 lm/W	0 4 8 - 2 7 0 0 1 1 <input checked="" type="checkbox"/> S

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.

#### MEDIUM 31°-34°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.2 W, 36 Vf, 450 mA	2700 K	2x1730 lm	114 lm/W	0 4 8 - 2 7 0 0 9 1 <input checked="" type="checkbox"/> M
	3000 K	2x1780 lm	117 lm/W	0 4 8 - 2 7 0 0 0 1 <input checked="" type="checkbox"/> M
	3500 K	2x1820 lm	120 lm/W	0 4 8 - 2 7 0 0 2 1 <input checked="" type="checkbox"/> M
	4000 K	2x1860 lm	122 lm/W	0 4 8 - 2 7 0 0 1 1 <input checked="" type="checkbox"/> M
2x22.7 W, 36 Vf, 650 mA	2700 K	2x2380 lm	105 lm/W	0 4 8 - 2 7 0 0 9 1 <input checked="" type="checkbox"/> M
	3000 K	2x2410 lm	106 lm/W	0 4 8 - 2 7 0 0 0 1 <input checked="" type="checkbox"/> M
	3500 K	2x2470 lm	109 lm/W	0 4 8 - 2 7 0 0 2 1 <input checked="" type="checkbox"/> M
	4000 K	2x2520 lm	111 lm/W	0 4 8 - 2 7 0 0 1 1 <input checked="" type="checkbox"/> M
2x23.8 W, 700 mA	CWD	2x2040 lm	86 lm/W	0 4 8 - 2 7 0 0 E 1 <input checked="" type="checkbox"/> M

The data values for the luminaire luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour matt silver, traffic white. CWD only for DALI-2; not for DIN-RAIL LED Driver



#### Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		

**FLOOD 38°-39°, CRI ≥ 90**


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.2 W, 36 Vf, 450 mA	2700 K	2x1650 lm	108 lm/W	0 4 8 - 2 7 0 0 9 1 <input checked="" type="checkbox"/> F
	3000 K	2x1700 lm	111 lm/W	0 4 8 - 2 7 0 0 0 1 <input checked="" type="checkbox"/> F
	3500 K	2x1740 lm	114 lm/W	0 4 8 - 2 7 0 0 2 1 <input checked="" type="checkbox"/> F
	4000 K	2x1780 lm	117 lm/W	0 4 8 - 2 7 0 0 1 1 <input checked="" type="checkbox"/> F
2x22.7 W, 36 Vf, 650 mA	2700 K	2x2270 lm	100 lm/W	0 4 8 - 2 7 0 0 9 1 <input checked="" type="checkbox"/> F
	3000 K	2x2300 lm	101 lm/W	0 4 8 - 2 7 0 0 0 1 <input checked="" type="checkbox"/> F
	3500 K	2x2350 lm	104 lm/W	0 4 8 - 2 7 0 0 2 1 <input checked="" type="checkbox"/> F
	4000 K	2x2410 lm	106 lm/W	0 4 8 - 2 7 0 0 1 1 <input checked="" type="checkbox"/> F

The data values for the luminaire luminous flux may differ for specific order options by -9%. Luminous flux value refers to colour traffic white.

**WIDE FLOOD 51°-56°, CRI ≥ 90**


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.2 W, 36 Vf, 450 mA	2700 K	2x1760 lm	115 lm/W	0 4 8 - 2 7 0 0 9 1 <input checked="" type="checkbox"/> W
	3000 K	2x1810 lm	119 lm/W	0 4 8 - 2 7 0 0 0 1 <input checked="" type="checkbox"/> W
	3500 K	2x1850 lm	122 lm/W	0 4 8 - 2 7 0 0 2 1 <input checked="" type="checkbox"/> W
	4000 K	2x1890 lm	124 lm/W	0 4 8 - 2 7 0 0 1 1 <input checked="" type="checkbox"/> W
2x22.7 W, 36 Vf, 650 mA	2700 K	2x2420 lm	106 lm/W	0 4 8 - 2 7 0 0 9 1 <input checked="" type="checkbox"/> W
	3000 K	2x2450 lm	108 lm/W	0 4 8 - 2 7 0 0 0 1 <input checked="" type="checkbox"/> W
	3500 K	2x2510 lm	111 lm/W	0 4 8 - 2 7 0 0 2 1 <input checked="" type="checkbox"/> W
	4000 K	2x2570 lm	113 lm/W	0 4 8 - 2 7 0 0 1 1 <input checked="" type="checkbox"/> W
2x23.8 W, 700 mA	CWD	2x2260 lm	95 lm/W	0 4 8 - 2 7 0 0 E 1 <input checked="" type="checkbox"/> W

CWD only for DALI-2; not for DIN-RAIL LED Driver

**Electrical mounting accessories (optional)****THROUGH WIRING CONNECTION BOX**

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

**Mounting accessories (required)****MOUNTING SET with trim 2 lamps** for intermediate ceilings, 2-25 mm

L-W-H (mm)	ORDER CODE
218-118-35	0 4 8 - 2 7 9 8 3 1 <input checked="" type="checkbox"/>


**Electrical accessories (required)****POWER SUPPLY PC2**

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
450 mA   21 W   non DIM	198-264 V AC	η 86 %	143-43-30	0 0 2 - 9 0 7 6 6
450 mA   28 W   DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 6 7
700 mA   28 W   DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 7 6
650 mA   31 W   non DIM	198-264 V AC	η 88 %	143-43-30	0 0 2 - 9 0 7 8 0
650 mA   28 W   DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 8 9

**Order options**

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		

## Electrical accessories (optional)



### DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W   PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

### DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40V

### POWER SUPPLY PRE-WIRED with junction box 28 W, PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	ORDER CODE
450 mA   DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 6 7 A
650 mA   DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 8 9 A
700 mA   DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 7 6 A
450 mA   non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 6 6 A
650 mA   non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 8 0 A
700 mA   non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 7 4 A

## Optical accessories (optional)



### HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø-H (mm)	ORDER CODE
jet black	50-3	0 0 7 - 1 9 6 5 5 9 8

## Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		