



## Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
jusqu'à 109 lm/W
L80 / 75000 h
DALI-2, non DIM
front IP20

### Types

trim




trimless




### Colours



### Set de montage



### Répartition de la lumière



# **SASSO 40** round wallwasher

recessed 1 lamp

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

FR Spot rond encastrable ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; surface laquée ; encastrement possible dans différents boîtiers ; caractéristique de rayonnement asymétrique ; avec réflecteur asymétrique (calcul spécial) pour intensités d'éclairage verticales homogènes ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée



wallwasher/ wallwasher floor inset



60 mm recess depth (DIN rail)



## **SASSO 40** round wallwasher








### WALLWASHER CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 7.0 W, | 2700 K | 760 lm | 109 lm/W | 048-284091 A |
| 36 Vf, | 3000 K | 716 lm | 103 lm/W | 048-284001 A |
| 200 mA | 3500 K | 746 lm | 107 lm/W | 048-284021 A |
| | 4000 K | 716 lm | 103 lm/W | 048-284011 A |


The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white.

## Mounting accessories (required)





### MOUNTING SET trimless for plasterboard ceilings

| COLOUR | PLASTERBOARD CEILING THICKNESS | Ø·H (mm) | ORDER CODE |
|---|---|---|---|
| traffic white | 12.5/15/25 mm | 56·29 | 048-2896117 |





### MOUNTING SET trimless for soft acoustic ceilings

| TYPE | COLOUR | CEILING THICKNESS | Ø·H (mm) | ORDER CODE |
|---|---|---|---|---|
| For Rockfon Mono® Acoustic | traffic white | 25-40 mm | 64·25 | 048-2896197 |




### MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic


| COLOUR | Ø·H (mm) | ORDER CODE |
|---|---|---|
| traffic white | 64·27 | 048-2896397 |
| jet black | 64·27 | 048-2896398 |




### MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

| COLOUR | Ø·H (mm) | ORDER CODE |
|---|---|---|
| traffic white | 60·40 | 048-2896317 |
| jet black | 60·40 | 048-2896318 |

## Mounting tools accessories (optional)




### MOUNTING TOOL for soft acoustic ceilings

| COLOUR | ORDER CODE |
|---|---|
| traffic black | 048-2895918 |

**Order options**

| COLOUR | |
|---|---|
| jet black RAL 9005 | 1 |
| matt silver | 4 |
| traffic white RAL 9016 | 7 |
| gold dust RAL 260-M | 9 |

| COLOUR | |
|---|---|
| traffic black | RAL 9017 |


## Electrical accessories (required)

**POWER SUPPLY** 200 mA, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 15 W \| DALI-2 | η 87 % | 165·29·21 | 002-90740 |
| 10 W \| non DIM | η 80 % | 65·39·20 | 002-90744 |

2 power supplies for 2 lamps variants necessary

## Electrical accessories (optional)




**DIN RAIL POWER SUPPLY BASIC** 48 V

| TYPE | INPUT VOLTAGE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|---|
| 160 W \| PC2 | 220-240 V AC | η 94 % | 72·90·63 | 005-6520210 |

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

**DIN RAIL LED DRIVER**

| TYPE | L·W·H (mm) | ORDER CODE |
|---|---|---|
| DALI-2 DT6 1-2 addresses / DT8 1 adress | 36·88·59 | 005-6121030 |

200 -1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40 V SELV

**POWER SUPPLY PRE-WIRED with junction box** DALI-2, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | ORDER CODE |
|---|---|---|
| 450 mA | η 87 % | 002-90750A |
| 200 mA | η 87 % | 002-90749A |

2 power supplies for 2 lamps variants necessary

**POWER SUPPLY with loop through function** DALI-2, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 450 mA | η 87 % | 185·30·21 | 002-90750 |
| 200 mA | η 87 % | | 002-90749 |

2 power supplies for 2 lamps variants necessary