



SASSO 60 round adjustable

recessed 2 lamps


EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; light insets rotatable and tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

FR Spot rond encastrable ; montage sans outil en kit de montage par système à déclic à bille ; surface laquée ; avec bord continu ; biflamme ; modules d'éclairage rotatif et orientable ; caractéristiques de rayonn. précises grâce à l'optique à lentille ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K,
 colour warm dimming 1800 - 3000 K
 CRI \geq 90 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
 UGR \leq 13, UGR \leq 16, UGR \leq 19
 jusqu'à 107 lm/W
 L80 / 50000 h, L85 / 50000 h
 DALI-2, non DIM
 front IP40, back IP20

Types



Couleur



Set de montage




Répartition de la lumière



360° rotatable,
 30° tiltable



glare control
 (UGR \leq 16)



Colour Warm
 Dimming 1800 -
 3000 K



SASSO 60 round adjustable



SPOT 15°, CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|-------------------------|--------------|-----------|----------|---|
| 2x10.9 W, 36 Vf, 300 mA | 2700 K | 2x879 lm | 81 lm/W | 0 4 8 - 2 6 2 2 9 1 <input checked="" type="checkbox"/> S |
| | 3000 K | 2x908 lm | 84 lm/W | 0 4 8 - 2 6 2 2 0 1 <input checked="" type="checkbox"/> S |
| | 3500 K | 2x927 lm | 85 lm/W | 0 4 8 - 2 6 2 2 2 1 <input checked="" type="checkbox"/> S |
| | 4000 K | 2x956 lm | 88 lm/W | 0 4 8 - 2 6 2 2 1 1 <input checked="" type="checkbox"/> S |

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.



MEDIUM 26°-27°, CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|-------------------------|--------------|-----------|----------|---|
| 2x10.2 W, 300 mA | CWD | 2x781 lm | 76 lm/W | 0 4 8 - 2 6 2 2 E 1 <input checked="" type="checkbox"/> M |
| 2x10.6 W, 36 Vf, 300 mA | 2700 K | 2x1040 lm | 98 lm/W | 0 4 8 - 2 6 2 2 9 1 <input checked="" type="checkbox"/> M |
| | 3000 K | 2x1080 lm | 102 lm/W | 0 4 8 - 2 6 2 2 0 1 <input checked="" type="checkbox"/> M |
| | 3500 K | 2x1110 lm | 104 lm/W | 0 4 8 - 2 6 2 2 2 1 <input checked="" type="checkbox"/> M |
| | 4000 K | 2x1130 lm | 106 lm/W | 0 4 8 - 2 6 2 2 1 1 <input checked="" type="checkbox"/> M |

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour traffic white, matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver

FLOOD 36°-41°, CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|-------------------------|--------------|-----------|----------|---|
| 2x10.2 W, 300 mA | CWD | 2x745 lm | 73 lm/W | 0 4 8 - 2 6 2 2 E 1 <input checked="" type="checkbox"/> F |
| 2x10.6 W, 36 Vf, 300 mA | 2700 K | 2x992 lm | 93 lm/W | 0 4 8 - 2 6 2 2 9 1 <input checked="" type="checkbox"/> F |
| | 3000 K | 2x1030 lm | 97 lm/W | 0 4 8 - 2 6 2 2 0 1 <input checked="" type="checkbox"/> F |
| | 3500 K | 2x1050 lm | 99 lm/W | 0 4 8 - 2 6 2 2 2 1 <input checked="" type="checkbox"/> F |
| | 4000 K | 2x1070 lm | 101 lm/W | 0 4 8 - 2 6 2 2 1 1 <input checked="" type="checkbox"/> F |


The data values for the luminaire luminous flux may differ for specific order options by -14%. Luminous flux value refers to colour traffic white, matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver

WIDE FLOOD 56°, CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|-------------------------|--------------|-----------|----------|---|
| 2x10.6 W, 36 Vf, 300 mA | 2700 K | 2x1050 lm | 98 lm/W | 0 4 8 - 2 6 2 2 9 1 <input checked="" type="checkbox"/> W |
| | 3000 K | 2x1090 lm | 102 lm/W | 0 4 8 - 2 6 2 2 0 1 <input checked="" type="checkbox"/> W |
| | 3500 K | 2x1110 lm | 104 lm/W | 0 4 8 - 2 6 2 2 2 1 <input checked="" type="checkbox"/> W |
| | 4000 K | 2x1130 lm | 107 lm/W | 0 4 8 - 2 6 2 2 1 1 <input checked="" type="checkbox"/> W |

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour traffic white, matt silver.

Electrical mounting accessories (optional)



THROUGH WIRING CONNECTION BOX


| TYPE | L-W-H (mm) | ORDER CODE |
|---------------------------|------------|-----------------------|
| non DIM cable ø 4 – 12 mm | 105-58-30 | 0 0 5 - 2 5 3 1 1 1 0 |
| DALI cable ø 4 – 12 mm | 105-58-30 | 0 0 5 - 2 5 5 1 1 1 0 |

Linect®-Ready

Order options

| COLOUR | <input checked="" type="checkbox"/> | COLOUR | <input checked="" type="checkbox"/> |
|------------------------|-------------------------------------|--------------------------|-------------------------------------|
| jet black RAL 9005 | 1 | traffic white RAL 9016 | 7 |
| matt silver | 4 | jet black RAL 9005 | 8 |
| traffic white RAL 9016 | 7 | white aluminium RAL 9006 | G |
| gold dust RAL 260-M | 9 | | |

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L-W-H (mm)
147-80-21

ORDER CODE


0 4 8 - 2 6 9 8 3 1

Electrical accessories (required)

POWER SUPPLY 300 mA, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|---------|------------|------------|-------------------|
| non DIM | η 84 % | 85-40-22 | 0 0 2 - 9 0 7 7 1 |
| DALI-2 | η 87 % | 165-29-21 | 0 0 2 - 9 0 7 9 0 |

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

| TYPE | INPUT VOLTAGE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|-------------|---------------|------------|------------|-----------------------|
| 160 W PC2 | 220-240 V AC | η 94 % | 72-90-63 | 0 0 5 - 6 5 2 0 2 1 0 |

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

DIN RAIL LED DRIVER

| TYPE | L-W-H (mm) | ORDER CODE |
|--------------------------|------------|-----------------------|
| DALI-2 DT6 1-2 addresses | 36-88-59 | 0 0 5 - 6 1 2 1 0 3 0 |

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10-40V

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

| TYPE | EFFICIENCY | ORDER CODE |
|-------------------------|------------|---------------------|
| 300 mA 15 W DALI-2 | η 87 % | 0 0 2 - 9 0 7 9 0 A |
| 250 mA 15 W DALI-2 | η 87 % | 0 0 2 - 9 0 7 4 8 A |
| 300 mA 15 W non DIM | η 84 % | 0 0 2 - 9 0 7 7 1 A |
| 250 mA 10 W non DIM | η 80 % | 0 0 2 - 9 0 7 4 2 A |

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|--------|------------|------------|-------------------|
| 300 mA | η 87 % | 185-30-21 | 0 0 2 - 9 0 7 7 0 |
| 250 mA | η 87 % | 185-30-21 | 0 0 2 - 9 0 7 4 7 |

Order options

| COLOUR | | COLOUR | |
|------------------------|---|--------------------------|---|
| jet black RAL 9005 | 1 | traffic white RAL 9016 | 7 |
| matt silver | 4 | jet black RAL 9005 | 8 |
| traffic white RAL 9016 | 7 | white aluminium RAL 9006 | G |
| gold dust RAL 260-M | 9 | | |