



SASSO 60 round wallwasher/floor

recessed 1 lamp

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

FR Spot rond encastrable ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à dé clic à bille ; surface laquée ; encastrément possible dans différents boîtiers ; caractéristique de rayonnement asymétrique ; avec réflecteur asymétrique (calcul spécial) pour intensités d'éclairage verticales homogènes ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 90 / 2 SDCM (initial MacAdam)
 jusqu'à 118 lm/W
 L85 / 50000 h
 DALI-2, non DIM
 front IP20

Types



Couleur



Set de montage



Répartition de la lumière



wallwasher/
wallwasher floor
inset



60 mm
recessed depth
(non DIM)



quick mounting
in soft acoustic
ceilings



SASSO 60 round wallwasher/floor




WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W,	2700 K	1050 lm	118 lm/W	0 4 8 - 2 6 4 1 9 1 <input checked="" type="checkbox"/> W
36 Vf,	3000 K	985 lm	111 lm/W	0 4 8 - 2 6 4 1 0 1 <input checked="" type="checkbox"/> W
250 mA	3500 K	1030 lm	116 lm/W	0 4 8 - 2 6 4 1 2 1 <input checked="" type="checkbox"/> W
	4000 K	985 lm	111 lm/W	0 4 8 - 2 6 4 1 1 1 <input checked="" type="checkbox"/> W



Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)




MOUNTING SET trimless for plasterboard ceilings

COLOUR	PLASTERBOARD CEILING THICKNESS	Ø-H (mm)	ORDER CODE
traffic white	12.5/15/25 mm	73-29	0 4 8 - 2 6 9 6 1 1 7

for SASSO 60 round | SPIO 60 downlight


* SASSO 60
** SPIO 60



MOUNTING SET trimless for soft acoustic ceilings

COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
traffic white	25-40 mm	80-25	0 4 8 - 2 6 9 6 1 9 7


loop through function



MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	80-27	0 4 8 - 2 6 9 6 3 9 7
jet black	80-27	0 4 8 - 2 6 9 6 3 9 8

loop through function



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm


COLOUR	Ø-H (mm)	ORDER CODE
traffic white	80-40	0 4 8 - 2 6 9 6 3 1 7
jet black	80-40	0 4 8 - 2 6 9 6 3 1 8
white aluminium	80-40	0 4 8 - 2 6 9 6 3 1 G

loop through function

Order options


COLOUR	<input checked="" type="checkbox"/>	COLOUR
jet black RAL 9005	1	white aluminium RAL 9006
matt silver	4	traffic black RAL 9017
traffic white RAL 9016	7	
gold dust RAL 260-M	9	

Mounting accessories (optional)



EXPOSED CONCRETE MOUNTING HOUSING

COLOUR	L-W-H (mm)	ORDER CODE
white aluminium	230-230-162	0 4 8 - 2 6 9 5 2 1 0



PRIMED CONCRETE MOUNTING HOUSING

L-W-H (mm)	ORDER CODE
614-307-120	0 4 8 - 2 6 9 5 1 1 0

order mounting set separately

Mounting tools accessories (optional)



MOUNTING TOOL for soft acoustic ceilings


COLOUR	L-W-H (mm)	ORDER CODE
traffic black	77-77-35	0 4 8 - 2 6 9 5 9 1 8

Electrical accessories (required)

POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
10 W non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 2
15 W DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 4 8

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10-40V

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 9 0 A
250 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 4 8 A
300 mA 15 W non DIM	η 84 %	0 0 2 - 9 0 7 7 1 A
250 mA 10 W non DIM	η 80 %	0 0 2 - 9 0 7 4 2 A

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
300 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 7 0
250 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 4 7

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
matt silver	4	traffic black	RAL 9017
traffic white RAL 9016	7		
gold dust RAL 260-M	9		