



## SASSO 60 round wallwasher/floor

recessed 2 lamps

**EN** Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

**FR** Spot rond encastrable ; montage sans outil en kit de montage par système à déclic à bille ; surface laquée ; avec bord continu ; biflamme ; caractéristique de rayonnement asymétrique ; avec réflecteur asymétrique (calcul spécial) pour intensités d'éclairage verticales homogènes ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
CRI  $\geq$  90 / 2 SDCM (initial MacAdam)  
jusqu'à 118 lm/W  
L85 / 50000 h  
DALI-2, non DIM  
front IP20

### Types

double trim



### Couleur



### Set de montage



### Répartition de la lumière



wallwasher/  
wallwasher floor  
inset



## SASSO 60 round wallwasher/floor




### WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x8.9 W,	2700 K	2x1050 lm	118 lm/W	0 4 8 - 2 6 4 1 9 1 <input checked="" type="checkbox"/> W
36 Vf,	3000 K	2x985 lm	111 lm/W	0 4 8 - 2 6 4 1 0 1 <input checked="" type="checkbox"/> W
250 mA	3500 K	2x1030 lm	116 lm/W	0 4 8 - 2 6 4 1 2 1 <input checked="" type="checkbox"/> W
	4000 K	2x985 lm	111 lm/W	0 4 8 - 2 6 4 1 1 1 <input checked="" type="checkbox"/> W



## Electrical mounting accessories (optional)




### THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

## Mounting accessories (required)



### MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm


L-W-H (mm)	ORDER CODE
147-80-21	0 4 8 - 2 6 9 8 3 1 <input checked="" type="checkbox"/>

## Electrical accessories (required)

### POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
10 W   non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 2
15 W   DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 4 8

## Electrical accessories (optional)



### DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W   PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

### DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 -1050 mA settable const. current | 2x42W | 48V DC | U OUT 10-40V SELV

## Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		

**POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2**

TYPE	EFFICIENCY	ORDER CODE
300 mA   15 W   DALI-2	$\eta$ 87 %	0 0 2 - 9 0 7 9 0 A
250 mA   15 W   DALI-2	$\eta$ 87 %	0 0 2 - 9 0 7 4 8 A
300 mA   15 W   non DIM	$\eta$ 84 %	0 0 2 - 9 0 7 7 1 A
250 mA   10 W   non DIM	$\eta$ 80 %	0 0 2 - 9 0 7 4 2 A

**POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2**

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
300 mA	$\eta$ 87 %	185-30-21	0 0 2 - 9 0 7 7 0
250 mA	$\eta$ 87 %	185-30-21	0 0 2 - 9 0 7 4 7

**Order options**

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		