




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
jusqu'à 113 lm/W
L80 / 75000 h
DALI-2, non DIM
front IP20

Types



Colours



Set de montage



Répartition de la lumière



SASSO 60 round wallwasher


recessed 2 lamps

EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminium-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

FR Spot rond encastrable ; montage sans outil en kit de montage par système à déclic à bille ; surface laquée ; avec bord continu ; biflamme ; caractéristique de rayonnement asymétrique ; avec réflecteur asymétrique (calcul spécial) pour intensités d'éclairage verticales homogènes ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée



SASSO 60 round wallwasher






WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W, 36 Vf, 250 mA	2700 K	1890 lm	106 lm/W	048-264191 A
	3000 K	1890 lm	106 lm/W	048-264101 A
	3500 K	1970 lm	111 lm/W	048-264121 A
	4000 K	2000 lm	113 lm/W	048-264111 A

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white. 2 insets necessary, order code only applies to 1 inset

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 10
DALI cable ø 4 – 12 mm	105·58·30	005-255111 10

Linect®-Ready

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L·W·H (mm)	ORDER CODE
147·80·21	048-269831 1


Electrical accessories (required)

POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
10 W | non DIM	η 80 %	65·39·20	002-90742
15 W | DALI-2	η 87 %	165·29·21	002-90748

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8
white aluminium RAL 9006	G

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 -1050 mA settable const. current | 2 × 42W | 48V DC | U OUT 10 – 40 V SELV

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA | 15 W | DALI-2	η 87 %	002-90790A
250 mA | 15 W | DALI-2	η 87 %	002-90748A
300 mA | 15 W | non DIM	η 84 %	002-90771A
250 mA | 10 W | non DIM	η 80 %	002-90742A

2 power supplies for 2 lamps variants necessary

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
300 mA	η 87 %	185·30·21	002-90770
250 mA	η 87 %	185·30·21	002-90747

2 power supplies for 2 lamps variants necessary