




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
jusqu'à 117 lm/W
L80 / 75000 h
DALI-2, non DIM
front IP20

Types



Colours



Set de montage



Répartition de la lumière



SASSO 60 square wallwasher

recessed 1 lamp

EN Square recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

FR Spot carré encastrable ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; surface laquée ; encastrement possible dans différents boîtiers ; caractéristique de rayonnement asymétrique ; avec réflecteur asymétrique (calcul spécial) pour intensités d'éclairage verticales homogènes ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée



wallwasher/
wallwasher floor inset



60 mm
recessed depth




CRI ≥ 95 2 SDCM
(optional)



SASSO 60 square wallwasher

CRI ≥ 90 · 2 SDCM · DALI · 1 ADDR. · X-PERT




WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W, 36 Vf, 250 mA	2700 K	973 lm	110 lm/W	048-265191 ◪ A
	3000 K	972 lm	110 lm/W	048-265101 ◪ A
	3500 K	1010 lm	114 lm/W	048-265121 ◪ A
	4000 K	1030 lm	117 lm/W	048-265111 ◪ A

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white, matt silver. 2 insets necessary, order code only applies 1 inset

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253110
DALI cable ø 4 – 12 mm	105·58·30	005-255110


Linect®-Ready

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings


COLOUR	PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
traffic white	12.5/15/25 mm	72·72·29	048-269711 7



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
traffic white	80·80·21	048-269731 7
jet black	80·80·21	048-269731 8
white aluminium	80·80·21	048-269731 G

Mounting accessories (optional)



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	048-269511 0

order mounting set separately

Order options

COLOUR	◪
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

COLOUR	
white aluminium	RAL 9006


Electrical accessories (required)

POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
10 W | non DIM	η 80 %	65·39·20	0 0 2 - 9 0 7 4 2
15 W | DALI-2	η 87 %	165·29·21	0 0 2 - 9 0 7 4 8

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	0 0 5 - 6 1 2 1 0 3 0

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA | 15 W | DALI-2	η 87 %	0 0 2 - 9 0 7 9 0 A
250 mA | 15 W | DALI-2	η 87 %	0 0 2 - 9 0 7 4 8 A
300 mA | 15 W | non DIM	η 84 %	0 0 2 - 9 0 7 7 1 A
250 mA | 10 W | non DIM	η 80 %	0 0 2 - 9 0 7 4 2 A

2 power supplies for 2 lamps variants necessary

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
300 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 7 0
250 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 4 7

2 power supplies for 2 lamps variants necessary