



## Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
jusqu'à 117 lm/W
L80 / 75000 h
DALI-2, non DIM
front IP20

### Types




### Colours

### Set de montage

### Répartition de la lumière

# **SASSO 60** square wallwasher

recessed 2 lamps

EN Square recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminium-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

FR Spot carré encastrable ; montage sans outil en kit de montage par système à déclic à bille ; surface laquée ; avec bord continu ; biflamme ; caractéristique de rayonnement asymétrique ; avec réflecteur asymétrique (calcul spécial) pour intensités d'éclairage verticales homogènes ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée



wallwasher/
wallwasher floor
inset



60 mm
recessed depth



CRI ≥ 95 2
SDCM
(optional)



## **SASSO 60** square wallwasher

CRI ≥ 90 | 2 SDCM | III | DALI 1 ADDR. | X-PERT




### WALLWASHER CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 8.9 W, 36 Vf, 250 mA | 2700 K | 1950 lm | 110 lm/W | 048-265191 A |
| | 3000 K | 1940 lm | 110 lm/W | 048-265101 A |
| | 3500 K | 2020 lm | 114 lm/W | 048-265121 A |
| | 4000 K | 2060 lm | 117 lm/W | 048-265111 A |

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white, matt silver. 2 insets necessary, order code only applies to 1 inset

## Electrical mounting accessories (optional)




### THROUGH WIRING CONNECTION BOX

| TYPE | L·W·H (mm) | ORDER CODE |
|---|---|---|
| non DIM cable ø 4 – 12 mm | 105·58·30 | 005-253111 10 |
| DALI cable ø 4 – 12 mm | 105·58·30 | 005-255111 10 |

Linect®-Ready

## Mounting accessories (required)




### MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

| L·W·H (mm) | ORDER CODE |
|---|---|
| 147·81·35 | 048-269931 1 |

## Electrical accessories (required)

### POWER SUPPLY 250 mA, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 10 W \| non DIM | η 80 % | 65·39·20 | 002-90742 |
| 15 W \| DALI-2 | η 87 % | 165·29·21 | 002-90748 |

2 power supplies for 2 lamps variants necessary

## Electrical accessories (optional)




### DIN RAIL POWER SUPPLY BASIC 48 V

| TYPE | INPUT VOLTAGE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|---|
| 160 W \| PC2 | 220-240 V AC | η 94 % | 72·90·63 | 005-652021 0 |

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

## Order options

| COLOUR | |
|---|---|
| jet black RAL 9005 | 1 |
| matt silver | 4 |
| traffic white RAL 9016 | 7 |
| gold dust RAL 260-M | 9 |

| COLOUR | |
|---|---|
| traffic white RAL 9016 | 7 |
| jet black RAL 9005 | 8 |
| white aluminium RAL 9006 | G |

**DIN RAIL LED DRIVER**

| TYPE | L·W·H (mm) | ORDER CODE |
|---|---|---|
| DALI-2 DT6 1-2 addresses / DT8 1 adress | 36·88·59 | 005-612103 0 |

200 -1050 mA settable const. current | 2 × 42W | 48V DC | U OUT 10 – 40 V SELV

**POWER SUPPLY PRE-WIRED with junction box** 198-264 V AC, PC2

| TYPE | EFFICIENCY | ORDER CODE |
|---|---|---|
| 300 mA \| 15 W \| DALI-2 | η 87 % | 002-90790A |
| 250 mA \| 15 W \| DALI-2 | η 87 % | 002-90748A |
| 300 mA \| 15 W \| non DIM | η 84 % | 002-90771A |
| 250 mA \| 10 W \| non DIM | η 80 % | 002-90742A |

2 power supplies for 2 lamps variants necessary

**POWER SUPPLY with loop through function** DALI-2, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 300 mA | η 87 % | 185·30·21 | 002-90770 |
| 250 mA | η 87 % | 185·30·21 | 002-90747 |

2 power supplies for 2 lamps variants necessary