



MINO 25

surface


EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 25 x 25mm); no visible screws; surface raw or powder coated; suitable for ceiling mounting; high quality reflector with micro-faceted, aluminum-vaporised surface; or fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; precise radiation characteristic with symmetrical light distribution; or completely homogeneously illuminated, opal cover; converter integrated into luminaire housing; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en profil extrudé en alu, version arête ; forme extrêmement élancée (seulement 25 x 25 mm) ; aucune vis visible ; surface brute ou thermolaquée ; approprié pour montage au plafond ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; ou équipé de points lumineux à LED simples ; bon anti-éblouissement grâce aux points lumineux en retrait ; malgré tout efficacité accrue grâce à une tech. de lentilles spéciale ; lentilles utilisées avec caractéristique de rayonnement wide flood ; caractéristique d'émission précise avec répartition symétrique de la lumière ; ou éclairage parfaitement homogène, cache opale ; convertisseur intégré dans le corps de luminaire ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000 K, 4000 K
 CRI ≥ 80, CRI ≥ 90 / 3 SDCM
 (initial MacAdam)
 UGR ≤ 16, UGR ≤ 19
 jusqu'à 168 lm/W
 L90 / 100000 h
 Cache : Opal, Wideflood
 DALI-2
 IP20

Types



Colours



Insert




Répartition de la lumière




black & chrome
louver



up to 168 lm/W
(high efficiency)



super slim
design





MINO 25 opal surface




OPAL DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
9.5 W	1004 mm	80	1220 lm	128 lm/W	0 4 3 - 0 1 2 1 : 3 3 O
		90	1000 lm	105 lm/W	0 4 3 - 0 1 2 1 : 3 3 O
18.3 W	2004 mm	80	2450 lm	134 lm/W	0 4 3 - 0 1 2 2 : 3 3 O
		90	2000 lm	109 lm/W	0 4 3 - 0 1 2 2 : 3 3 O
25.2 W	2754 mm	80	3370 lm	134 lm/W	0 4 3 - 0 1 2 3 : 3 3 O
		90	2760 lm	110 lm/W	0 4 3 - 0 1 2 3 : 3 3 O

The data values for the luminous flux may differ for specific order options by -12%. Luminous flux value refers to colour temperature 4000 K.





MINO 25 louver surface




LOUVER DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
10.7 W	1004 mm	80	1730 lm	162 lm/W	0 4 3 - 0 1 0 1 : 3 3 X
		90	1420 lm	133 lm/W	0 4 3 - 0 1 0 1 : 3 3 X
20.6 W	2004 mm	80	3470 lm	168 lm/W	0 4 3 - 0 1 0 2 : 3 3 X
		90	2840 lm	138 lm/W	0 4 3 - 0 1 0 2 : 3 3 X
27.5 W	2754 mm	80	4630 lm	168 lm/W	0 4 3 - 0 1 0 3 : 3 3 X
		90	3790 lm	138 lm/W	0 4 3 - 0 1 0 3 : 3 3 X

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour temperature 4000 K.




MINO 25 spotline surface



SPOTLINE DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
10.7 W	1004 mm	80	1710 lm	160 lm/W	0 4 3 - 0 1 1 1 : 3 3 W
		90	1400 lm	131 lm/W	0 4 3 - 0 1 1 1 : 3 3 W
20.6 W	2004 mm	80	3410 lm	166 lm/W	0 4 3 - 0 1 1 2 : 3 3 W
		90	2790 lm	135 lm/W	0 4 3 - 0 1 1 2 : 3 3 W
27.5 W	2754 mm	80	4560 lm	166 lm/W	0 4 3 - 0 1 1 3 : 3 3 W
		90	3730 lm	136 lm/W	0 4 3 - 0 1 1 3 : 3 3 W

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inset traffic white colour temperature 4000 K.



Order options

COLOUR TEMPERATURE		COLOUR TEMPERATURE		COLOUR		INSET	
3000 K	0	3000 K	5	aluminium raw	0	chrome reflector	4
4000 K	1	4000 K	6	signal white RAL 9003	7	black reflector	8
				signal black RAL 9004	8		

INSET	
traffic white RAL 9016	7
jet black RAL 9005	8