

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
L90 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours



Set de montage



Répartition de la lumière






UNICO Q1 / Q4

recessed

EN Square recessed multi-downlight made of die-cast aluminium; equipped with one (Q1) / four (Q4) individually selectable or pre-specified, customised light element(s); or with a sensor; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering

FR Multi-Downlight carré en aluminium moulé sous pression pour encastrement ; équipé d'un (Q1) / quatre (Q4) éléments optiques à choisir de façon personnalisée ou définis de manière fixe, spécifiques à chaque application ; ou avec un capteur (Q1) ; montage sans outil en kit de montage par système à déclic à bille ; installation électrique facile par enfichage protégé contre les inversions de polarité ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; encastrement possible dans différents boîtiers ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; caractéristique de diffusion précise avec différentes possibilités de répartitions symétriques de la lumière ; ou avec distribution asymétrique de la lumière ; High-Power-LED à grande efficacité énergétique, très bon rendu des couleurs



black & chrome reflector




one luminaire multiple scenes




up to 145 lm/W (high efficiency)



tunable white 2700 – 5000 K (optional)





UNICO Q1

CRI ≥ 90 · 2 SDCM · 1 ADDR. · X-PERT · X-PERT

MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	lm	0 9 0 - 7 Q 1 9 ⇕ B 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 1 0 ⇕ B 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 1 2 ⇕ B 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 1 1 ⇕ B 0 ◪ 4 1

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	lm	0 9 0 - 7 Q 1 9 ⇕ C 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 1 0 ⇕ C 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 1 2 ⇕ C 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 1 1 ⇕ C 0 ◪ 4 1

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	lm	0 9 0 - 7 Q 1 9 ⇕ D 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 1 0 ⇕ D 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 1 2 ⇕ D 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 1 1 ⇕ D 0 ◪ 4 1

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	lm	0 9 0 - 7 Q 1 9 ⇕ K 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 1 0 ⇕ K 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 1 2 ⇕ K 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 1 1 ⇕ K 0 ◪ 4 1

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	lm	0 9 0 - 7 Q 1 9 ⇕ E 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 1 0 ⇕ E 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 1 2 ⇕ E 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 1 1 ⇕ E 0 ◪ 4 1

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	lm	0 9 0 - 7 Q 1 9 ⇕ F 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 1 0 ⇕ F 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 1 2 ⇕ F 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 1 1 ⇕ F 0 ◪ 4 1

Order options

CONTROL ⇕		COLOUR ◪	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	lm	0 9 0 - 7 Q 1 9 ⇕ G 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 1 0 ⇕ G 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 1 2 ⇕ G 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 1 1 ⇕ G 0 ◪ 4 1

RECTANGULAR MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	lm	0 9 0 - 7 Q 1 9 ⇕ R 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 1 0 ⇕ R 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 1 2 ⇕ R 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 1 1 ⇕ R 0 ◪ 4 1

WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	374 lm	0 9 0 - 7 Q 1 9 ⇕ A 0 0 4 1
	3000 K	374 lm	0 9 0 - 7 Q 1 0 ⇕ A 0 0 4 1
	3500 K	390 lm	0 9 0 - 7 Q 1 2 ⇕ A 0 0 4 1
	4000 K	398 lm	0 9 0 - 7 Q 1 1 ⇕ A 0 0 4 1

WALLWASHER FLOOR CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
4.5 W	2700 K	440 lm	0 9 0 - 7 Q 1 9 ⇕ W 0 ◪ 4 1
	3000 K	440 lm	0 9 0 - 7 Q 1 0 ⇕ W 0 ◪ 4 1
	3500 K	458 lm	0 9 0 - 7 Q 1 2 ⇕ W 0 ◪ 4 1
	4000 K	468 lm	0 9 0 - 7 Q 1 1 ⇕ W 0 ◪ 4 1







UNICO Q4



MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	0 9 0 - 7 Q 4 9 ⇕ B 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 4 0 ⇕ B 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 4 2 ⇕ B 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 4 1 ⇕ B 0 ◪ 4 1

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	0 9 0 - 7 Q 4 9 ⇕ C 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 4 0 ⇕ C 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 4 2 ⇕ C 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 4 1 ⇕ C 0 ◪ 4 1

Order options

CONTROL	⇕	COLOUR	◪	COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7Q49 ⇕ D0 ◪ 41
	3000 K	lm	090-7Q40 ⇕ D0 ◪ 41
	3500 K	lm	090-7Q42 ⇕ D0 ◪ 41
	4000 K	lm	090-7Q41 ⇕ D0 ◪ 41

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7Q49 ⇕ K0 ◪ 41
	3000 K	lm	090-7Q40 ⇕ K0 ◪ 41
	3500 K	lm	090-7Q42 ⇕ K0 ◪ 41
	4000 K	lm	090-7Q41 ⇕ K0 ◪ 41

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7Q49 ⇕ E0 ◪ 41
	3000 K	lm	090-7Q40 ⇕ E0 ◪ 41
	3500 K	lm	090-7Q42 ⇕ E0 ◪ 41
	4000 K	lm	090-7Q41 ⇕ E0 ◪ 41

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7Q49 ⇕ F0 ◪ 41
	3000 K	lm	090-7Q40 ⇕ F0 ◪ 41
	3500 K	lm	090-7Q42 ⇕ F0 ◪ 41
	4000 K	lm	090-7Q41 ⇕ F0 ◪ 41

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7Q49 ⇕ G0 ◪ 41
	3000 K	lm	090-7Q40 ⇕ G0 ◪ 41
	3500 K	lm	090-7Q42 ⇕ G0 ◪ 41
	4000 K	lm	090-7Q41 ⇕ G0 ◪ 41

WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	1140 lm	090-7Q49 ⇕ A0041
	3000 K	1140 lm	090-7Q40 ⇕ A0041
	3500 K	1190 lm	090-7Q42 ⇕ A0041
	4000 K	1210 lm	090-7Q41 ⇕ A0041

Order options

CONTROL ⇕		COLOUR ◪		COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016


CORRIDOR chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	1140 lm	0 9 0 - 7 Q 4 9 ⇕ A 0 0 4 2
	3000 K	1140 lm	0 9 0 - 7 Q 4 0 ⇕ A 0 0 4 2
	3500 K	1190 lm	0 9 0 - 7 Q 4 2 ⇕ A 0 0 4 2
	4000 K	1210 lm	0 9 0 - 7 Q 4 1 ⇕ A 0 0 4 2

WALLWASHER FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	1340 lm	0 9 0 - 7 Q 4 9 ⇕ W 0 ◪ 4 1
	3000 K	1340 lm	0 9 0 - 7 Q 4 0 ⇕ W 0 ◪ 4 1
	3500 K	1400 lm	0 9 0 - 7 Q 4 2 ⇕ W 0 ◪ 4 1
	4000 K	1430 lm	0 9 0 - 7 Q 4 1 ⇕ W 0 ◪ 4 1

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready


Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	47·47·47	0 9 0 - 7 Q 1 0 1 0 0

for UNICO Q1



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	85·85·47	0 9 0 - 7 Q 4 0 1 0 0


for UNICO Q4 | UNICO wall recessed 2 lamps



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	63·63·30	0 9 0 - 7 Q 1 0 2 0 B
traffic white	63·63·30	0 9 0 - 7 Q 1 0 2 0 W

for UNICO Q1



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	101·101·30	0 9 0 - 7 Q 4 0 2 0 B
traffic white	101·101·30	0 9 0 - 7 Q 4 0 2 0 W

for UNICO Q4 | UNICO wall recessed 2 lamps

Order options


CONTROL	⇕	COLOUR	◪	COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016

Mounting tools accessories (optional)

DISMOUNTING TOOL

L·W·H (mm)	ORDER CODE
70·30·2	090-002100

Electrical accessories (optional)



POWER SUPPLY pre-wired

Available in the configurator	see POWER SUPPLY PRE-WIRED

De House, Saint Niklaas

Belgique

Architecte
Jacobsen Arquitectura

Lighting Design
Rodrigo Jardim
(Illumination Strategic
Design Group)

Photographe
Didier Engels Fernando
Guerra FG+SG



Produits utilisés



**UNICO Q1 / Q4
recessed**

No liability is assumed for
typographical or printing errors.
© XAL GmbH · Auer-Welsbach-
Gasse 36 · 8055 Graz · Austria ·
www.xal.com







https://xal.com/fr/decouvrir-lumiere/projets/pr/de-house-saint-niklaas-578645





