



Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
L90 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours



Set de montage



Répartition de la lumière






UNICO L4 / L6

recessed

EN Rectangular recessed multi-downlight made of die-cast aluminium; equipped with four (L4) / six (L6) individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminium-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering

FR Multi-Downlight rectangulaire en aluminium moulé sous pression pour encastrement ; équipé de quatre (L4) / six (L6) éléments optiques à choisir de façon personnalisée ou définis de manière fixe, spécifiques à chaque application ; montage sans outil en kit de montage par système à déclic à bille ; installation électrique facile par enfichage protégé contre les inversions de polarité ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; encastrement possible dans différents boîtiers ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; caractéristique de diffusion précise avec différentes possibilités de répartitions symétriques de la lumière ; ou avec distribution asymétrique de la lumière ; High-Power-LED à grande efficacité énergétique, très bon rendu des couleurs



black & chrome reflector



one luminaire multiple scenes




up to 145 lm/W (high efficiency)



tunable white 2700 – 5000 K (optional)







UNICO L4

CRI ≥ 90 · 2 SDCM · 1 ADDR. · X-PERT · X-PERT

MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 ◆ B0 ◪ 41
	3000 K	lm	090-7L40 ◆ B0 ◪ 41
	3500 K	lm	090-7L42 ◆ B0 ◪ 41
	4000 K	lm	090-7L41 ◆ B0 ◪ 41

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 ◆ C0 ◪ 41
	3000 K	lm	090-7L40 ◆ C0 ◪ 41
	3500 K	lm	090-7L42 ◆ C0 ◪ 41
	4000 K	lm	090-7L41 ◆ C0 ◪ 41

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 ◆ D0 ◪ 41
	3000 K	lm	090-7L40 ◆ D0 ◪ 41
	3500 K	lm	090-7L42 ◆ D0 ◪ 41
	4000 K	lm	090-7L41 ◆ D0 ◪ 41

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 ◆ K0 ◪ 41
	3000 K	lm	090-7L40 ◆ K0 ◪ 41
	3500 K	lm	090-7L42 ◆ K0 ◪ 41
	4000 K	lm	090-7L41 ◆ K0 ◪ 41

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 ◆ E0 ◪ 41
	3000 K	lm	090-7L40 ◆ E0 ◪ 41
	3500 K	lm	090-7L42 ◆ E0 ◪ 41
	4000 K	lm	090-7L41 ◆ E0 ◪ 41

Order options

CONTROL ◆		COLOUR ◪	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 ⇕ F0 ◪ 41
	3000 K	lm	090-7L40 ⇕ F0 ◪ 41
	3500 K	lm	090-7L42 ⇕ F0 ◪ 41
	4000 K	lm	090-7L41 ⇕ F0 ◪ 41

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	lm	090-7L49 ⇕ G0 ◪ 41
	3000 K	lm	090-7L40 ⇕ G0 ◪ 41
	3500 K	lm	090-7L42 ⇕ G0 ◪ 41
	4000 K	lm	090-7L41 ⇕ G0 ◪ 41

WALLWASHER chrome reflector, CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	1140 lm	090-7L49 ⇕ A0041
	3000 K	1140 lm	090-7L40 ⇕ A0041
	3500 K	1190 lm	090-7L42 ⇕ A0041
	4000 K	1210 lm	090-7L41 ⇕ A0041

WALL FLOOR CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
11.0 W	2700 K	1340 lm	090-7L49 ⇕ W0 ◪ 42
	3000 K	1340 lm	090-7L40 ⇕ W0 ◪ 42
	3500 K	1400 lm	090-7L42 ⇕ W0 ◪ 42
	4000 K	1430 lm	090-7L41 ⇕ W0 ◪ 42







UNICO L6



MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ B0 ◪ 41
	3000 K	lm	090-7L60 ⇕ B0 ◪ 41
	3500 K	lm	090-7L62 ⇕ B0 ◪ 41
	4000 K	lm	090-7L61 ⇕ B0 ◪ 41

Order options

CONTROL	⇕	COLOUR	◪	COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ C0 ◪ 41
	3000 K	lm	090-7L60 ⇕ C0 ◪ 41
	3500 K	lm	090-7L62 ⇕ C0 ◪ 41
	4000 K	lm	090-7L61 ⇕ C0 ◪ 41

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ D0 ◪ 41
	3000 K	lm	090-7L60 ⇕ D0 ◪ 41
	3500 K	lm	090-7L62 ⇕ D0 ◪ 41
	4000 K	lm	090-7L61 ⇕ D0 ◪ 41

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ K0 ◪ 41
	3000 K	lm	090-7L60 ⇕ K0 ◪ 41
	3500 K	lm	090-7L62 ⇕ K0 ◪ 41
	4000 K	lm	090-7L61 ⇕ K0 ◪ 41

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ E0 ◪ 41
	3000 K	lm	090-7L60 ⇕ E0 ◪ 41
	3500 K	lm	090-7L62 ⇕ E0 ◪ 41
	4000 K	lm	090-7L61 ⇕ E0 ◪ 41

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ F0 ◪ 41
	3000 K	lm	090-7L60 ⇕ F0 ◪ 41
	3500 K	lm	090-7L62 ⇕ F0 ◪ 41
	4000 K	lm	090-7L61 ⇕ F0 ◪ 41

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ G0 ◪ 41
	3000 K	lm	090-7L60 ⇕ G0 ◪ 41
	3500 K	lm	090-7L62 ⇕ G0 ◪ 41
	4000 K	lm	090-7L61 ⇕ G0 ◪ 41

Order options

CONTROL ⇕		COLOUR ◪	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B

RECTANGULAR MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	lm	090-7L69 ⇕ R0 ◪ 41
	3000 K	lm	090-7L60 ⇕ R0 ◪ 41
	3500 K	lm	090-7L62 ⇕ R0 ◪ 41
	4000 K	lm	090-7L61 ⇕ R0 ◪ 41


WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	1710 lm	090-7L69 ⇕ A0041
	3000 K	1710 lm	090-7L60 ⇕ A0041
	3500 K	1780 lm	090-7L62 ⇕ A0041
	4000 K	1820 lm	090-7L61 ⇕ A0041

WALL FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
16.5 W	2700 K	2010 lm	090-7L69 ⇕ W0 ◪ 41
	3000 K	2010 lm	090-7L60 ⇕ W0 ◪ 41
	3500 K	2100 lm	090-7L62 ⇕ W0 ◪ 41
	4000 K	2140 lm	090-7L61 ⇕ W0 ◪ 41

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253 1110
DALI cable ø 4 – 12 mm	105·58·30	005-255 1110

Linect®-Ready


Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	160·47·47	090-7L40100

for UNICO L4




MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	235·47·47	090-7L60100

for UNICO L6

Order options


CONTROL	⇕	COLOUR	◪	COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	176·63·30	090-7L4020B
traffic white	176·63·30	090-7L4020W

for UNICO L4



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	251·63·30	090-7L6020B
traffic white	251·63·30	090-7L6020W


for UNICO L6

Mounting tools accessories (optional)

DISMOUNTING TOOL

L·W·H (mm)	ORDER CODE
70·30·2	090-002100

Electrical accessories (optional)



POWER SUPPLY pre-wired

Available in the configurator — see POWER SUPPLY PRE-WIRED

Order options

COLOUR

jet black	RAL 9005
traffic white	RAL 9016

Gasthaus Vilsalpsee, Tannheim

Autriche

Architecte
Mario Gasser
Architecture

Photographe
Christian Flatscher Mario
Gasser Architecture




Produits utilisés



SASSO 60 round wall



UNICO L4 / L6 recessed



SASSO 60 round downlight recessed 1 lamp

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com







