

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 16, UGR ≤ 19, UGR ≤ 22, UGR ≤ 25
jusqu'à 143 lm/W
L90 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours



Set de montage



Répartition de la lumière




UNICO Q9

recessed

EN Square recessed multi-downlight made of die-cast aluminium; equipped with nine individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminium-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering

FR Multi-Downlight carré en aluminium moulé sous pression pour encastrement ; équipé de neuf éléments optiques à choisir de façon personnalisée ou définis de manière fixe, spécifiques à chaque application ; montage sans outil en kit de montage par système à déclic à bille ; installation électrique facile par enfichage protégé contre les inversions de polarité ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; encastrement possible dans différents boîtiers ; réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; caractéristique de diffusion précise avec différentes possibilités de répartitions symétriques de la lumière ; ou avec distribution asymétrique de la lumière ; High-Power-LED à grande efficacité énergétique, très bon rendu des couleurs



black & chrome reflector



one luminaire multiple scenes




up to 145 lm/W (high efficiency)



tunable white 2700 – 5000 K (optional)







UNICO Q9



MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ B 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ B 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ B 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ B 0 ◪ 4 1

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ C 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ C 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ C 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ C 0 ◪ 4 1

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ D 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ D 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ D 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ D 0 ◪ 4 1

SPOT ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ K 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ K 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ K 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ K 0 ◪ 4 1

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	0 9 0 - 7 Q 9 9 ⇕ E 0 ◪ 4 1
	3000 K	lm	0 9 0 - 7 Q 9 0 ⇕ E 0 ◪ 4 1
	3500 K	lm	0 9 0 - 7 Q 9 2 ⇕ E 0 ◪ 4 1
	4000 K	lm	0 9 0 - 7 Q 9 1 ⇕ E 0 ◪ 4 1

Order options

CONTROL ⇕		COLOUR ◪	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090-7Q99 ⇕ F0 ◪ 41
	3000 K	lm	090-7Q90 ⇕ F0 ◪ 41
	3500 K	lm	090-7Q92 ⇕ F0 ◪ 41
	4000 K	lm	090-7Q91 ⇕ F0 ◪ 41

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	lm	090-7Q99 ⇕ G0 ◪ 41
	3000 K	lm	090-7Q90 ⇕ G0 ◪ 41
	3500 K	lm	090-7Q92 ⇕ G0 ◪ 41
	4000 K	lm	090-7Q91 ⇕ G0 ◪ 41


WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	2660 lm	090-7Q99 ⇕ A0041
	3000 K	2660 lm	090-7Q90 ⇕ A0041
	3500 K	2770 lm	090-7Q92 ⇕ A0041
	4000 K	2830 lm	090-7Q91 ⇕ A0041

WALLWASHER FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
25.7 W	2700 K	3130 lm	090-7Q99 ⇕ W0 ◪ 41
	3000 K	3130 lm	090-7Q90 ⇕ W0 ◪ 41
	3500 K	3260 lm	090-7Q92 ⇕ W0 ◪ 41
	4000 K	3330 lm	090-7Q91 ⇕ W0 ◪ 41

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 10
DALI cable ø 4 – 12 mm	105·58·30	005-255111 10

Linect®-Ready

Mounting accessories (required)




MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	122·122·47	090-7Q90 100

for UNICO Q9

Order options

CONTROL	⇕	COLOUR	◪	COLOUR	
non DIM	1	chrome reflector	0	jet black	RAL 9005
DALI-2	3	black reflector	B	traffic white	RAL 9016



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	138·138·30	090-7Q9020B
traffic white	138·138·30	090-7Q9020W


for UNICO Q9

Mounting tools accessories (optional)

DISMOUNTING TOOL

L·W·H (mm)	ORDER CODE
70·30·2	090-002100

Electrical accessories (optional)



POWER SUPPLY pre-wired

Available in the configurator — see POWER SUPPLY PRE-WIRED

Order options

COLOUR

jet black	RAL 9005
traffic white	RAL 9016

Aertssen Group, Beveren

Belgique

Architecte
Mertens Architecten

Lighting Design
Eef Debeuf

Photographe
Kris Dekeijser



Produits utilisés



MINO 60 CIRCLE suspended



MOVE IT 25 surface / suspended system



SPOTLINE MOVE IT 25




JUST 45 MOVE IT 25 / 25 S / 45



UNICO Q9 recessed



UNICO L2 / L3 recessed



SASSO 60 round downlight recessed 1 lamp

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



















