


Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 16, UGR ≤ 19
jusqu'à 176 lm/W
L90 / 100000 h
DALI-2
IP20

Types





Colours



Insert



Répartition de la lumière



ENVIVA

track

EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; suitable for mounting in 3-phase power tracks; converter in the adapter; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; efficient LEDs with very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks

FR Corps de luminaire en profil extrudé en alu, version arête ; forme extrêmement élancée (seulement 45 x 15 mm) ; aucune vis visible ; surface brute ou thermolaquée ; adapté au montage sur des rails électriques triphasés ; convertisseur dans l'adaptateur ; insert lumineux linéaire en plastique ; équipé de points lumineux à LED simples ; bon anti-éblouissement grâce aux points lumineux en retrait ; malgré tout efficacité accrue grâce à une tech. de lentilles spéciale ; lentilles utilisées avec caractéristique de rayonnement wide flood ; ou réflecteur de grande qualité avec surface à microfacettes, métallisée à l'aluminium ; caractéristique d'émission précise avec répartition symétrique de la lumière ; LED économes en énergie à restitution de couleur élevée ; adaptateur pour installation ou déplacement sans outil dans différents rails triphasés



DIN EN 12464-1
UGR ≤ 16




up to 176 lm/W
(high efficiency)



ENVIVA lens track

CRI ≥90 | UGR ≤19 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | X-PERT | X-PERT




LENS DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.6 W	1204 mm	3000 K	80	3240 lm	165 lm/W	067-263453 ◪ W
			90	2820 lm	144 lm/W	067-263403 ◪ W
		4000 K	80	3450 lm	176 lm/W	067-263463 ◪ W
			90	2820 lm	144 lm/W	067-263413 ◪ W
24.8 W	1504 mm	3000 K	80	4100 lm	165 lm/W	067-263553 ◪ W
			90	3570 lm	144 lm/W	067-263503 ◪ W
		4000 K	80	4370 lm	176 lm/W	067-263563 ◪ W
			90	3570 lm	144 lm/W	067-263513 ◪ W



ENVIVA louver track

CRI ≥90 | UGR ≤19 | cd/m² ≤1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT




LOUVER DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.7 W	1204 mm	3000 K	80	3260 lm	165 lm/W	067-063453 ◪ ■ X
			90	2840 lm	144 lm/W	067-063403 ◪ ■ X
		4000 K	80	3470 lm	176 lm/W	067-063463 ◪ ■ X
			90	2840 lm	144 lm/W	067-063413 ◪ ■ X
25.1 W	1504 mm	3000 K	80	4120 lm	164 lm/W	067-063553 ◪ ■ X
			90	3590 lm	143 lm/W	067-063503 ◪ ■ X
		4000 K	80	4380 lm	175 lm/W	067-063563 ◪ ■ X
			90	3590 lm	143 lm/W	067-063513 ◪ ■ X



ENVIVA spotline track

CRI ≥90 | UGR ≤16 | cd/m² ≤1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT



SPOTLINE DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.7 W	1204 mm	3000 K	80	3180 lm	161 lm/W	067-163453 ◪ ■₁ W
			90	2770 lm	141 lm/W	067-163403 ◪ ■₁ W
		4000 K	80	3390 lm	172 lm/W	067-163463 ◪ ■₁ W
			90	2770 lm	141 lm/W	067-163413 ◪ ■₁ W
25.1 W	1504 mm	3000 K	80	4020 lm	160 lm/W	067-163553 ◪ ■₁ W
			90	3500 lm	139 lm/W	067-163503 ◪ ■₁ W
		4000 K	80	4280 lm	171 lm/W	067-163563 ◪ ■₁ W
			90	3500 lm	139 lm/W	067-163513 ◪ ■₁ W

Order options

COLOUR ◪		INSET ■		INSET ■₁	
aluminium raw	0	chrome reflector	4	traffic white RAL 9016	7
traffic white RAL 9016	7	black reflector	8	jet black RAL 9005	8
jet black RAL 9005	8				