




SASSO 100 square high efficient adjustable

recessed 2 lamps


EN Square recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; light insets tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

FR Spot carré encastrable ; montage sans outil en kit de montage par système à déclic à bille ; surface laquée ; avec bord continu ; biflamme ; modules d'éclairage orientable ; caractéristiques de rayonn. précises grâce à l'optique à lentille ; Technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI $\geq$ 90 / 2 SDCM (initial MacAdam)
UGR $\leq$ 10, UGR $\leq$ 13, UGR $\leq$ 16, UGR $\leq$ 19
jusqu'à 144 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non DIM
front IP40, back IP20

Types



Colours



Set de montage



Répartition de la lumière



glare control
(UGR $\leq$ 16)




60 mm
recessed depth



Colour Warm
Dimming 1800 –
3000 K



CRI $\geq$ 95 2
SDCM
(optional)



SASSO 100 square high efficient adjustable



SPOT 20°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.5 W, 36 Vf, 450 mA	2700 K	2x2060 lm	133 lm/W	0 4 8 - 2 7 3 3 9 1 ☒ S
	3000 K	2x2140 lm	138 lm/W	0 4 8 - 2 7 3 3 0 1 ☒ S
	4000 K	2x2180 lm	140 lm/W	0 4 8 - 2 7 3 3 1 1 ☒ S
2x17.3 W, 36 Vf, 450 mA	3500 K	2x2170 lm	126 lm/W	0 4 8 - 2 7 3 3 2 1 ☒ S
2x23.2 W, 36 Vf, 650 mA	2700 K	2x2740 lm	118 lm/W	0 4 8 - 2 7 3 3 9 1 ☒ S
	3000 K	2x2850 lm	123 lm/W	0 4 8 - 2 7 3 3 0 1 ☒ S
	4000 K	2x2890 lm	125 lm/W	0 4 8 - 2 7 3 3 1 1 ☒ S
2x25.8 W, 36 Vf, 650 mA	3500 K	2x2890 lm	112 lm/W	0 4 8 - 2 7 3 3 2 1 ☒ S

The data values for the luminous flux of fraction may differ for specific order options by -8%. Luminous flux value refers to colour traffic white. 2 insets necessary, order code only applies to 1 inset

MEDIUM 31°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.5 W, 36 Vf, 450 mA	2700 K	2x2070 lm	133 lm/W	0 4 8 - 2 7 3 3 9 1 ☒ M
	3000 K	2x2150 lm	139 lm/W	0 4 8 - 2 7 3 3 0 1 ☒ M
	4000 K	2x2180 lm	141 lm/W	0 4 8 - 2 7 3 3 1 1 ☒ M
2x17.3 W, 36 Vf, 450 mA	3500 K	2x2180 lm	126 lm/W	0 4 8 - 2 7 3 3 2 1 ☒ M
2x23.2 W, 36 Vf, 650 mA	2700 K	2x2750 lm	119 lm/W	0 4 8 - 2 7 3 3 9 1 ☒ M
	3000 K	2x2860 lm	124 lm/W	0 4 8 - 2 7 3 3 0 1 ☒ M
	4000 K	2x2910 lm	125 lm/W	0 4 8 - 2 7 3 3 1 1 ☒ M
2x25.8 W, 36 Vf, 650 mA	3500 K	2x2900 lm	112 lm/W	0 4 8 - 2 7 3 3 2 1 ☒ M

2 insets necessary, order code only applies to 1 inset

FLOOD 39°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.5 W, 36 Vf, 450 mA	2700 K	2x1970 lm	127 lm/W	0 4 8 - 2 7 3 3 9 1 ☒ F
	3000 K	2x2050 lm	132 lm/W	0 4 8 - 2 7 3 3 0 1 ☒ F
	4000 K	2x2080 lm	134 lm/W	0 4 8 - 2 7 3 3 1 1 ☒ F
2x17.3 W, 36 Vf, 450 mA	3500 K	2x2080 lm	120 lm/W	0 4 8 - 2 7 3 3 2 1 ☒ F
2x23.2 W, 36 Vf, 650 mA	2700 K	2x2620 lm	113 lm/W	0 4 8 - 2 7 3 3 9 1 ☒ F
	3000 K	2x2730 lm	118 lm/W	0 4 8 - 2 7 3 3 0 1 ☒ F
	4000 K	2x2770 lm	119 lm/W	0 4 8 - 2 7 3 3 1 1 ☒ F
2x25.8 W, 36 Vf, 650 mA	3500 K	2x2760 lm	107 lm/W	0 4 8 - 2 7 3 3 2 1 ☒ F

The data values for the luminous flux of fraction may differ for specific order options by -9%. Luminous flux value refers to colour traffic white. 2 insets necessary, order code only applies to 1 inset

WIDE FLOOD 56°, CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x15.5 W, 36 Vf, 450 mA	2700 K	2x2120 lm	136 lm/W	0 4 8 - 2 7 3 3 9 1 ☒ W
	3000 K	2x2200 lm	142 lm/W	0 4 8 - 2 7 3 3 0 1 ☒ W
	4000 K	2x2240 lm	144 lm/W	0 4 8 - 2 7 3 3 1 1 ☒ W
2x17.3 W, 36 Vf, 450 mA	3500 K	2x2230 lm	129 lm/W	0 4 8 - 2 7 3 3 2 1 ☒ W
2x23.2 W, 36 Vf, 650 mA	2700 K	2x2820 lm	121 lm/W	0 4 8 - 2 7 3 3 9 1 ☒ W
	3000 K	2x2930 lm	127 lm/W	0 4 8 - 2 7 3 3 0 1 ☒ W
	4000 K	2x2980 lm	128 lm/W	0 4 8 - 2 7 3 3 1 1 ☒ W
2x25.8 W, 36 Vf, 650 mA	3500 K	2x2970 lm	115 lm/W	0 4 8 - 2 7 3 3 2 1 ☒ W

2 insets necessary, order code only applies to 1 inset

Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L-W-H (mm)	ORDER CODE
218-118-35	0 4 8 - 2 7 9 9 3 1


Electrical accessories (required)

POWER SUPPLY PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
450 mA 21 W non DIM	198-264 V AC	η 86 %	143-43-30	0 0 2 - 9 0 7 6 6
450 mA 28 W DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 6 7
650 mA 100 W non DIM	176-264 V AC	η 92 %	143-43-30	0 0 2 - 9 0 7 8 0
650 mA 28 W DALI-2	176-264 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 8 9

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050mA settable const. current | 2x42W | 48V DC | U OUT 10-40V SELV

POWER SUPPLY PRE-WIRED with junction box 28 W, PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	ORDER CODE
450 mA DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 6 7 A
650 mA DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 8 9 A
700 mA DALI-2	176-264 V AC	η 85 %	0 0 2 - 9 0 7 7 6 A
450 mA non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 6 6 A
650 mA non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 8 0 A
700 mA non DIM	198-264 V AC	η 88 %	0 0 2 - 9 0 7 7 4 A

2 power supplies for 2 lamps variants necessary

Order options

COLOUR

traffic white RAL 9016	7
jet black RAL 9005	8
white aluminium RAL 9006	G