



UNICO L2 / L3 basic

recessed

EN Rectangular recessed multi-downlight made of die-cast aluminium; equipped with two (L2) / three (L3) individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25mm; surface powder coated; installation possible in different housings; high-quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering; clank-free

IT Downlight multiplo rettangolare da incasso in alluminio pressofuso; dotata di due (L2) / tre (L3) lenti selezionabili individualmente o definite per applicazioni specifiche; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili; montaggio elettrico semplice grazie a collegamenti a spina a prova di polarizzazione inversa; per soffitti di spessore 2-25mm; verniciatura a polvere; incasso possibile in vari telai; riflettore di alta qualità con superficie a microfaccette e vaporizzata in alluminio; emissione precisa con diversi fasci luminosi simmetrici; o con distribuzione asimmetrica della luce; LED high power a risparmio energetico con ottima resa cromatica; senza distorsione

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 3 SDCM
UGR ≤ 10 , UGR ≤ 16 , UGR ≤ 19
fino a 132 lm/W
L85 / 50000 h, L90 / 50000 h
DALI-2, non DIM
front IP20

Types

trim	trimless
	
138x63	122x47
	
101x63	85x47

Colore



Set di montaggio



Distribuzione della luce




DiiA® standards
251, 252, 253



one luminaire
multiple scenes




plug / socket
connector



black & gold
reflector
(optional)



tunable white
2700 – 5000 K
(optional)



UNICO L2 basic high efficient



FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
6.0 W	2700 K	663 lm	111 lm/W	0 9 0 - 7 L 2 9 ◆ C 0 3 1
	3000 K	690 lm	115 lm/W	0 9 0 - 7 L 2 0 ◆ C 0 3 1
	3500 K	690 lm	115 lm/W	0 9 0 - 7 L 2 2 ◆ C 0 3 1
	4000 K	718 lm	120 lm/W	0 9 0 - 7 L 2 1 ◆ C 0 3 1

WIDE FLOOD ROUND CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
6.0 W	2700 K	682 lm	114 lm/W	0 9 0 - 7 L 2 9 ◆ D 0 3 1
	3000 K	710 lm	118 lm/W	0 9 0 - 7 L 2 0 ◆ D 0 3 1
	3500 K	710 lm	118 lm/W	0 9 0 - 7 L 2 2 ◆ D 0 3 1
	4000 K	739 lm	123 lm/W	0 9 0 - 7 L 2 1 ◆ D 0 3 1

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
6.0 W	2700 K	696 lm	116 lm/W	0 9 0 - 7 L 2 9 ◆ F 0 3 1
	3000 K	725 lm	121 lm/W	0 9 0 - 7 L 2 0 ◆ F 0 3 1
	3500 K	725 lm	121 lm/W	0 9 0 - 7 L 2 2 ◆ F 0 3 1
	4000 K	754 lm	126 lm/W	0 9 0 - 7 L 2 1 ◆ F 0 3 1

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
6.0 W	2700 K	715 lm	119 lm/W	0 9 0 - 7 L 2 9 ◆ G 0 3 1
	3000 K	745 lm	124 lm/W	0 9 0 - 7 L 2 0 ◆ G 0 3 1
	3500 K	745 lm	124 lm/W	0 9 0 - 7 L 2 2 ◆ G 0 3 1
	4000 K	775 lm	129 lm/W	0 9 0 - 7 L 2 1 ◆ G 0 3 1



UNICO L2 basic



SPOT ROUND CRI ≥ 90, chrome reflector

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	408 lm	56 lm/W	0 9 0 - 7 L 2 4 ◆ K 0 0 2 1
	3000 K	435 lm	60 lm/W	0 9 0 - 7 L 2 5 ◆ K 0 0 2 1
	4000 K	467 lm	64 lm/W	0 9 0 - 7 L 2 6 ◆ K 0 0 2 1

NARROW MEDIUM ROUND CRI ≥ 90, chrome reflector

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	415 lm	57 lm/W	0 9 0 - 7 L 2 4 ◆ N 0 0 2 1
	3000 K	442 lm	61 lm/W	0 9 0 - 7 L 2 5 ◆ N 0 0 2 1
	4000 K	475 lm	65 lm/W	0 9 0 - 7 L 2 6 ◆ N 0 0 2 1

MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	555 lm	76 lm/W	0 9 0 - 7 L 2 4 ◆ B 0 2 1
	3000 K	591 lm	81 lm/W	0 9 0 - 7 L 2 5 ◆ B 0 2 1
	4000 K	634 lm	87 lm/W	0 9 0 - 7 L 2 6 ◆ B 0 2 1

Order options

CONTROL

non DIM

DALI-2



1

3

COLOUR

chrome reflector







black reflector









0

B







FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	638 lm	87 lm/W	0 9 0 - 7 L 2 4  C 0  2 1
	3000 K	680 lm	93 lm/W	0 9 0 - 7 L 2 5  C 0  2 1
	4000 K	729 lm	100 lm/W	0 9 0 - 7 L 2 6  C 0  2 1







WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	632 lm	87 lm/W	0 9 0 - 7 L 2 4  D 0  2 1
	3000 K	673 lm	92 lm/W	0 9 0 - 7 L 2 5  D 0  2 1
	4000 K	722 lm	99 lm/W	0 9 0 - 7 L 2 6  D 0  2 1







MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	545 lm	75 lm/W	0 9 0 - 7 L 2 4  E 0  2 1
	3000 K	581 lm	80 lm/W	0 9 0 - 7 L 2 5  E 0  2 1
	4000 K	623 lm	85 lm/W	0 9 0 - 7 L 2 6  E 0  2 1







FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	648 lm	89 lm/W	0 9 0 - 7 L 2 4  F 0  2 1
	3000 K	691 lm	95 lm/W	0 9 0 - 7 L 2 5  F 0  2 1
	4000 K	741 lm	102 lm/W	0 9 0 - 7 L 2 6  F 0  2 1




RECTANGULAR MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	562 lm	77 lm/W	0 9 0 - 7 L 2 4  R 0  2 1
	3000 K	600 lm	82 lm/W	0 9 0 - 7 L 2 5  R 0  2 1
	4000 K	643 lm	88 lm/W	0 9 0 - 7 L 2 6  R 0  2 1







WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	666 lm	91 lm/W	0 9 0 - 7 L 2 4  G 0  2 1
	3000 K	710 lm	97 lm/W	0 9 0 - 7 L 2 5  G 0  2 1
	4000 K	762 lm	104 lm/W	0 9 0 - 7 L 2 6  G 0  2 1

WALLWASHER CRI ≥ 90, chrome reflector



SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	564 lm	77 lm/W	0 9 0 - 7 L 2 4  A 0 0 2 2
	3000 K	601 lm	82 lm/W	0 9 0 - 7 L 2 5  A 0 0 2 2
	4000 K	645 lm	88 lm/W	0 9 0 - 7 L 2 6  A 0 0 2 2

WALL FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.3 W	2700 K	588 lm	81 lm/W	0 9 0 - 7 L 2 4  W 0  2 2
	3000 K	627 lm	86 lm/W	0 9 0 - 7 L 2 5  W 0  2 2
	4000 K	672 lm	92 lm/W	0 9 0 - 7 L 2 6  W 0  2 2

Order options

CONTROL		COLOUR	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B



UNICO L3 basic high efficient



FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
8.8 W	2700 K	994 lm	113 lm/W	0 9 0 - 7 L 3 9 ◆ C 0 3 1
	3000 K	1040 lm	118 lm/W	0 9 0 - 7 L 3 0 ◆ C 0 3 1
	3500 K	1040 lm	118 lm/W	0 9 0 - 7 L 3 2 ◆ C 0 3 1
	4000 K	1080 lm	123 lm/W	0 9 0 - 7 L 3 1 ◆ C 0 3 1

WIDE FLOOD ROUND CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
8.8 W	2700 K	1020 lm	116 lm/W	0 9 0 - 7 L 3 9 ◆ D 0 3 1
	3000 K	1070 lm	122 lm/W	0 9 0 - 7 L 3 0 ◆ D 0 3 1
	3500 K	1070 lm	122 lm/W	0 9 0 - 7 L 3 2 ◆ D 0 3 1
	4000 K	1110 lm	126 lm/W	0 9 0 - 7 L 3 1 ◆ D 0 3 1

FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
8.8 W	2700 K	1040 lm	118 lm/W	0 9 0 - 7 L 3 9 ◆ F 0 3 1
	3000 K	1090 lm	124 lm/W	0 9 0 - 7 L 3 0 ◆ F 0 3 1
	3500 K	1090 lm	124 lm/W	0 9 0 - 7 L 3 2 ◆ F 0 3 1
	4000 K	1130 lm	128 lm/W	0 9 0 - 7 L 3 1 ◆ F 0 3 1

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
8.8 W	2700 K	1070 lm	122 lm/W	0 9 0 - 7 L 3 9 ◆ G 0 3 1
	3000 K	1120 lm	127 lm/W	0 9 0 - 7 L 3 0 ◆ G 0 3 1
	3500 K	1120 lm	127 lm/W	0 9 0 - 7 L 3 2 ◆ G 0 3 1
	4000 K	1160 lm	132 lm/W	0 9 0 - 7 L 3 1 ◆ G 0 3 1



UNICO L3 basic



SPOT ROUND CRI ≥ 90, chrome reflector

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	585 lm	60 lm/W	0 9 0 - 7 L 3 4 ◆ K 0 0 2 1
	3000 K	623 lm	64 lm/W	0 9 0 - 7 L 3 5 ◆ K 0 0 2 1
	4000 K	669 lm	68 lm/W	0 9 0 - 7 L 3 6 ◆ K 0 0 2 1

NARROW MEDIUM ROUND CRI ≥ 90, chrome reflector

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	594 lm	61 lm/W	0 9 0 - 7 L 3 4 ◆ N 0 0 2 1
	3000 K	633 lm	65 lm/W	0 9 0 - 7 L 3 5 ◆ N 0 0 2 1
	4000 K	680 lm	69 lm/W	0 9 0 - 7 L 3 6 ◆ N 0 0 2 1

MEDIUM ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	794 lm	81 lm/W	0 9 0 - 7 L 3 4 ◆ B 0 2 1
	3000 K	847 lm	86 lm/W	0 9 0 - 7 L 3 5 ◆ B 0 2 1
	4000 K	908 lm	93 lm/W	0 9 0 - 7 L 3 6 ◆ B 0 2 1

Order options

CONTROL		COLOUR	
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B

FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	913 lm	93 lm/W	0 9 0 - 7 L 3 4 ◆ C 0 2 1
	3000 K	974 lm	99 lm/W	0 9 0 - 7 L 3 5 ◆ C 0 2 1
	4000 K	1040 lm	106 lm/W	0 9 0 - 7 L 3 6 ◆ C 0 2 1

WIDE FLOOD ROUND CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	905 lm	92 lm/W	0 9 0 - 7 L 3 4 ◆ D 0 2 1
	3000 K	964 lm	98 lm/W	0 9 0 - 7 L 3 5 ◆ D 0 2 1
	4000 K	1030 lm	105 lm/W	0 9 0 - 7 L 3 6 ◆ D 0 2 1

MEDIUM SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	781 lm	80 lm/W	0 9 0 - 7 L 3 4 ◆ E 0 2 1
	3000 K	832 lm	85 lm/W	0 9 0 - 7 L 3 5 ◆ E 0 2 1
	4000 K	893 lm	91 lm/W	0 9 0 - 7 L 3 6 ◆ E 0 2 1

FLOOD SQUARE CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	929 lm	95 lm/W	0 9 0 - 7 L 3 4 ◆ F 0 2 1
	3000 K	990 lm	101 lm/W	0 9 0 - 7 L 3 5 ◆ F 0 2 1
	4000 K	1060 lm	108 lm/W	0 9 0 - 7 L 3 6 ◆ F 0 2 1

WIDE FLOOD SQUARE CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	954 lm	97 lm/W	0 9 0 - 7 L 3 4 ◆ G 0 2 1
	3000 K	1020 lm	104 lm/W	0 9 0 - 7 L 3 5 ◆ G 0 2 1
	4000 K	1090 lm	111 lm/W	0 9 0 - 7 L 3 6 ◆ G 0 2 1


WALLWASHER CRI ≥ 90, chrome reflector

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.8 W	2700 K	807 lm	82 lm/W	0 9 0 - 7 L 3 4 ◆ A 0 0 2 1
	3000 K	861 lm	88 lm/W	0 9 0 - 7 L 3 5 ◆ A 0 0 2 1
	4000 K	924 lm	94 lm/W	0 9 0 - 7 L 3 6 ◆ A 0 0 2 1

Electrical mounting accessories (optional)**THROUGH WIRING CONNECTION BOX**


TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)**MOUNTING SET trimless**

TYPE	L-W-H (mm)	ORDER CODE
for plasterboard ceilings 12.5/15/20/25 mm	85-47-47	0 9 0 - 7 L 2 0 1 0 0

for UNICO L2 and UNICO wall recessed 1 lamp

**MOUNTING SET trimless**

TYPE	L-W-H (mm)	ORDER CODE
for plasterboard ceilings 12.5/15/20/25 mm	122-47-47	0 9 0 - 7 L 3 0 1 0 0

for UNICO L3

Order options

CONTROL	◆	COLOUR	■
non DIM	1	chrome reflector	0
DALI-2	3	black reflector	B



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	101-63-30	0 9 0 - 7 L 2 0 2 0 B
traffic white	101-63-30	0 9 0 - 7 L 2 0 2 0 W

for UNICO L2 and UNICO wall recessed 1 lamp



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	138-63-30	0 9 0 - 7 L 3 0 2 0 B
traffic white	138-63-30	0 9 0 - 7 L 3 0 2 0 W

for UNICO L3

Benaki Museum Shop, Navarino AgoraBenaki Museum Shop, Athens

Grecia

Architetto

STUDIOLAV and
Kostantia Manthou

Fotografo

Manos Chatzikonstantis



Prodotti utilizzati



**UNICO L2 / L3 basic
recessed**





Forschungsbau Weltbeziehungen Universität Erfurt

Germania

Lighting Design

lichtraum

Fotografo

Steven Neukirch

Fotografie



Prodotti utilizzati



LENO surface



**UNICO L2 / L3 basic
recessed**

